



TECHNICAL DATA SHEET

ANTI SLIP SF-288

100% ACRYLIC LATEX SANDED FLOOR PAINT

PRODUCT

DESCRIPTION: A high performance, water-based, 100% acrylic latex and sanded paint designed to withstand the heavy traffic of floors and prevent potentially harmful or dangerous slips.

BASIC USES: Ideal for interior or exterior surfaces such as wood, metal and concrete; excellent for basement floors, porches, decks, patios, steps, etc.

PRODUCT

ADVANTAGES:

* Fade resistant	* Abrasion resistant
* One-coat hiding	* Water cleanup
* No flame hazard	* Oil and grease resistant

COLORS: Available in six ready-mixed colors and 4 tint bases.

TECHNICAL DATA

Solids:	59.00 ± 1% by weight 45.00 ± 1% by volume	Finish:	Flat (2° - 5°)* *Geometry 60°
Weight / Gallon:	11.20 ± 0.5 lbs.	Viscosity:	70 - 80 Ku's
Flash Point:	Non-flammable	Percent Pigment by Weight:	37.80 ± 1%
Theoretical Coverage:	Up to 700 sq. / ft. per gallon @ 1 mil	Drying Time:	To touch: 1 hr. To recoat: 5 hrs.
Recommended Coverage:	465 sq. / ft. @ 1.5 dry mils, 3.3 wet mils	Sizes:	5 gallons 1 gallon
Thinning:	Not recommended.		

Surface Preparation: All surfaces must be dry, clean and free of contaminants such as dirt, grease, chalk, mildew, oil, rust, and loose or badly cracked paint. Dull glossy surfaces by lightly sanding.

New Surfaces: UNPAINTED EXTERIOR WOOD must be weathered at least sixty days prior to the application of *LANCO® Anti Slip™*. UNPAINTED CONCRETE must be fully cured (thirty days) and acid-etched prior to the application of *LANCO® Anti Slip™*. (For acid-etching, use one pint of *CROSSCO® Cross-Crete™* diluted in one gallon of water; follow label directions). Rinse thoroughly and let dry.

Application: Intermix all gallons of the same color in order to insure color uniformity; stir gently. Apply liberally, rolling out no more than a two feet by two feet area at a time with a *LANCO® 1/4" Nap Enamel Roller PA-565*.

Note: Surface should be let to dry eighteen hours before being ready to take light foot traffic. Drying time may be extended with variations in temperatures and/or humidity.

Precaution: Do not apply when air temperature is below 60° F (15°C). Avoid painting in direct sunlight. Do not apply late in the day or when rain or dew is likely.

Washing: For proper curing of finish, do not wash or let water sit on painted surface before 14 days have lapsed. Thereafter, wash with mild detergent and a soft cloth or sponge mop, and rinse. *Do not use abrasive cleaners.*

Cleanup: Clean brushes, roller, or spray equipment with warm soapy water immediately after use. Seal partially used cans to prevent skinning.

Caution: Harmful if swallowed. Contains acrylic resin. Use only with adequate ventilation. Avoid prolonged or repeated breathing of vapor. Keep out of reach of children.

Notice: The technical data contained herein are true and accurate to the best of our knowledge. Published technical data and instructions are subject to change without prior notice.

M.S.D.S.: Available upon request.