



TECHNICAL DATA SHEET

ACRYLIC LATEX TRAFFIC PAINT™ ACRYLIC WATERBORNE MARKING PAINT

PRODUCT

DESCRIPTION: A quick drying, acrylic latex ready-to-use marking paint of high visibility for asphalt, concrete, brick and other surfaced highways and uncured asphalt and driveways; conforms to the U.S. Bureau of Public Roads colors.

BASIC USES: For industrial, commercial and residential use on new or previously painted asphalt, concrete, brick and other surfaced highways.

PRODUCT

ADVANTAGES:

* Quick-drying	* Durable and tough
* Stain and chip resistant	* Non-flammable
* No primer or undercoater necessary	* Easy to clean
	* Excellent coverage

COLORS: Available in white, yellow, and (handicap) blue.

TECHNICAL DATA

Percent Solids: 55 ±1 % by weight
35 ±1 % by volume

Finish: Flat (2°-5°)*

Weight / Gallon: 11.84 ± .10 lbs.

Viscosity: 80–90 Ku's

Flash Point: Non-flammable

Sizes: 55 gallons
5 gallons
1 gallon

Drying Time: To touch: 25 minutes
To recoat: 45 minutes

Percent Pigment by Weight: 44 ± 1%

Colors: Yellow (TP-115)
White (TP-116)
Blue (TP-117)

Theoretical Coverage: 15 gallons per mile of standard 4 inch strip, or 350 linear feet of standard 4 inch strip per gallon at an average wet film of 0.0014 inches.

Thinning: Not normally recommended, but if necessary, reduce with up to one quart of water.

Surface Preparation: Surface must be dry and free of contaminants such as dirt, grease, oil or grit. No primer or undercoat is necessary. Do not paint on wet surfaces or when humidity is below 85%, nor when temperature is below 50° F (10° C). When applied over emulsified coal tar compound, the surface should be allowed to age seven days before striping.

Application Method:

BRUSH: Use a good quality nylon or polyester brush.

ROLLER: Use a *LANCO® 1 1/4" Nap Extra-Rough Roller PA-567*, or any adequate marking equipment.

Mixing: Always mix thoroughly with a power agitator before application.

Cleanup: Clean all equipment immediately after use with warm soapy water. Completely flush spray equipment with this solution.

Precaution: Do not apply when air or surface temperature is below 50° F (10° C). Apply liberally, but do not overspread. Stop painting at least two hours before dew is expected to form or the temperature to fall below 50° F (10° C).

Caution: Do not take internally. Close container after each use. Keep out of reach of children. Use with adequate ventilation.

Notice: The technical data contained herein are true and accurate to the best of our knowledge. Published technical data and instructions are subject to change without prior notice.

M.S.D.S.: Available upon request.