



TRANSITION™

CEILING PAINT

PRODUCT

DESCRIPTION: Lanco® Transition Ceiling Paint™ is the easiest way to paint your ceilings without missing spots. It is an acrylic flat paint that has a revolutionary tint system which gives the paint a light purple color at the moment of application and becomes bright white once it dries, allowing you to see exactly what you are painting .

BASIC USES: This state of the art technology minimizes the amount of spots you may miss if you painted with a traditional white paint. Use to paint the ceiling without the messy consequence of painting vertically.

PRODUCT

ADVANTAGES:

- * Splatter resistant
- * One coat coverage
- * Eliminates missed spots
- * Resist chipping, cracking and peeling
- * Non-yellowing film
- * Mildew resistant

TECHNICAL DATA

Percent Solids:	51.6 ± 1%	Finish:	flat (5° - 10°) Geometry 60°
Weight / Gallon:	11.84 ± 0.05 lbs	Percent Pigment by Weight:	43.4 ± 1%
Color:	Purple on application; Ultra white in 30 minutes	Flash Point:	Non-Flammable
Drying Time:	To touch: 1 hour To recoat: 5 hours	Theoretical Coverage:	561 sq. ft. / gal. @ 1 mil dry, 2.9 mil wet
Recommended Coverage:	374 sq. ft. / gal. @ 1.5 mil dry, 4.3 mil wet	Sizes:	5 gallons 1 gallon
Thinning:	Not normally recommended, but if necessary, add water up to 1/2 pint per gallon.		

Surface preparation

1. Remove Loose Paint: Multi-coat peeling can be caused by adhesion failure in older paints. Remove all loose or peeling paint to provide a sound surface. Glossy Surfaces- Lightly sand, or apply Lanco® Stain Killer WP-039 previous to new paint application.
2. Wash and Rinse: Wash surfaces to remove dirt. Remove existing mildew before priming or painting to prevent re-growth through the new paint film. Mildew Removal: Scrub mildewed surfaces with a mixture of 1 quart household bleach and 3 quarts warm water. Use long handled brush. Rinse completely. CAUTION: Read warnings on label. Wear rubber gloves and safety glasses.
3. Patch: Patch all holes with Lanco® Spackling Compound and seal cracks with Lanco® Siliconizer Crack Filler.

Recommended paint systems:

Concrete- Let new concrete cure for 30 days. Prime with Lanco® Stain Killer Primer WP-039.

Wood- Prime with Lanco® Wall-Prep White Alkyd Binder WP-825.

Plywood- Prime with Lanco® Stain Killer Primer WP-039.

Composition Materials- Prime with Lanco® Stain Killer Primer WP-039.

Vinyl Siding- No primer needed. Do not paint with any color darker than the original siding color. Painting with darker colors may cause the siding to warp.

Aluminum Siding- Prime with Lanco® Durex Waterbase Primer DE-730.

Galvanized Metal- Clean with a degreaser, rinse and allow to dry; welded or abraded areas must be spot primed with Lanco® Galvacon GC-243. Prime the entire surface using Lanco® Galvanized Primer SG-664.

Steel- Prime with Lanco® Polyurethane Red Oxide Primer MM-100.

Application:

- Stir thoroughly before using.
- Paint always on shaded side of the building.
- Do not dilute paint, use as supplied.
- Do not apply when surface or air temperature is below 50° F or if rain is expected within 5 hours.
- Apply product with brush, roller or sprayer.
- Apply generously with a full brush or roller and avoid excessive brushing or spreading too thinly. If you use a roller we recommend a synthetic cover.
- When working with more than one container of the same color, intermix them to ensure uniformity.

Coverage: One gallon covers up to 450 square feet on smooth surfaces; up to 300 square feet on rough, porous or textured surfaces, which may require two coats.

Clean up: Use warm, soapy water immediately.

Drying time: To touch: 1 hour - To Recoat: 5 hours

Contains agents which inhibit the growth of mildew on the surface of this paint film.

Important: It is important that you apply one coat of primer and two full coats of paint to achieve the warranty protection.

Caution: Harmful if swallowed. Contains Acrylic Resin. In case of eye contact, flush thoroughly with water. Do not rub eyes. In case of skin contact, flush area immediately with clean water. If swallowed, do not induce vomiting.

Consult a physician immediately. Use only with adequate ventilation. Adequate ventilation required when sanding or abrading the dried film. Always use (NIOSH/MSHA TC21C or equivalent). Goggles are recommended while handling the product. KEEP OUT OF REACH OF CHILDREN.

Warning! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting The National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Protect from freezing. For Chemical Emergency Call ChemTrec 1-800-424-9300

10 years guaranteed - Lanco warrants your complete satisfaction for 10 years from date of application, when two coats of this product are applied over prepared and primed surface according to label directions, for as long as you continue residence in your home. Lanco warrants that this product: • Will not peel or blister • Will not stain • Will resist normal washing and scrubbing. If this product fails to perform as above explained, when used according to label direction, upon proof of purchase, Lanco will furnish either an equivalent amount of product at no cost or will refund the purchase price. This warranty gives you specific legal rights. You may also have other rights, which vary from state to state. EXCLUSIONS - Fires, construction, hurricanes, floods, tornados damages, or other unusual weather events are not covered in this warranty. This warranty does not include labor or cost of labor for the application of any product. This warranty does not apply to commercial jobs, for these purposes call Lanco® (506) 438-2257.