



## ACRYLIC CAULK CC-753

### ACRYLIC LATEX SEALANT 7-Year Warranty

#### PRODUCT

**DESCRIPTION:** A good quality latex caulk suitable for all interior and exterior applications where minimum joint movement is expected; adheres to most building materials and is easy to apply, tool and clean up.

#### BASIC USES:

Ideal to seal cracks around doors and window frames, baseboard trim and other areas where joint movement is minimal; excellent for sealing cracks in concrete, drywall and wood.

#### PRODUCT

#### ADVANTAGES:

- \* 100% paintable
- \* Water cleanup
- \* Seven-year warranty
- \* Mildew resistant
- \* Moisture resistant
- \* Interior / exterior
- \* All-purpose
- \* Long-lasting

### TECHNICAL DATA

<b>Percent Solids:</b>	72.00 ± 1% by weight 58.00 ± 1% by volume	<b>Finish:</b>	White
<b>Weight / Gallon:</b>	12.73 ± 1 lb.	<b>Viscosity:</b>	350,000 – 400,000 cps
<b>Drying Time:</b>	Tack free: 15 minutes To coat with latex paint: 2 hours To coat with alkyd paint: 24 hours	<b>Percent Pigment by Weight:</b>	51.00 ± 1%
<b>Sizes:</b>	10.1 fl. oz. cartridge (CC-753) 5.5 fl. oz. tube (TP-868)	<b>Flash Point:</b>	Non-flammable
<b>Theoretical Coverage:</b>	Approximately 34 linear feet of 1/4" bead per 10.1-oz. cartridge.		

**Surface Preparation:** All surfaces must be free of dust, dirt, grease and mildew. Remove all loose or badly cracked sealant and paint.

**Mildewed Surfaces:** Any existing mildew on the surface must be completely killed and removed prior to the application of new caulk. Using a long-handled brush, scrub mildewed surface with a mixture of one quart of household bleach and three quarts of warm water. Rinse thoroughly and let dry completely.

**Previously Caulked Surfaces:** It is critical to remove as much old sealant as possible before applying new caulk, especially if it is cracked, eroded or pulled away from the joint.

**Application Instructions:** For best results, follow these steps.

- (1) Apply at temperatures above 40°F (5°C) and when no precipitation is expected within 72 hours.
- (2) Cut nozzle to desired bead size (1/4" is recommended).
- (3) Hold gun at 45° angle to the seam and push *LANCO® Acrylic Caulk CC-753* ahead of nozzle, applying uniform pressure to the trigger in order to get a smooth bead.
- (4) Tool within 15 minutes with finger or damp smooth sponge.
- (5) Limit joint size to be filled to approximately 1/4" (0.6 cm) deep by 1/4" (0.6 cm) wide. If depth of joint exceeds 3/8", use polyethylene foam or oakum as backup filler.
- (6) Wipe away excess with a damp cloth before surface skins.

**Drying Time:** Wait two hours before painting with latex paint or 24 hours if using alkyd (oil based) paint.

**Cleanup:** Clean up excess with damp cloth before caulk cures.

**Coverage:** Approximately 34 linear feet of 1/4" bead per 10.1-oz. cartridge.

**Storage:** Protect from freezing; store in a cool, dry place at room temperature. Product must be used within one year of purchase.

**Note:** Always use a sealer such as shellac before topcoating with a lacquer. Not recommended for use on horizontal surfaces where water may collect, or for marine use or areas below water level.

**Limited Warranty:** Satisfaction guaranteed for seven years. If product cracks, peels or separates while you own your home during period of guarantee, when used as directed, return sales receipt and used container to *LANCO®* Mfg. Corporation, Customer Service Dept., Urb. Aponte #5, San Lorenzo, PR 00754 for product replacement. The seller will not accept liability for more than product replacement or purchase price.

**Notice:** The technical data contained herein are true and accurate to the best of our knowledge. Published technical data and instructions are subject to change without prior notice.

**M.S.D.S.:** Available upon request.