



ACRYLIC PLUS CAULK™

CC-757

ELASTOMERIC ACRYLIC SEALANT

30-Year Warranty

(ASTM C 834-91)

PRODUCT

DESCRIPTION:

A one-component, non-staining high performance sealant with excellent resistance to air and moisture penetration and UV rays that cures into a flexible rubber and gasket that will not crack, even after many years of outdoor exposure; can be painted over shortly after application with latex or oil paint.

BASIC USES:

Suitable for most interior or exterior applications. Seals cracks on concrete, drywall and wood; excellent for caulking around doors and window frames, siding corner joints, skylights, vents, air ducts and chimneys, where joint movement is moderate.

PRODUCT

ADVANTAGES:

- * Seals cracks in concrete
- * 100% paintable in two hours
- * 100% water cleanup
- * Mildew and moisture resistant
- * 100% flexible
- * 100% exterior / interior
- * 100% elastomeric
- * Non-yellowing white finish

TECHNICAL DATA

Percent Solids:

70.00 ± 1% by weight
58.00 ± 1% by volume

Color:

Ultra white

Weight / Gallon:

11.65 ± 0.5 lbs.

Viscosity:

300,000 – 350,000 cps.

Drying Time:

Tack free: 15 minutes
To coat with latex paint: 2 hours
To coat with alkyd paint: 24 hours

Percent Pigment

by Weight: 41.00 ± 1%

Flash Point:

Non-flammable

Sizes:

10.1 oz. cartridge

Theoretical

Coverage:

Approximately 34 linear feet of 1/4" bead per 10.1-oz. cartridge.

Surface Preparation: Surfaces must be free of dust, dirt, grease and mildew. Remove all loose or badly cracked sealant.

Mildewed Surfaces: Any existing mildew on the surface must be completely killed and removed prior to the application of new caulk. Using a long-handled brush, scrub mildewed surface with a mixture of one quart of household bleach and three quarts of warm water. Rinse thoroughly and let dry completely.

Previously Caulked Surfaces: It is critical to remove as much old sealant as possible before applying new caulk, specially if it is cracked, eroded or pulled away from the joint.

Application Instructions: For best results, follow these steps:

- (1) Apply at temperatures above 40°F (5°C) and when no precipitation is expected within 72 hours.
- (2) Cut nozzle to desired bead size (1/4" is recommended).
- (3) Hold gun at 45° angle to the seam and push *LANCO® Acrylic Plus Caulk™ CC-757* ahead of nozzle, applying uniform pressure to the trigger in order to get a smooth bead.
- (4) Tool within 15 minutes with finger or damp smooth sponge.
- (5) Limit joint size to be filled to approximately 3/8" x 3/8". If depth of joint exceeds 3/8", use polyethylene foam or oakum as backup filler.
- (6) Wipe away excess with a damp cloth before surface skins.

Drying Time: Wait two hours before painting with latex paint; 24 hours if using alkyd (oil based) paint.

Coverage: Approximately 34 linear feet of 1/4" bead per 10.1-oz. cartridge.

Cleanup: Clean up excess with damp cloth before caulk cures.

Storage: Protect from freezing; store in a cool, dry place at room temperature. Product must be used within one year of purchase.

Note: Always use a sealer such as shellac before topcoating with a lacquer. Not recommended for use on horizontal surfaces where water may collect, nor for marine use or areas below water grade level.

Limited Warranty: Satisfaction guaranteed for thirty years. If product cracks, peel or separates while you own your home during period of guarantee, when used as directed, return sales receipt and used container to *LANCO®* Mfg. Corporation, Customer Service Dept., Urb. Aponte #5, San Lorenzo, PR 00754 for product replacement. Seller will not accept liability for more than product replacement or purchase price.

Notice: The technical data contained herein are true and accurate to the best of our knowledge. Published technical data and instructions are subject to change without prior notice.

M.S.D.S.: Available upon request