



## SILICONFLEX™

CC-766 • CC-767 • CC-768 • CC-769 • CC-770 • CC-771

HIGH PERFORMANCE SILICONIZED ACRYLIC SEALANTS

40-Year Warranty

(ASTM C 834-91)

### PRODUCT

**DESCRIPTION:** A one-component, high-performance, elastomeric sealant with the permanent adhesion and UV resistant properties of acrylic plus the permanent flexibility and lifetime durability of silicone. A high quality caulk will not crack, crumble or peel, even when exposed to severe weather or total joint movement; for interior or exterior use.

**BASIC USES:** Provides a waterproof and weatherproof seal, adhering tightly even to ceramic and glass substrates. Excellent for siding corner joints and caulking around windows, doors, skylights, vents, air ducts and chimneys.

### PRODUCT

- ADVANTAGES:**
- \* Interior / exterior
  - \* 40-year warranty
  - \* Non-yellowing
  - \* Seals in concrete, drywall, wood and metal
  - \* 100% odor free
  - \* 100% flexible
  - \* 100% silicone durability
  - \* 100% paintable in two hours
  - \* Mildew and moisture resistant

### TECHNICAL DATA

<b>Percent Solids:</b>	(Clear)	59.56 ± 1% by weight	<b>Colors:</b>	Clear	(CC-766)
		55.59 ± 1% by volume		White	(CC-767)
	(Colors)	82.02 ± 1% by weight		Almond	(CC-768)
		70.00 ± 1% by volume		Black	(CC-769)
<b>Weight /Gallon:</b>		8.86 ± 0.5 lbs		Bronze	(CC-770)
					Brown
<b>Flash Point:</b>	Non-flammable		<b>Viscosity:</b>	250,000 – 275,000 cps.	
<b>Drying Time:</b>	To touch: 15 minutes		<b>Sizes:</b>	10.1-oz. cartridge	
	To coat with latex paint: 2 hours				
	To coat with alkyd paint: 24 hours				
<b>Theoretical Coverage:</b>	Approximately 34 linear feet of 1/4" bead per 10.1-oz. cartridge.				

**Surface Preparation:** Surface must be free of dust, dirt, grease and mildew. Remove all loose or badly cracked sealant and paint.

**Mildewed Surfaces:** Any existing mildew on the surface must be completely killed and removed prior to the application of new caulk. Using a long-handled brush, scrub mildewed surface with a mixture of one quart of household bleach and three quarts of warm water., Rinse completely and let dry.

**Previously Caulked Surfaces:** It is critical to remove as much old sealant as possible before applying new caulk, specially if it is cracked, eroded or pulled away from the joint.

**Application Instructions:** For best results, follow these steps:

- (1) Apply at temperatures above 40°F (5°C) and when no precipitation is expected within 72 hours.
- (2) Cut nozzle to desired bead size (1/4" is recommended).
- (3) Hold gun at 45° angle to the seam and push *LANCO® SiliconFlex Caulk™* ahead of nozzle, applying uniform to the trigger in order to get a smooth bead.
- (4) Tool within 15 minutes with wet finger or damp smooth sponge.
- (5) Limit joint size to be filled to approximately 3/8" x 3/8". If depth of joint exceeds 3/8", use polyethylene foam or oakum as backup filler.
- (6) Wipe away excess with a damp cloth before surface skins.

**Note:** *LANCO® SiliconFlex (Clear) Caulk™ CC-766* guns out white but will dry clear; maximum clarity after thirteen days.

**Drying Time:** Wait two hours before painting with latex paint; 24 hours if using alkyd (oil based) paint.

**Cleanup:** Clean up excess with damp cloth before caulk cures.

**Coverage:** Approximately 34 linear feet of 1/4" bead per 10.1-oz. cartridge.

**Storage:** Protect from freezing; store in a cool, dry place at room temperature. Product must be used within one year of purchase.

**Note:** Always use a sealer such as shellac, before topcoating with a lacquer. Not recommended for use on horizontal surfaces where water may collect, or for marine use on areas below water level.

**Limited Warranty:** Satisfaction guaranteed for forty years. If product cracks, peels or separates while you own your home during period of guarantee when used as directed, return sales receipt and used container to *LANCO®* Mfg. Corporation, Customer Service Dept., Urb. Aponte #5, San Lorenzo, PR 00754 for product replacement. Seller will not accept liability for more than product replacement or purchase price.

**Notice:** The technical data contained herein are true and accurate to the best of our knowledge. Published technical data and instructions are subject to change without prior notice.

**M.S.D.S.:** Available upon request.