



TUB & TILE CAULK TP-874

HIGH PERFORMANCE ADHESIVE & SEALANT

Lifetime Warranty

(ASTM 920-86 Type S, Grade NS, Class 25, Use NT)

PRODUCT

DESCRIPTION: A high-performance, acrylic elastomeric sealant and adhesive with permanent adhesion and flexibility and the lifetime durability of a silicone sealant that adheres to painted or unpainted glass, wood, metal, brick, concrete, drywall, tile, marble and many other interior or exterior surfaces.

BASIC USES: Ideal for sealing around kitchen counters, tubs, showers and sinks, for caulking around windows and doors, and for bonding moldings, ceramic tile, vinyl cove base, foam insulation and tub surroundings.

PRODUCT

ADVANTAGES:

| | |
|----------------------------------|----------------------|
| * Silicone adhesion | * Lifetime warranty |
| * Up to 50% total joint movement | * 100% flexible |
| * 100% paintable | * Mildew resistant |
| * Non-yellowing | * Moisture resistant |

TECHNICAL DATA

| | | | |
|----------------------------------|---|---------------------------------------|---------------------|
| Percent Solids: | 74.00 ± 1% by weight 70.00 ± 1% by volume | Finish: | Ultra white |
| Weight / Gallon: | 13.19 ± 0.5 lbs. | Viscosity: | 175,000-195,000 cps |
| Drying Time: | To touch: 15 minutes To coat with latex paint: 2 hours To coat with alkyd paint: 24 hours | Percent Pigment by Weight: | 54.00 ± 1% |
| Flash Point: | Non-flammable | Sizes: | 5.5 fl. oz. tube |
| Theoretical Coverage: | Approximately seven linear feet of 1/4" bead per 5.5 oz. tube. | | |

Surface Preparation: Surface must be free of dust, dirt, grease and mildew. Remove all loose or badly cracked sealant and paint.

Mildewed Surfaces: Any existing mildew on the surface must be completely killed and removed prior to the application of new caulk. Using a long-handled brush, scrub surface with a mixture of one quart of household bleach and three quarts of warm water. Rinse completely and let dry.

Previously Caulked Surfaces: It is critical to remove as much old sealant as possible before applying new caulk, specially if it is cracked, eroded or pulled away from the joint.

Application Instructions: For best results, follow this procedure:

- (1) Knead tube well before using.
- (2) Apply at temperatures above 40°F (5°C) and when no precipitation is expected within 72 hours.
- (3) Cut nozzle to desired bead (1/4" is normally recommended).
- (4) Hold tube at 45° angle to the seam and push *LANCO® Tub & Tile Caulk TP-874* ahead of nozzle, applying uniform pressure in order to get a smooth bead.
- (5) Limit joint size to be filled to approximately 1/4"x 1/4". If joint size exceeds 1/4", use polyethylene foam or oakum as backup filler.
- (6) If necessary, tool immediately with wet finger. Wipe off excess with damp cloth.

Drying Time: Tack-free in fifteen minutes. Wait two hours before painting with latex paint; 24 hours if using alkyd (oil based) paint.

Cleanup: Clean up excess with damp cloth before caulk cures.

Storage: Protect from freezing; store in a cool, dry place at room temperature. Product must be used within one year of purchase.

Note: Do not use below water line. Joint size should not exceed 1/4" x 1/4". If joint depth exceeds 1/4", use polyethylene foam. Keep from freezing. Product must be used within one year of purchase.

Lifetime Warranty: Satisfaction guaranteed. If product cracks, peels or separates while you own your home, *LANCO®* will replace this cartridge. Return sales receipt and used container to *LANCO®* Mfg. Corporation, Customer Service Dept., Urb. Aponte #5 San Lorenzo, PR 00754. Seller will not accept liability for more than product replacement.

Notice: The technical data contained herein are true and accurate to the best of our knowledge. Published technical data and instructions are subject to change without prior notice.

M.S.D.S.: Available upon request.