



ULTRA CLEAR CAULK TP-872

HIGH PERFORMANCE SILICONIZED ACRYLIC SEALANTS 40-Year Warranty (ASTM C 834-91)

PRODUCT

DESCRIPTION: A one-component, high-performance, elastomeric sealant with the permanent adhesion and UV resistant properties of acrylic plus the permanent flexibility and lifetime durability of silicone. A high quality caulk will not crack, crumble or peel, even when exposed to severe weather or total joint movement; for interior or exterior use.

BASIC USES: LANCO® Ultra Clear Caulk provides a waterproof and weatherproof seal, adhering tightly to interior and exterior surfaces, even to ceramic and glass substrates. Excellent for siding corner joints and caulking around windows, doors, skylights, vents, air ducts and chimneys.

PRODUCT

ADVANTAGES:

- * Interior / exterior
- * 40-year warranty
- * Non-yellowing
- * Seals in concrete, drywall, wood and metal
- * 100% odor free
- * 100% flexible
- * 100% silicone durability
- * 100% clear
- * Mildew and moisture resistant

TECHNICAL DATA

Percent Solids:	59.56 ± 1% by weight 55.59 ± 1% by volume	Colors:	Clear
Weight /Gallon:	8.86 ± 0.5 lbs	Viscosity:	175,000 – 195,000 cps.
Flash Point:	Non-flammable	Sizes:	5.5-oz. cartridge
Drying Time:	To touch: 15 minutes		
Theoretical Coverage:	Approximately seven linear feet of 1/4" bead per 5.5-oz. cartridge.		

Surface Preparation: Surface must be free of dust, dirt, grease and mildew. Remove all loose or badly cracked sealant and paint.

Mildewed Surfaces: Any existing mildew on the surface must be completely killed and removed prior to the application of new caulk. Using a long-handled brush, scrub mildewed surface with a mixture of one quart of household bleach and three quarts of warm water., Rinse completely and let dry.

Previously Caulked Surfaces: It is critical to remove as much old sealant as possible before applying new caulk, specially if it is cracked, eroded or pulled away from the joint.

Application Instructions: For best results, follow these steps:

- (1) Knead tube well before using.
- (2) Apply at temperatures above 40°F (5°C) and when no precipitation is expected within 72 hours.
- (3) Cut nozzle to desired bead size (1/4" is recommended).
- (4) Hold tube at 45° angle to the seam and push *LANCO® Ultra ClearCaulk* ahead of nozzle, applying uniform to the trigger in order to get a smooth bead.
- (5) Limit joint size to be filled to approximately 1/4" x 1/4". If depth of joint exceeds 1/4", use polyethylene foam or oakum as backup filler.
- (6) Wipe away excess with a damp cloth before surface skins.

Note: *LANCO® Ultra Clear Caulk* guns out white but will dry clear; maximum clarity after thirteen days.

Cleanup: Clean up excess with damp cloth before caulk cures.

Coverage: Approximately seven linear feet of 1/4" bead per 5.5-oz. cartridge.

Storage: Protect from freezing; store in a cool, dry place at room temperature. Product must be used within one year of purchase.

Note: Always use a sealer such as shellac, before topcoating with a lacquer. Not recommended for use on horizontal surfaces where water may collect, or for marine use on areas below water level.

Limited Warranty: Satisfaction guaranteed for forty years. If product cracks, peels or separates while you own your home during period of guarantee when used as directed, return sales receipt and used container to *LANCO®* Mfg. Corporation, Customer Service Dept., Urb. Aponte #5, San Lorenzo, PR 00754 for product replacement. Seller will not accept liability for more than product replacement or purchase price.

Notice: The technical data contained herein are true and accurate to the best of our knowledge. Published technical data and instructions are subject to change without prior notice.

M.S.D.S.: Available upon request.