



TECHNICAL DATA SHEET

WHITE TILE GROUT & ADHESIVE

TP-875

HIGH STRENGTH ADHESIVE

PRODUCT

DESCRIPTION: A water and mildew resistant ultra white acrylic compound that bonds and grouts ceramic and mosaic wall and floor tiles. Adheres permanently, resists cracking, shrinking and discoloration.

BASIC USES: Excellent for bonding and grouting ceramics, mosaic walls and floor tiles.

PRODUCT

ADVANTAGES:

| | |
|--------------------------|----------------------|
| * Bright white | * Permanent adhesion |
| * Bonds over any surface | * Mildew resistant |

TECHNICAL DATA

| | | | |
|----------------------------------|--|---------------------------------------|--------------------|
| Percent Solids: | 80.99 ± 1% by weight 71.16 ± 1% by volume | Color: | White |
| Weight / Gallon: | 13.82 ± 0.5 lbs. | Viscosity: | 230,000-250,00 cps |
| Drying Time: | To touch: 15 minutes To cure: 16 -24 hours | Percent Pigment by Weight: | 61.90 ± 1% |
| Flash Point: | Non-flammable | Sizes: | 5.5 fl. oz. tube |
| Theoretical Coverage: | Approximately seven linear feet of 1/4" bead per 5.5 oz. tube. | | |

Surface Preparation: Surface must be free of dust, dirt, grease and mildew. Remove all loose or badly cracked sealant and paint.

Mildewed Surfaces: Any existing mildew on the surface must be completely killed and removed prior to the application of new caulk. Using a long-handled brush, scrub mildewed surface with a mixture of one quart of household bleach and three quarts of warm water. Rinse completely and let dry.

Application Instructions: For best results, follow these steps:

- (1) Knead tube well before using.
- (2) Apply at temperatures above 40°F (5°C) and when no precipitation is expected for 72 hours.
- (3) Cut nozzle to desired bead (1/4" is recommended)
- (4) Hold gun at 45° angle to the seam and push *LANCO® White Tile Grout & Adhesive TP-875* ahead of nozzle, applying uniform pressure to dry surface.
- (5) Set tile.
- (6) Apply *LANCO® White Tile Grout & Adhesive TP-875* again around tile. Work product thoroughly into each joint with a spurge or finger.

(7) Wait about two minutes. Remove excess with damp sponge.

(8) Allow to dry 16 to 24 hours before exposure to water.

Note: *LANCO® White Tile Grout & Adhesive TP-875* can be tinted before application to color match colored tile using *LANCO® Color Express System*.

Cleanup: Clean up excess with damp sponge.

Storage: Protect from freezing; store in a cool, dry place at room temperature. Product must be used within one year of purchase.

Notice: The technical data contained herein are true and accurate to the best of our knowledge. Published technical data and instructions are subject to change without prior notice.

M.S.D.S.: Available upon request.