



TECHNICAL DATA SHEET

SPACKLING COMPOUND

SC-101

VINYL ACRYLIC LATEX

PRODUCT

DESCRIPTION: An extremely durable, ultra white compound to fill and repair cracks and holes in interior or exterior plaster, concrete, drywall and wood surfaces. Sticks tightly to plaster and dries quickly. Water resistant and sandable when dry.

BASIC USES: Excellent for the repair of nail holes, cracks and dents in drywall, plaster, wood, brick, stone, concrete and other interior or exterior surfaces.

PRODUCT

ADVANTAGES:

* Anti-fungus	* Interior / exterior
* Ready mixed	* Ultra white
* Weather resistant	* Water cleanup
* Dries hard	* Easy to sand
* Will not crack peel or shrink	* Easy to use

TECHNICAL DATA

Percent Solids:	74.00 ± 1% by weight 58.00 ± 1% by volume	Finish:	Ultra white
Texture:	Smooth	Viscosity:	550,000-600,000 cps.
Weight / Gallon:	14.2 ± 0.5 lbs.	Percent Pigment by Weight:	70.00 ± 1%
Flash Point:	Non-flammable		
Drying Time:	To touch: 30 minutes To sand: 1 hour To coat with latex paint: 2 hour To coat with alkyd paint: 24 hours	Sizes:	1 gallon 1 quart 1 pint 8 ounces 5.5-oz tube (TP-871)
Theoretical Coverage	Depends on depth and size of holes and cracks		

Surface Preparation: Surfaces to be filled must be dry, clean and free of contaminants such as dirt, grease, chalk, dust, wax, loose paint or plaster.

Application Instructions: For best results, follow these steps:

- (1) Apply *LANCO® Vinyl/Acrylic Spackling Compound SC-101* with putty knife. One fill is usually sufficient for small dents and holes.
- (2) For deep fills, apply two or more layers of *LANCO® Vinyl/Acrylic Spackling Compound SC-101*, allowing it to dry between applications.
- (3) *LANCO® Vinyl/Acrylic Spackling Compound SC-101* can be sanded or painted two hours after application. Allow longer drying time for deep fills. When dry, sand excess flush with surface. May be painted with latex or oil based paint.

Limitation: Do not apply in exterior surfaces if rain is expected within 2 hours of application. Do not use as caulk, sealant or joint filler over cracks or joint where expansion and contraction may occur. For these purpose use *LANCO® Siliconizer Crack Filler™ RC-230*.

Cleanup: Clean all equipment immediately after use with warm soapy water.

Caution: Do not take internally. Keep out of reach of children. Use only with adequate ventilation.

Precaution: Do not apply when temperature is below 40°F (5°C). Apply liberally, but do not overspread. Keep from freezing.

Notice: The technical data contained herein are true and accurate to the best of our knowledge. Published technical data and instructions are subject to changes without prior notice.

M.S.D.S.: Available upon request.