



TECHNICAL DATA SHEET

ZERO LIGHTWEIGHT SPACKLING™

SC-098

ACRYLIC LATEX COMPOUND

PRODUCT

DESCRIPTION: An ultra white acrylic and fast-drying lightweight spackling made of glass beads that will not shrink, sag, crumble or chalk, thus creating an extra smooth paste that covers large or small holes in one quick step without need for sanding. The non-slump formula of LANCO® *Zero Lightweight Spackling™* SC-098 hangs perfectly on knife for easy application in interior or exterior surfaces, preventing rust from bleeding through the finish.

BASIC USES: To patch and repair in only one application large or small holes, cracks, crevices and dents in exterior and interior brick, wood, stucco and concrete.

PRODUCT

ADVANTAGES:

- * Ultra white
- * All-purpose
- * Will not crack
- * Fast drying
- * Easy to use
- * Interior / exterior
- * Will not shrink
- * No sanding required

TECHNICAL DATA

Percent Solids:	37.00 ± 1% by weight 73.00 ± 1% by volume	Finish:	Ultra white
Texture:	Smooth	Viscosity:	650,000-750,000 cps
Weight / Gallon:	3.5 ± 0.5 lbs.	Percent Pigment by Weight:	19.00 ± 1%
Flash Point:	Non-flammable		
Drying Time:	To touch: Immediately To coat with latex paint: Immediately To coat with alkyd paint: 24 hours	Sizes:	1 gallon 1 quart 1 pint 8 ounces
Theoretical Coverage:	Depends on depth and size of hole or crack.		

Surface Preparation: Surface to be filled must be dry, clean and free of contaminants such as dirt, grease, chalk, dust, wax, loose paint or plaster.

Application: Apply *LANCO® Zero Lightweight Spackling™* with a flexible putty knife. For a smooth finish, dip putty knife into water and lightly smooth spackling. *LANCO® Zero Lightweight Spackling™* can be painted immediately with latex paint. If sanding is desired or oil paint is to be used, allow to dry thoroughly.

Note: Do not apply in exterior surfaces if rain is expected within 24 hours of application. Do not use on floors. Do not use as caulk, sealant or joint filler over cracks or joints where expansion and contraction may occur. Do not use as skim coat for smoothing large, rough surfaces. For this purpose use *LANCO® Vinyl/Acrylic Spackling Compound SC-101*. Temperature should be above 50°F (10°C).

Cleanup: Clean all equipment immediately after use with warm soapy water.

Caution: Do not take internally. Keep out of reach of children. Use only with adequate ventilation.

Precaution: Do not apply when temperature is below 40°F (5°C). Apply liberally, but do not overspread. Keep from freezing.

Notice: The technical data contained herein are true and accurate to the best of our knowledge. Published technical data and instructions are subject to changes without prior notice.

M.S.D.S.: Available upon request.