



**WHITE WOOD FILLER
TP-873
PAINTABLE FILLER**

PRODUCT

DESCRIPTION: An all-purpose acrylic white filler for patching all types of interior or exterior wood surfaces. This unique filler cures into a flexible patch that will not crack or crumble, even after many years of service; suitable for use with latex or oil paints.

BASIC USES: Excellent for patching all types of woods.

PRODUCT

ADVANTAGES:

- * Super flexible
- * Interior / exterior use
- * Non-cracking
- * Permanent adhesion
- * 100% paintable

TECHNICAL DATA

Percent Solids: 70.00 ± 1% by weight
59.26 ± 1% by volume

Color: White

Weight / Gallon: 11.98 ± 0.5 lbs.

Viscosity: 175,000-195,000 cps

Drying Time: To touch: 15 minutes
To sand: 24 hours

**Percent Pigment
by Weight:** 44.33 ± 1%

Flash Point: Non-flammable

Sizes: 5.5 fl. oz. tube

**Theoretical
Coverage:**

Approximately seven linear feet of 1/4" bead per 5.5-oz. tube.

Surface Preparation: Surface must be free of dust, dirt, grease and mildew. Remove all loose or badly cracked sealant and paint.

Mildewed Surfaces: Any existing mildew on the surface must be completely killed and removed prior to the application of new caulk. To remove mildew scrub surface with a mixture of 1 quart of household bleach and 3 quarts of warm water. Use longhandle brush. Rinse completely and let dry.

Application Instructions: For best results, follow these procedures:

- (1) Knead tube well before using.
- (2) Apply at temperatures above 40°F (5°C) and when no precipitation is expected for 72 hours.
- (3) Cut nozzle to desired bead (1/4" is normally recommended).
- (4) Hold tube at 45° angle to the seam and push *LANCO® White Wood Filler TP-873* ahead of nozzle, applying uniform pressure in order to get a smooth bead.

(5) Remove excess with putty knife.

(6) When dry, sand if required.

Note: For deep holes; apply two thin applications of *LANCO® White Wood Filler TP-873*.

Topcoat: Let dry for 24 hours when using acrylic paint and 48 hours when using alkyd (oil base) paint.

Cleanup: Clean all equipment with water.

Storage: Protect from freezing; store in a cool, dry place at room temperature. Product must be used within one year of purchase.

Notice: The technical data contained herein are true and accurate to the best of our knowledge. Published technical data and instructions are subject to change without prior notice.

M.S.D.S.: Available upon request.