



TECHNICAL DATA SHEET

BORDER & VINYL WALLCOVERING ADHESIVE™

LA-643

PROFESSIONAL GRADE VINYL & FOIL BORDERS ADHESIVE

PRODUCT

DESCRIPTION: LANCO® *Border & Vinyl Over Vinyl Wallcoverig Adhesive* is a heavy duty ready mix adhesive formulated to make the installation of all vinyl and foil borders easier, trouble free and stronger. LANCO® *Border & Vinyl Over Vinyl Wallcoverig Adhesive* dries clear and is easily cleaned with water.

BASIC USES: For the installation of all vinyl and foil borders easier, trouble free and stronger.

PRODUCT

ADVANTAGES:

- * Dries clear
- * Heavy duty
- * Low water content
- * Mildew resistant
- * Ready mixed
- * Non-flammable
- * Non-staining
- * Non-toxic

TECHNICAL DATA

Percent Solids:	45.00 ± 1% by weight 34.00 ± 1% by volume	Drying Time:	20 minutes
Weight / Gallon:	9.97 ± 0.5 lbs.	Viscosity:	130,000-150,000 cps
Flash Point:	Non-flammable	Thinning:	Do not thin
Specific Gravity:	1.20	Color:	Clear
Sizes:	5 gallons 1 gallon 1 quart	Coverage:	1,120 linear feet of 3” border per gallon.

Surface Preparation: All surfaces must be dry, clean and free of contaminants such as dirt, grease, chalk, mildew, oil, rust, loose or badly cracked paint. Glossy surfaces should be primed with *LANCO® Stain Killer WP-039*. This product will not adhere to waxed, siliconized surfaces.

Mildewed Surfaces: Any existing mildew on the surface must be completely killed and removed prior to the application of this product. Any mildew not removed may continue to grow. Using a longhandled brush, scrub mildewed surface with a mixture of one quart of household bleach and three quarts of warm water. Rinse completely and let dry.

Porous Surfaces: Such as plaster and latex painted walls should need no primer.

Non Porous Surfaces: Such as plastic, glass, formica, baked enamel, glossy paint or existing vinyl wallcovering should be primed with *LANCO® Stain Killer WP-039* prior to hanging wallcovering with this adhesive.

Application: Use this products full strength. Do not dilute. Apply a thin even coat with a pasting brush or roller to the back of the wallcovering or border, as recommended by the wallcovering manufacturer. When hanging wallcovering, pasted strips should be folded and allow to set 10 minutes. If border is pre-pasted, dampen back of border with wet sponge. Wait two minutes and apply *Lanco®* adhesive in a thin coat to the back of the border, this will prevent over absorption of the *LANCO®* paste. Pre-pasted border strip should be folded back to back and allow to set 5 minutes. Hang 2 strips and check carefully for proper adhesion, smooth out the wallcovering when hung. Remove excess adhesion before it dries with warm water (do not allow to dry).

Coverage: Hangs 1,120 linear feet of 3” border per gallon.

Cleanup: Remove excess adhesive before it dries with warm water. Clean all equipment after use with warm soapy water before adhesive dries.

Note: Not recommended for use with high shrinkage wallcovering (many grasscloths, strings and untreated fabrics) over vinyl wallcovering.

Caution: Do not take internally. Close container after each use. Keep out of reach of children. Use with adequate ventilation.

Notice: The technical data contained herein are true and accurate to the best of our knowledge. Published technical data and instructions are subject to change without prior notice.

M.S.D.S.: Available upon request.