



## PRE-PASTED WALLCOVERING ACTIVATOR & ADHESIVE™

### LA-642

#### FOR ALL PRE-PASTED WALLCOVERING

#### PRODUCT

##### DESCRIPTION:

A ready to use pre-pasted adhesive, formulated to make the installation of all pre-pasted wallcovering easier, cleaner and trouble free. Eliminates the need for a messy eater tray. Just apply to the back of the wallcovering with a paint roller. *LANCO® Pre-pasted Wallcovering Activator & Adhesive* prevents the adhesive from drying too quick which is an advantage when matching patterns and butting seams. *LANCO® Pre-pasted Wallcovering Activator & Adhesive* dries clear and is easily cleaned with water.

##### BASIC USES:

For the installation of all pre-pasted wallcoverings.

#### PRODUCT

##### ADVANTAGES:

- \* Easier positioning
- \* Eliminates water soaking
- \* Keep seams tight
- \* Mildew resistant
- \* Activates adhesion
- \* Non-flammable
- \* Non-staining
- \* Non-toxic

#### TECHNICAL DATA

<b>Percent Solids:</b>	45.00 ± 1% by weight 34.00 ± 1% by volume	<b>Drying Time:</b>	20 minutes
<b>Weight / Gallon:</b>	9.97 ± 0.5 lbs.	<b>Viscosity:</b>	130,000-150,000 cps
<b>Flash Point:</b>	Non-flammable	<b>Thinning:</b>	Do not thin
<b>Specific Gravity:</b>	1.20	<b>Color:</b>	Clear
<b>Sizes:</b>	5 gallons 1 gallon 1 quart	<b>Coverage:</b>	350 sq. ft./gal.

**Surface Preparation:** All surfaces must be dry, clean and free of contaminants such as dirt, grease, chalk, mildew, oil, rust, loose or badly cracked paint. Glossy surfaces should be primed with *LANCO® Stain Killer WP-039*. If surface is plastic, baked enamel, or already covered with vinyl material, use *LANCO® Wallpaper Primer™ LA-822*.

**Porous Surfaces:** Such as plaster and latex painted walls should be primed with *LANCO® Wallpaper Primer™ LA-822*.

**Non Porous Surfaces:** Such as plastic, glass, formica, baked enamel, glossy paint or existing vinyl wallcovering should be primed with *LANCO® Stain Killer WP-039* prior to hanging wallcovering with this adhesive.

**Application:** Use this product full strength. Do not dilute. Apply liberally with a brush or roller to the back of the wallcovering (this procedure eliminates the need to soak the wallcovering in water). Fold pasted sheet back to back and allow for booking time as recommended by the wallcovering manufacturer. Hang two strips and check carefully for proper adhesion. If have any doubt, contact *LANCO®*. Smooth out the wallcovering when hung, using a brush or soft squeegee. Do not use excessive pressure, particularly at seams or edges.

**Coverage:** Hang 10 single rolls per gallon (350 sq.ft per gallon).

**Cleanup:** Remove excess adhesive with warm water. Clean all equipment after use with warm soapy water before adhesive dries.

**Caution:** Do not take internally. Close container after each use. Keep out of reach of children. Use with adequate ventilation.

**Notice:** The technical data contained herein are true and accurate to the best of our knowledge. Published technical data and instructions are subject to change without prior notice.

**M.S.D.S.:** Available upon request.