



TECHNICAL DATA SHEET

SUPER-STRIP™

PR-111

SEMI-PASTE COATING REMOVER

PRODUCT

DESCRIPTION:

A super powerful, non-running type gel stripper formulated with a strong chlorinated solvent and deep acting and wetting agents that effectively removes coatings from metal, wood, concrete and other surfaces. Aircraft, automotive, industrial and marine grade.

BASIC USES:

For a fast-acting and quick removal of polyurethanes, enamels, lacquers, primers, and clear coats over base coat systems from wood, metal, concrete and other surfaces. Not for use on plastics.

PRODUCT

ADVANTAGES:

- * Non-running
- * Non-caustic
- * Easy water cleanup
- * Fast-acting
- * Non-staining

TECHNICAL DATA

Percent solids: 10.18 ± 0.5% by weight
11.29 ± 0.5% by volume

Color: Blue

Weight / Gallon: 10.03 ± 0.5 lbs.

Viscosity: 3,500-4,000 cps.

Solvent: 89.82 ± 1%

Flash Point: > 100°F Setaflash

Sizes: 55 gallons
5 gallons
1 gallon
1 quart

Thinning: Do not thin.

Directions:

- (1) Shake well before using.
- (2) Apply a thick (minimum 1/8") coat of stripper to the entire piece of material, furniture or woodwork; the thicker the coat of stripper applied the more effective the stripper action. Brushing in one direction helps provide a thick, uniform coat.
- (3) Allow gel to work and to penetrate into the old finish and do the work for you. For varnish, lacquer and shellac, wait at least 20 minutes. For polyurethane and enamels, let it work 1-2 hours. (Waiting time will depend on the number of coats to be stripped.). After one hour, the paint stripper will skin over and appear dry, but it is still wet and working under the skin. Test with a putty knife to see if the surface is ready for stripping.
- (4) Remove finish with a putty knife or scraper. Use medium-grade steel wool on rounded or curved surfaces and to remove any remaining gel from within the wood grain or surfaces stripped. *LANCO® Super Strip™ PR-111* will not raise the grain of the wood.
- (5) For tough spots, reapply gel and wait only 15 minutes.
- (6) Wipe off with a paper towel or use water-dipped rags. For best results on wood, wipe surface clean with rubbing alcohol. Let dry thoroughly and sand before refinishing.
- (7) Clean all tools with water.

Limitations:

LANCO® Super Strip™ PR-111 is not recommended for use on fiberglass or plastic. For exterior use only.

Method of Application:

- (1) *Brushing:* Use a soft natural or nylon bristle brush to apply a coat of *LANCO® Super Strip™ PR-111* in one direction only. Do not rebrush.
- (2) *Spraying:* Use a high-pressure spray gun with 20-21 psi.

Precaution: Keep away from heat, spark and open flame. Vapor is heavier than air. Prevent build-up of vapor – open all windows and doors; use only with cross ventilation. Extinguish all flames and pilot lights; and turn off stoves, heaters and electric motors, eliminate all other sources of ignition (including static spark) during use and until all vapors are gone. Keep container closed when not in use. *LANCO® Super Strip™ PR-111* is not recommended for use on fiberglass or plastic. Test for suitability first before applying on unlisted surfaces. (User accepts all responsibility for such use.) **USE ONLY WITH ADEQUATE VENTILATION:** Ventilation must be sufficient to limit exposure below M.S.D.S. limits.

Notice: The technical data contained herein are true and accurate to the best of our knowledge. Published technical data and instructions are subject to change without prior notice.

M.S.D.S.: Available upon request.