



TECHNICAL DATA SHEET

ACRYLIC RETARDER SR-110

PRODUCT

DESCRIPTION: A high quality, slow evaporating retarded for use with acrylic and nitrocellulose lacquers to promote flow and eliminate blushing in hot or humid weather.

BASIC USES: To promote flow and eliminate blushing in hot or humid weather when using acrylic and nitrocellulose lacquers.

PRODUCT

ADVANTAGES:

* 100% virgin	* Low odor
* Improves gloss	* Prevents blushing
* Renders a smooth glass-like finish	* Crystal Clear

TECHNICAL DATA

Weight / Gallon: 7.52 ± 0.5 lbs **Color:** Transparent

Flash Point: 154° F TCC

Sizes:

- 55 gallons
- 5 gallons
- 1 gallon
- 1 quart

Directions For Use: Thin acrylic or nitrocellulose lacquer top coat as per directions for those products.

Warning: Contains toluene, acetone and methyl alcohol; cannot be made non-poisonous.

Precautions: USE ONLY IN WELL VENTILATED AREA. Keep away from heat and open flame. Avoid contact with skin and eyes. If swallowed, do not induce vomiting. Call a physician immediately. In case of eye contact, flush with water for 15 minutes. Get prompt medical attention. Keep out of reach of children. **KEEP AWAY FROM HEAT, SPARKS AND OPEN FLAME.** Vapor is heavier than air. Prevent build-up vapor — open all windows and doors; use only with cross ventilation. Extinguish all flames and pilot lights and turn off stoves, heaters and electric motors and eliminate all other sources of ignition (including static sparks) during use and until all vapors are gone. Keep container closed when not in use. **USE ONLY WITH ADEQUATE VENTILATION.** Ventilation must be sufficient to limit exposure below M.S.D.S limits. Eye irritation and dizziness are indications of over-exposure. Refer to the *LANCO*[®] Material Safety Data Sheet. **AVOID PROLONGED OR REPEATED BREATHING OF VAPORS.** It is important to use adequate ventilation, as high vapor concentration may cause unconsciousness or even asphyxiation.

DO NOT TAKE INTERNALLY. Swallowing may cause injury, illness or death. **AVOID PROLONGED OR REPEATED CONTACT WITH SKIN.** Contact may cause skin irritation and dermatitis. **DO NOT GET IN EYES.** Will cause discomfort and irritation. **DO NOT EAT, DRINK OR SMOKE IN WORK AREAS.**

First Aid: *Inhalation Overexposure:* Remove patient to fresh air. If breathing stops, give artificial respiration. Call a physician. *Swallowing:* Seek medical attention immediately. Do not induce vomiting. *Skin Contact:* Remove contaminated clothing and shoes. Wash skin with warm water and soap. Wash clothes and air out shoes.

Caution: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage, peripheral nervous tissue damage and liver abnormalities. Intentional misuse by deliberately concentrating and inhaling the content may be harmful or fatal.

Notice: The technical data contained herein are true and accurate to the best of our knowledge. Published technical data and instructions are subject to change without prior notice.

M.S.D.S.: Available upon request.