



Gel Strip Paint Remover

PR-111

Non-Running Gel Paint Remover

Description:

Gel Strip is a super powerful, non-running type gel stripper formulated with a strong chlorinated solvent and deep acting and wetting agents that effectively removes coatings from metal, wood, concrete and other surfaces. Aircraft, automotive, industrial and marine grade.

Product Advantages:

- Non-running
- Non-caustic
- Easy water cleanup
- Fast-acting
- Non-staining

Uses:

Designed for a fast-acting and quick removal of polyurethanes, enamels, lacquers, primers, and clear coats over base coat systems from wood, metal, concrete and other surfaces. Not for use on plastics.

Surface Preparation:

All surfaces must be clean, dry prior to apply this product.

Product Data:

Weight/Gallon:	10.03 ± 0.05 lb. (4.55 ± 0.02 kg.)
Sizes:	55 gallons 5 gallons 1 gallon 1 quart
Viscosity:	3,500-4,000 KU.
Flash Point:	< 100°F Setaflash

Notice: The technical data contained herein are true and accurate to the best of our knowledge. Published technical data and instructions are subject to change without prior notice.

F.D.S.: Available upon request.

Storage:

Protect from freezing; store in a cool, dry place at room temperature. Product must be used within one year of purchase.

Application Method:

For best results, follow these steps:

1. **Brushing:** Using a soft natural nylon bristle brush, apply a thick coat of Lanco® Gel Strip in one direction only. Let it stand for 15 to 30 minutes. Do not rebrush.

2. **Spraying:** Using a pressure spray gun designed for spraying heavy mastic type material, spray at 20 to 22 P.S.I., apply wet heavy coat. Let it stand for 15 to 30 minutes.

Note: always use respiratory protection.

3. **Dipping:** Dip the entire piece into the Lanco® Gel Strip for 15 to 30 minutes. Allow Lanco® Gel Strip to penetrate into the old finish and do the work for you.

When action is completed, scrap off with a flexible putty knife or squeegee. Then rinse thoroughly either with water from a hose, water dipped rags or steel wool, or solvent dipped rags. Allow stripped and cleaned surface to dry before applying new finish. On metal surfaces and aluminum apply to prevent rust or oxidation. Prime immediately after surface is dry. Lanco® Gel Strip is not recommended for use on fiberglass or plastic. Before using on unlisted surfaces, first test for suitability. User accepts all responsibility for such use. Do not use on plastics.

Danger/Warning:

Use only with adequate ventilation. Ventilation must be sufficient to limit exposure below F.D.S. limits. Maintain close container when not in use.

Caution: flammable vapors may cause flash fire. Before applying, extinguish pilot lights, shut off electrically operated appliances and eliminate other sources of flame or sparks and leave off until area is clear of vapors. Do not smoke. Close container tightly after each use. Provide adequate ventilation during application and drying cycle.

First aid: avoid prolonged or repeated breathing of vapor. High vapor concentrations may cause unconsciousness or even asphyxiation. Do not take internally. Swallowing may cause injury, illness or death. If swallowed do not induce vomiting; consult a physician immediately. Avoid prolonged or repeated contact with skin. Contact may cause skin irritation and dermatitis. Do not get in eyes. Keep out reach of children.

Notice: Reports have associated repeated and prolonged occupational over exposure to solvents with permanent brain and nervous system damage, peripheral nervous tissue damage and liver abnormalities. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

Warning!: Keep out of reach of children. Do not take internally.

Important: Use only with adequate ventilation. Ventilation must be sufficient to limit exposure below MSDS limits. Read Safety Data prior to use. Protect from freezing. Go to www.lancopaints.com.

For chemical emergency call ChemTrec 1-800-424-9300 (USA) or 1-703-527-3887 (International).