



Supreme Flooring Adhesive™ KA-

548

Extreme Duty Flooring Adhesive

Description:

Supreme Flooring Adhesive™ is a high performance styrene acrylic water resistant interior flooring adhesive.

Product Advantages:

- Good adhesion to construction materials
- Water resistant
- Water cleanup
- White mastic
- Multi-purpose

Use:

Supreme Flooring Adhesive™ is for use in floor installations such as vinyl, vinyl asphalt, carpet tiles, sponged-backed vinyl sheet and indoor carpeting. During process it will permit adjustments of the flooring materials before setting to a permanent bond.

Surface Preparation:

All surfaces must be dry, clean and free of contaminants such as dirt, grease, loose or badly cracked paint.

Product Data:

| | |
|----------------------------|---|
| Product Type: | Styrene-Acrylic |
| Finish color: | White |
| Solids (%): | 71±2 by weight 60±2 by volume |
| Weight/Gallon: | 11.51 lb±0.05 (5.22 kg±.02) |
| Drying time: | 24 hours |
| Coverage: | Approximately 30 ft. ² /gal. (3 m ² /gal.) or 30 mils dry thick with a notched trowel 1/32" |
| Sizes: | 5 gallos 2 gallons 1 gallon 1 quart |
| Viscosity: | 175,000- 200,000 cps |
| Percent Pigment by weight: | 41 ±2% |
| Specific gravity: | 1.48 |

Notice: The technical data contained herein are true and accurate to the best of our knowledge. Published technical data and instructions are subject to change without prior notice.

S.D.S.: Available upon request.

Application with a Trowel:

1. Spread Supreme Flooring Adhesive™ with a notched trowel. For rubber, plastic floor tile and linoleum, use a notched trowel of 1/16" x 1/16" x 1/16". For vinyl and vinyl fiber floor tile - light gauge, use a notched trowel of 1/32" x 1/16" x 1/32".
2. Set tiles or lay flooring within fifteen minutes after application, leaving no bare spots.
3. Before setting vinyl tile let Lanco® Supreme Flooring Adhesive™ get slightly tacky.
4. Roll installed resilient tiles immediately with a floor roller.
5. Remove any excess adhesive with a damp cloth before the surface dries.

Clean-up: Clean all equipment immediately after use with warm soapy water. Fresh mastic may be removed with a wet soapy cloth. Dried adhesive may be removed with a razor blade. Keep tools in water when not in use.

Precaution: Protect from freezing. Do not apply when air or surface temperature is below 72° F (22° C).

Caution: Contact with skin may cause irritation, in case of eye contact, flush thoroughly with water. Do not rub eyes. Do not take internally. If swallowed do not induce vomiting. Consult a physician immediately or regional poison control center. Use only with adequate ventilation. Keep out of reach of children. Do not take internally. Close container after each use. Keep out of reach of children. Use only with adequate ventilation. Product must be used within one year of purchase.

Limited Warranty: Manufacturers' liability in connection with the safety of this product extends only to the replacement value if it should fail to comply with quality standard or specifications. Protect from freezing.



- **NORTH AMERICA** • 600 Mid Florida Drive Airport Industrial Park of Orlando, Florida 32824 • Tel. (407) 240-4000 Fax (407) 240-4046
- **CARIBBEAN & SOUTH AMERICA** • Urb. Aponte #5, San Lorenzo, Puerto Rico USA 00754 • Tel. (787) 736-4221 Fax (787) 736-5313
- **CENTRAL AMERICA** • Zona Industrial Bes, lote #4, El Coyol de Alajuela, Costa Rica • Tel. (506) 2438-2257 Fax (506) 2438-2162