



# Acrylic Painter's Caulk™ cc-753

## Acrylic Sealant for Windows and Doors

### Description:

**Acrylic Painter's Caulk™** is an acrylic resin sealant of good performance. Ideal to seal joints in doors, windows and moldings to be painted. Creates a tight seal, highly flexible and durable to protect against penetration of air and moisture.

### Product Advantages:

- Good adhesion to construction materials
- Can be painted
- Mildew resistant
- Can be used to seal cracks
- 7 year warranty
- Moisture resistant
- Cleans with water
- Multi-purpose

### Uses:

Acrylic Painter's Caulk™ can be used to caulk cracks around door and window frames, baseboard trim and other areas where joint movement is minimal.

Adheres to painted or unpainted surfaces:

- Wood
- Plaster
- Drywall
- Masonry

For use to seal in:

- Windows
- Doors frames
- Corner joints
- Moldings
- Siding / trim

### Coverage:

Joint size in inches.

		Depth	
	Inch	1/4"	1/2"
Width	1/4"	24.8'	
	1/2"	12.4'	6.1'
	3/4"	8.1'	4'
	1"	6.1'	3'

Linear feet of sealant per 10.1 fl.oz.

### Product Data:

Product Type:	Acrylic Resin
Finish color:	White
Solids (%):	73 ± 2% by weight 59 ± 2% by volume
Weight/Gallon:	12.75 ± 0.05 lbs. ( 5.78 ± 0.02 kg.)
Drying Time:	
Tack Free:	12-15 minutes
Final Cure:	24 hours
Sizes:	10.1 fl.oz. cartridge 5.5 fl.oz tube
Viscosity:	300,000-350000 CPS
Percent Pigment by Weight:	50 ± 2%
VOC:	<100 g/L

Notice: The technical data contained herein are true and accurate to the best of our knowledge. Published technical data and instructions are subject to change without prior notice.

S.D.S.: Available upon request.

### Application Method:

1. Surface must be free of dust, dirt and grease. Remove all loose sealant.
2. Apply at temperatures above 40°F (5°C) when no precipitation is expected for 72 hours.
3. Cut nozzle to desired bead size.
4. Hold gun at a 45° degree angle to the seam.
5. Wipe away excess with a damp cloth before surface skins.
6. Wait 2 hours before painting with latex paint, 24 hours if using alkyd (oil) based paint.

**Note:** Not recommended for use on horizontal surfaces where water may collect, or for marine use areas below water grade level.

### Surface Preparation:

The surface and edges of the joint must be sound, clean, dry and free of oil, grease or other contaminants that may prevent adhesion.

**Mildewed surfaces:** Any existing mildew on the surface must be completely killed and removed prior to the application of new caulk. Using a long-handled brush, scrub mildewed surface with a mixture of one quart of household bleach and three quarts of warm water. Rinse thoroughly and let dry completely.

**Previously caulked surfaces:** It is critical to remove as much old sealant as possible before applying new caulk, especially if it is cracked, eroded or pulled away from the joint.

**Additional Label Information :**

**Cleanup:** Clean up excess with damp cloth before caulk cures.

**Storage:** Protect from freezing; store in a cool, dry place at room temperature. Product must be used within one year of purchase.

**Notice:** The technical data contained herein are true and accurate to the best of our knowledge. Published technical data and instructions are subject to change without prior notice.

**S.D.S.:** Available upon request.

**Warning!:** Keep out of reach of children. Do not take internally.

For chemical emergency call ChemTrec 1-800-424-9300 (USA) or 1-703-527-3887 (International).

**7-Year Limited Warranty:** Satisfaction guaranteed. If product cracks, peels or separates during period of guarantee when used as directed, return sales receipt and used container to Lanco® Mfg. Corp. for product replacement. The seller will not accept liability for more than product replacement or purchase price.

**Limitations & more information:**

Read Safety Data Sheet prior to use.

Go to [www.lancopaints.com](http://www.lancopaints.com).

Protect from freezing.

