



# Wood Parquet™ Adhesive WP-550 Waterproofing & Crack Isolation Base Membrane

### Description:

**Wood Parquet™ Adhesive** is an ultra-white, acrylic resin-based adhesive glue designed to install and glue wooden floors on vinyl or plank boards. For interior use, adhesion of high resistance, on or above grade and application of trowel.

### Product Advantages:

- High adhesion to wood and concrete.
- Not flammable.
- Easy application with trowel or spatula.
- Low odor and easy clean-up.
- Waterproof, water resistant.

### Uses:

Wood Parquet™ Adhesive is formulated to use in the installation of wood or parquet floors, decorative panels, wood, moldings, cork, etc. Creates a high adhesion between wood and concrete. Designed for easy application with good odor and flexibility for easy cleaning. It is water resistant, for better adhesion and is not flammable. It is perfect for installing wood floors indoors, simply and durably, with a glossy finish.

### Performance:

### Surface Preparation:

All surfaces to be bonded must be clean, dry and free from contaminants such as dirt, oil, dust, grease and mold. Remove loose pieces of old cracked paint or sealer. New concrete must be completely cured (30 days) and smooth.

### Technical Data:

Product Type:	Styrene Resin
Color:	Ultra White
Solids (%):	75 ± 2% by weight 64 ± 2% by volume
Weight/Gallon:	12.04 ± 0.05lbs. ( 5.46± 0.02kg.)
Open Time:	Max. 2 hours <i>*for working</i>
Drying Time:	To touch: 12-20 min. To recoat: 2-6 hrs.
Coverage:	50 ft. <sup>2</sup> /gal. (15.2 m <sup>2</sup> /gal.) <i>*depending on surfaces irregularities</i>
Can Sizes:	4 gallons 6 quartz
Viscosity:	325000-350000 CPS
Percent Pigment by Weight:	44.5 ± 2%
VOC:	<50 9/L

### Storage Information:

Protect from freezing temperatures; Store in a cool, dry room. The product must be used within the year it was purchased. It does not apply when the temperature is below 72°F (22°C).

### Application Method:

For best results, follow these instructions:

1. Spread Wood Parquet™ Adhesive with a notched trowel. For rubber, plastic floor tile and linoleum, use a notched trowel of 1/16" x 1/16" x 1/16". For vinyl and vinyl asbestos floor tile - light gauge, use a notched trowel of 1/32" x 1/16" x 1/32".
2. Set tiles or lay flooring within fifteen minutes after application, leaving no bare spots.
3. Before setting vinyl tile let Lanco® Super Multi-Purpose Flooring Adhesive™ get slightly tacky.
4. Roll installed resilient tiles immediately with a floor roller.
5. Remove any excess adhesive with a damp cloth before the surface dries.

Notice: The technical data contained herein are true and accurate to the best of our knowledge. Published technical data and instructions are subject to change without prior notice.

S.D.S.: Available upon request.

**Other Information:**

**Note:** New concrete must be completely dry and cured at least 3 months prior to application of this product. Do not use in areas where moisture, steam or alkylid conditions exist on concrete floors. Conduct a test to determine if the surface has any moisture problems. If there is a problem, you should locate the root of it and fix it before applying this glue.

**Cleaning:** Clean all tools immediately with warm water and soap. The fresh glue can be removed with a damp cloth and soap. The dry glue should be removed with a spatula. Keep tools in water when not in use.

**Important:** Protect from freezing. Do not apply glue when air temperature is below 72°F (22°C).

**Danger / Warning:**

Use only with adequate ventilation. Ventilation should be sufficient to limit exposure below the limits of S.D.S.

**Warning!** Harmful if swallowed. Contains turpentine and resins. Contact with skin may cause irritation. In case of contact with eyes, rinse with plenty of water. Do not rub your eyes. Do not ingest. If this occurs, do not induce vomiting. Call a physician immediately or local poison control. Use only with adequate ventilation. Keep out of the reach of children. Product must be used within one year after purchase.

**Precaution:** Do not take internally this product. Close container after each use. Keep out of the reach of children. Read the safety data sheets for this product before use. Use only with adequate ventilation. The product must be used within one year of purchase.

**Limited Warranty:** Manufacturer's liability in connection with the sale of this product will be extended to the replacement price only if the application specifications are met.

**Caution:** In the event of chemical emergencies, call ChemTrec 1-800-424-9300 (USA) or 1-703-527-3887 (International).

**Limitations and further information:**

Read the Material Safety Data Sheet before use.

Visit [www.lancopaints.com](http://www.lancopaints.com).

Protect from freezing. adequate ventilation. Keep out of reach of children.

