



# Tung-O-Var Varnish Stain

Basic Uses: interior/exterior wood

SPRAY PAINT



## TECHNICAL DATA

VISCOSITY: 15-20 KU's  
FLASH POINT: Less than 156° F  
SOLIDS (WEIGHT): 38% (varies with colors)  
SOLIDS (VOLUME): 27% (varies with colors)  
DRY FILM THICKNESS:  
1.05 mils dry recommended  
DRYING TIME: Set to touch in 3-4 hours

## SIZES

11 ounce can

## FINISH

GLOSS

## COLOR

Mahogany  
Maple  
Dark Oak  
Light Oak  
Medium Oak  
Walnut  
Clear

## DESCRIPTION

Spray that imparts both a stain and gloss varnish in one application without hiding the grain. It is ideal for protecting bare or previously stained wood, including furniture, cabinets, picture frames, tabletop, etc.

## APPLICATION

**SURFACE PREPARATION:** Sand with 150 garnet paper, then 280. Remove dust with vacuum cleaner, brush or tack-cloth. Apply two (2) or three (3) coats until color desired is obtained.

**PREVIOUSLY PAINTED SURFACES:** For best results, remove all finishes back to bare wood and refinish as for new work. For recoating over sound, aged finishes, first remove all wax, grease, oil, or other foreign matter by washing with paint thinner and then with water and detergent. When surface dries, sand well with medium fine sandpaper and wipe clean. Apply one (1) or two (2) coats of this product.

**METHOD OF APPLICATION:** Shake can vigorously for one minute after agitator ball rattles freely. Both object to be painted and paint should be at least 70° F (20° C). Hold can upright 10-12 inches from surface and spray short even strokes. Aim away from face. Several thin mist coats are better than on full wet coat. Shake can periodically while painting. If tip clogs, remove and clean.

## PRECAUTION

### CAUTION! EXTREMELY FLAMMABLE.

Combustible. Risk to your health depends on level and duration of exposure. Keep away from heat, sparks and open flame. Vapors may ignite explosively. Do not puncture or incinerate (burn) container. Use only with adequate ventilation. If you must use it in indoors, open windows and doors to ensure a continuous flow of fresh air during application and drying. Avoid prolonged contact with skin and breathing of vapor or spray mist. Close container after each use.

**KEEP OUT OF REACH OF CHILDREN.**

(Continued)

