



## SF-293 - SUPER FLOOR ANTI SLIP SILVER



### SECTION 1: IDENTIFICATION

- 1.1 Product identifier:** SF-293 - SUPER FLOOR ANTI SLIP SILVER  
**Other means of identification:**  
Non-applicable
- 1.2 Recommended use of the chemical and restrictions on use:**  
Relevant uses (Consumer use): Acrylic paint  
Relevant uses (Professional users): Acrylic paint  
Relevant uses (Industrial user): Acrylic paint  
Uses advised against: All uses not specified in this section or in section 7.3
- 1.3 Name, U.S. address, and U.S. telephone number of the chemical manufacturer, importer, or other responsible party:**  
Lanco Manufacturing Corp.  
Urb. Aponte #5  
00754 San Lorenzo - Puerto Rico - Estados Unidos  
Phone: +1-787-736-4221 - Fax: +1-787-736-5313  
info@lancopaints.com  
http://www.lancopaints.com
- 1.4 Emergency phone number:** CHEMTREC (US Transportation) +1-800-424-9300 | CHEMTREC (International Transportation) +1-703-527-3887

### SECTION 2: HAZARD(S) IDENTIFICATION

- 2.1 Classification of the substance or mixture:**  
This product contains crystalline silica but due to its liquid state does not require classification (STOT RE)  
**29 CFR 1910.1200:**  
Classification of the chemical in accordance with paragraph (d)(1)(i) of §1910.1200  
Carc. 1B: Carcinogenicity, Category 1B, H350  
STOT RE 1: Specific target organ toxicity — Repeated exposure, Hazard Category 1 (Inhalation), H372
- 2.2 Label elements:**  
**29 CFR 1910.1200:**  
**Danger**
- Hazard statements:**  
H350 - May cause cancer.  
H372 - Causes damage to organs through prolonged or repeated exposure (Inhalation).
- Precautionary statements:**  
P101: If medical advice is needed, have product container or label at hand.  
P102: Keep out of reach of children.  
P201: Obtain special instructions before use.  
P260: Do not breathe vapours  
P270: Do not eat, drink or smoke when using this product.  
P308+P313: IF exposed or concerned: Get medical advice/attention.  
P314: Get medical advice/attention if you feel unwell.  
P501: Dispose of the contents/containers according to the local, state and federal regulations.
- Substances that contribute to the classification**  
Quartz (RCS > 10%); Titanium dioxide (aerodynamic diameter ≤ 10 µm)
- Acute Toxicity Estimate (ATE mix):**  
34.01 % (oral), 40.68 % (dermal), 46.8 % (lc50 inhalation vapour) of the mixture consists of ingredient(s) of unknown toxicity
- Additional labeling:**

- CONTINUED ON NEXT PAGE -



SECTION 2: HAZARD(S) IDENTIFICATION (continued)



**WARNING**

Federal Hazardous Substances Act (FHSA) >> Chronic toxicity (Carcinogens)  
May cause cancer. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep out of reach of children. Store locked up.

**FIRST AID TREATMENT**

IF exposed or concerned: Get medical advice/attention.

Contains : Quartz (RCS > 10%); Titanium dioxide (aerodynamic diameter ≤ 10 µm).

This product can expose you to chemicals including Quartz (RCS > 10%) (silica, crystalline (airborne particles of respirable size)); Titanium dioxide (aerodynamic diameter ≤ 10 µm), which is [are] known to the State of California to cause cancer, and methanol, which is [are] known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

**2.3 Hazards not otherwise classified (HNOC):**

Non-applicable

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

**3.1 Substances:**

Non-applicable

**3.2 Mixtures:**

**Chemical description:** Aqueous mixture composed of chemical products for coatings

**Components:**

Remaining components are non-hazardous and/or present at amounts below reportable limits. The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200. Therefore, in accordance with Appendix D to § 1910.1200, the product contains:

| Identification      | Chemical name/Classification  | Concentration        |
|---------------------|---|----------------------|
| CAS: 7732-18-5      | <b>Water</b>  | <b>50 - &lt;75%</b>  |
| CAS: Non-applicable | <b>Acrylic polymer</b>  | <b>10 - &lt;25%</b>  |
| CAS: 14808-60-7     | <b>Quartz (RCS &gt; 10%)</b><br>Carc. 1B: H350; STOT RE 1: H372 - Danger                      | <b>10 - &lt;25%</b>  |
| CAS: 471-34-1       | <b>Calcium Carbonate</b>  | <b>2.5 - &lt;10%</b> |
| CAS: 13463-67-7     | <b>Titanium dioxide (aerodynamic diameter ≤ 10 µm)</b><br>Carc. 2: H351 - Warning             | <b>2.5 - &lt;10%</b> |
| CAS: 67-56-1        | <b>methanol</b><br>Acute Tox. 3: H301+H311+H331; Flam. Liq. 2: H225; STOT SE 1: H370 - Danger | <b>2.5 - &lt;10%</b> |
| CAS: 25265-77-4     | <b>Isobutyric acid, monoester with 2,2,4-trimethylpentane-1,3-diol</b>                        | <b>1 - &lt;2.5%</b>  |

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

SECTION 4: FIRST-AID MEASURES

**4.1 Description of necessary measures:**

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

**By inhalation:**

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance.

**By skin contact:**



## SF-293 - SUPER FLOOR ANTI SLIP SILVER



### SECTION 4: FIRST-AID MEASURES (continued)

This product is not classified as hazardous when in contact with the skin. However, in case of skin contact it is recommended to remove contaminated clothes and shoes, rinse the skin or shower the person affected if necessary thoroughly with cold water and neutral soap. In case of serious reaction consult a doctor.

**By eye contact:**

Rinse eyes thoroughly with water for at least 15 minutes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, as this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

**By ingestion/aspiration:**

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

**4.2 Most important symptoms/effects, acute and delayed:**

Acute and delayed effects are indicated in sections 2 and 11.

**4.3 Indication of immediate medical attention and special treatment needed, if necessary:**

Non-applicable

### SECTION 5: FIRE-FIGHTING MEASURES

**5.1 Suitable (and unsuitable) extinguishing media:**

**Suitable extinguishing media:**

Product is non-flammable under normal conditions of storage, handling and use. In the case of combustion as a result of improper handling, storage or use preferably use polyvalent powder extinguishers (ABC powder), in accordance with the Regulation on fire protection systems.

**Unsuitable extinguishing media:**

Non-applicable

**5.2 Specific hazards arising from the chemical:**

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

**5.3 Special protective equipment and precautions for fire-fighters:**

Depending on the magnitude of the fire it may be necessary to use full protective clothing and Self Contained Breathing Apparatus. Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...)

**Additional provisions:**

As in any fire, prevent human exposure to fire, smoke, fumes or products of combustion. Only properly trained personnel should be involved in firefighting. Evacuate nonessential personnel from the fire area. Destroy any source of ignition. In case of fire, refrigerate the storage containers and tanks for products susceptible to inflammation. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

### SECTION 6: ACCIDENTAL RELEASE MEASURES

**6.1 Personal precautions, protective equipment and emergency procedures:**

**For non-emergency personnel:**

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Remove any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

**For emergency responders:**

Wear protective equipment. Keep unprotected persons away. See section 8.

**6.2 Environmental precautions:**

This product is not classified as hazardous to the environment. Keep product away from drains, surface and underground water.

**6.3 Methods and materials for containment and cleaning up:**

For accidental releases in excess of reportable quantities (RQ) (Table 302.4), refer to 40 CFR 302 for detailed instructions concerning reporting requirements and notify the National Response Center (800) 424-8802.

- CONTINUED ON NEXT PAGE -



**SF-293 - SUPER FLOOR ANTI SLIP SILVER**



**SECTION 6: ACCIDENTAL RELEASE MEASURES (continued)**

Prevent the entrance of product in drains, sewers or watercourses. Absorb the spill using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. Collect the product in appropriate containers and manage it according to current legislation.

Spillages in water or sea:

Small spillages:

Contain spillage using barriers or similar equipment. Use suitable absorbents for collection and treat the waste in accordance with current regulations.

Large spillages:

If possible, contain spillage in open water using barriers or similar equipment. If this is not possible, try to control its spread and collect the product with suitable mechanical means. Always consult experts before using dispersants and make sure you have the necessary approvals if they are to be used. Treat the waste according to current regulations.

**6.4 Reference to other sections:**

See sections 8 and 13.

**SECTION 7: HANDLING AND STORAGE**

**7.1 Precautions for safe handling:**

A.- General precautions for safe use

Comply with the current legislation concerning the prevention of industrial risks with regards manually handling weights. Maintain order, cleanliness and dispose of using safe methods (section 6).

B.- Technical recommendations for the prevention of fires and explosions

Avoid the evaporation of the product as it contains flammable substances, which could form flammable vapour/air mixtures in the presence of sources of ignition. Control sources of ignition (mobile phones, sparks,...) and transfer at slow speeds to avoid the creation of electrostatic charges. Consult section 10 for conditions and materials that should be avoided.

C.- Technical recommendations on general occupational hygiene

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

It is recommended to have absorbent material available at close proximity to the product (See subsection 6.3)

**7.2 Conditions for safe storage, including any incompatibilities:**

A.- Specific storage requirements

Minimum Temp.: 45 °F

Maximum Temp.: 100 °F

Maximum time: 24 Months

NFPA 30: IIIB

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

**7.3 Specific end use(s):**

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

**8.1 Control parameters:**

Substances whose occupational exposure limits have to be assessed in the workplace:

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000):

| Identification   | Occupational exposure limits |         |                       |
|--|------------------------------|---------|-----------------------|
|  | 8-hour TWA PEL               |         | 15 mg/m <sup>3</sup>  |
| Titanium dioxide (aerodynamic diameter ≤ 10 µm)<br>CAS: 13463-67-7 | Ceiling Values - TWA PEL     |         |                       |
| methanol <sup>(1)</sup><br>CAS: 67-56-1                            | 8-hour TWA PEL               | 200 ppm | 260 mg/m <sup>3</sup> |
|  | Ceiling Values - TWA PEL     |         |                       |

- CONTINUED ON NEXT PAGE -



SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

US. ACGIH Threshold Limit Values (2022):

| Identification   | Occupational exposure limits |          |                         |
|--|------------------------------|----------|-------------------------|
|  | TLV-TWA                      | TLV-STEL |                         |
| Quartz (RCS > 10%)<br>CAS: 14808-60-7                              |                              |          | 0.025 mg/m <sup>3</sup> |
| Titanium dioxide (aerodynamic diameter ≤ 10 µm)<br>CAS: 13463-67-7 |                              |          | 10 mg/m <sup>3</sup>    |
| methanol <sup>(1)</sup><br>CAS: 67-56-1                            | 200 ppm                      | 250 ppm  |                         |

CALIFORNIA- TABLE AC-1 PERMISSIBLE EXPOSURE LIMITS FOR CHEMICAL CONTAMINANTS:

| Identification   | Occupational exposure limits |         |  |
|--|------------------------------|---------|--|
|  | PEL                          | STEL    |  |
| Quartz (RCS > 10%)<br>CAS: 14808-60-7                              | 1                            |         |  |
| Calcium Carbonate<br>CAS: 471-34-1                                 |                              |         | 10 mg/m <sup>3</sup> (Total)<br>5 mg/m <sup>3</sup> (Respirable) |
| Titanium dioxide (aerodynamic diameter ≤ 10 µm)<br>CAS: 13463-67-7 |                              |         | 10 mg/m <sup>3</sup> (Total)<br>5 mg/m <sup>3</sup> (Respirable) |
| methanol <sup>(1)</sup><br>CAS: 67-56-1                            | 200 ppm                      | 250 ppm | 260 mg/m <sup>3</sup><br>325 mg/m <sup>3</sup>                   |

NIOSH: Immediately Dangerous To Life or Health (IDLH) Values:

| Identification   | Occupational exposure limits |            |                        |
|--|------------------------------|------------|------------------------|
|  | TWA                          | IDLH Value |                        |
| Quartz (RCS > 10%)<br>CAS: 14808-60-7                              |                              |            | 25 mg/m <sup>3</sup>   |
| Titanium dioxide (aerodynamic diameter ≤ 10 µm)<br>CAS: 13463-67-7 |                              |            | 5000 mg/m <sup>3</sup> |
| methanol <sup>(1)</sup><br>CAS: 67-56-1                            |                              | 6000 ppm   |                        |

<sup>(1)</sup> Skin

**Biological limit values:**

Biological Exposure Indices (BEIs®) - ACGIH

| Identification           | BEIs®   | Determinant       | Sampling Time |
|--------------------------|---------|-------------------|---------------|
| methanol<br>CAS: 67-56-1 | 15 mg/L | Methanol in urine | End of shift  |

**8.2 Appropriate engineering controls:**

A.- Individual protection measures, such as personal protective equipment

Always provide effective general and, when necessary, local exhaust ventilation to maintain the ambient workplace atmosphere below the exposure limits.. For more information on Personal Protection Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For additional information see subsection 7.1. All information contained herein is a recommendation, the information on clothing performance must be combined with professional judgment, and a clear understanding of the clothing application, to provide the best protection to the worker. All chemical protective clothing use must be based on a hazard assessment to determine the risks for exposure to chemicals and other hazards. Conduct hazard assessments in accordance with 29 CFR 1910.132.

B.- Respiratory protection

| Pictogram                                  | PPE  | Remarks  |
|--|--|--|
| <br>Mandatory respiratory tract protection | Filter mask for gases and vapours (Filter type: A) | Replace when there is a taste or smell of the contaminant inside the face mask. If the contaminant comes with warnings it is recommended to use isolation equipment. Use respirator in accordance with manufacturer's use limitations and OSHA standard 1910.134 (29CFR) |

C.- Specific protection for the hands

- CONTINUED ON NEXT PAGE -



**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)**

| Pictogram                     | PPE                                       | Remarks  |
|-------------------------------|---|--|
| <br>Mandatory hand protection | NON-disposable chemical protective gloves | The Breakthrough Time indicated by the manufacturer must exceed the period during which the product is being used. Do not use protective creams after the product has come into contact with skin. Use gloves in accordance with manufacturer's use limitations and OSHA standard 1910.138 (29CFR) |

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.

**D.- Eye and face protection**

| Pictogram                     | PPE         | Remarks   |
|-------------------------------|-------------|---|
| <br>Mandatory face protection | Face shield | Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing. Use this PPE in accordance with manufacturer's use limitations and OSHA standard 1910.133 (29CFR) |

**E.- Bodily protection**

| Pictogram                              | PPE   | Remarks  |
|--|---|--|
| <br>Mandatory complete body protection | Disposable clothing for protection against chemical risks | For professional use only. Clean periodically according to the manufacturer's instructions.  |
| <br>Mandatory foot protection          | Safety footwear for protection against chemical risk      | Replace boots at any sign of deterioration. Use foot protection in accordance with manufacturer's use limitations and OSHA standard 1910.136 (29CFR) |

**F.- Additional emergency measures**

It is advised to implement additional emergency equipments in workplaces that are particularly exposed to the product or in situations where risk assessments highlight the necessity of such equipments.

| Emergency measure    | Standards                                       | Emergency measure    | Standards                                      |
|----------------------|---|----------------------|--|
| <br>Emergency shower | ANSI Z358-1<br>ISO 3864-1:2011, ISO 3864-4:2011 | <br>Eyewash stations | DIN 12 899<br>ISO 3864-1:2011, ISO 3864-4:2011 |

**Environmental exposure controls:**

To comply with environmental protection regulations, it is recommended to prevent any spillage of the product and its container. For more detailed information, please refer to subsection 7.1.D.

**40 CFR Part 59 (VOC):**

V.O.C.(weight-percent): 2.66 % weight  
V.O.C. at 68 °F: 132 kg/m<sup>3</sup> (132 g/L)

**California Air Resources Board (CARB) - VOC Regulatory:**

V.O.C.(weight-percent): 2.66 % weight  
V.O.C. at 68 °F: 132 kg/m<sup>3</sup> (132 g/L)

**South Coast Air Quality Management District (AQMD) - VOC Regulatory:**

V.O.C.(weight-percent): 2.66 % weight  
V.O.C. at 68 °F: 132 kg/m<sup>3</sup> (132 g/L)

**Ozone Transport Commission (OTC) Rules - VOC Regulatory:**

V.O.C.(weight-percent): 2.66 % weight  
V.O.C. at 68 °F: 132 kg/m<sup>3</sup> (132 g/L)

**SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

\*Non-applicable due to the nature of the product, not providing information property of its hazards.

- CONTINUED ON NEXT PAGE -



**SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)**

**9.1 Information on basic physical and chemical properties:**

For complete information see the product datasheet.

**Appearance:**

|                          |  |
|--------------------------|--|
| Physical state at 68 °F: | Liquid                                   |
| Appearance:              | Viscous                                  |
| Color:                   | According to the markings on the package |
| Odor:                    | Non-applicable *                         |

**Volatility:**

|  |                         |
|--|-------------------------|
| Boiling point at atmospheric pressure: | 211 °F                  |
| Vapour pressure at 68 °F:              | 2642 Pa                 |
| Vapour pressure at 122 °F:             | 13567.85 Pa (13.57 kPa) |
| Evaporation rate at 68 °F:             | Non-applicable *        |

**Product description:**

|  |                          |
|--|--------------------------|
| Density at 68 °F:                            | 1198.4 kg/m <sup>3</sup> |
| Relative density at 68 °F:                   | 1.198                    |
| Dynamic viscosity at 68 °F:                  | Non-applicable *         |
| Kinematic viscosity at 68 °F:                | Non-applicable *         |
| Kinematic viscosity at 104 °F:               | >20.5 mm <sup>2</sup> /s |
| Concentration:                               | Non-applicable *         |
| pH:  | 8.5 - 9.5                |
| Vapour density at 68 °F:                     | Non-applicable *         |
| Partition coefficient n-octanol/water 68 °F: | Non-applicable *         |
| Solubility in water at 68 °F:                | Non-applicable *         |
| Solubility properties:                       | Non-applicable *         |
| Decomposition temperature:                   | Non-applicable *         |
| Melting point/freezing point:                | Non-applicable *         |

**Flammability:**

|                            |                           |
|----------------------------|---------------------------|
| Flash Point:               | Non Flammable (>199.4 °F) |
| Flammability (solid, gas): | Non-applicable *          |
| Autoignition temperature:  | 739 °F                    |
| Lower flammability limit:  | Non-applicable *          |
| Upper flammability limit:  | Non-applicable *          |

**Particle characteristics:**

|                             |                  |
|-----------------------------|------------------|
| Median equivalent diameter: | Non-applicable * |
|-----------------------------|------------------|

**9.2 Other information:**

**Information with regard to physical hazard classes:**

|  |                  |
|--|------------------|
| Explosive properties:  | Non-applicable * |
| Oxidising properties:  | Non-applicable * |
| Corrosive to metals:   | Non-applicable * |
| Heat of combustion:  | Non-applicable * |
| Aerosols-total percentage (by mass) of flammable components: | Non-applicable * |

**Other safety characteristics:**

|                           |                  |
|---------------------------|------------------|
| Surface tension at 68 °F: | Non-applicable * |
| Refraction index:         | Non-applicable * |

\*Non-applicable due to the nature of the product, not providing information property of its hazards.

- CONTINUED ON NEXT PAGE -



**SF-293 - SUPER FLOOR ANTI SLIP SILVER**



**SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)**

MIR (Maximum Incremental Reactivity): 0.02

\*Non-applicable due to the nature of the product, not providing information property of its hazards.

**SECTION 10: STABILITY AND REACTIVITY**

**10.1 Reactivity:**

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7 from Safety Data Sheet.

**10.2 Chemical stability:**

Chemically stable under the indicated conditions of storage, handling and use.

**10.3 Possibility of hazardous reactions:**

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

**10.4 Conditions to avoid:**

Applicable for handling and storage at room temperature:

| Shock and friction | Contact with air | Increase in temperature | Sunlight   | Humidity       |
|--------------------|------------------|-------------------------|------------|----------------|
| Not applicable     | Not applicable   | Precaution              | Precaution | Not applicable |

**10.5 Incompatible materials:**

| Acids              | Water          | Oxidising materials | Combustible materials | Others                        |
|--------------------|----------------|---------------------|-----------------------|-------------------------------|
| Avoid strong acids | Not applicable | Avoid direct impact | Not applicable        | Avoid alkalis or strong bases |

**10.6 Hazardous decomposition products:**

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO<sub>2</sub>), carbon monoxide and other organic compounds.

**SECTION 11: TOXICOLOGICAL INFORMATION**

**11.1 Information on toxicological effects:**

The experimental information related to the toxicological properties of the product itself is not available

**Dangerous health implications:**

In case of exposure that is repetitive, prolonged or at concentrations higher than recommended by the occupational exposure limits, it may result in adverse effects on health depending on the means of exposure:

A- Ingestion (acute effect):

- Acute toxicity: Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for consumption. For more information see section 3.
- Corrosivity/Irritability: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

B- Inhalation (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for inhalation. For more information see section 3.
- Corrosivity/Irritability: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

C- Contact with the skin and the eyes (acute effect):

- Contact with the skin: Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for skin contact. For more information see section 3.
- Contact with the eyes: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):

- CONTINUED ON NEXT PAGE -



**SECTION 11: TOXICOLOGICAL INFORMATION (continued)**

- Carcinogenicity: Exposure to this product can cause cancer. For more specific information on the possible health effects see section 2.  
IARC: Titanium dioxide (aerodynamic diameter  $\leq 10 \mu\text{m}$ ) (2B: Possibly carcinogenic to humans); Quartz (RCS  $> 10\%$ ) (1: Carcinogenic to humans)
- Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

E- Sensitizing effects:

- Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous with sensitising effects. For more information see section 3.
- Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

F- Specific target organ toxicity (STOT) - single exposure:

Based on available data, the classification criteria are not met, however, it does contain substances which are classified as dangerous as a result of a single exposure. For more information see section 3.

G- Specific target organ toxicity (STOT)-repeated exposure:

- Specific target organ toxicity (STOT)-repeated exposure: Serious health effects in the case of prolonged inhalation, including death, serious functional disorders or morphological changes of toxicological importance.
- Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

H- Aspiration hazard:

Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

**Other information:**

CAS 13463-67-7 Titanium dioxide (aerodynamic diameter  $\leq 10 \mu\text{m}$ ): The classification as a carcinogen by inhalation applies only to mixtures in powder form containing 1 % or more of titanium dioxide which is in the form of or incorporated in particles with aerodynamic diameter  $\leq 10 \mu\text{m}$

Contains substances that have been listed by the International Agency for Research on Cancer (IARC) as Group 1 human carcinogens. However, exposure to such substances does not occur during normal use of products in which the substance is bound to other materials, such as rubber, inks, paints, etc., in a liquid state or polymer-encapsulated.

**Specific toxicology information on the substances:**

| Identification   | Acute toxicity         |             | Genus  |
|--|------------------------|-------------|--------|
| Titanium dioxide (aerodynamic diameter $\leq 10 \mu\text{m}$ )<br>CAS: 13463-67-7  | LD50 oral              | 10000 mg/kg | Rat    |
|  | LD50 dermal            | 10000 mg/kg | Rabbit |
|  | LC50 inhalation dust   |             |        |
| Isobutyric acid, monoester with 2,2,4-trimethylpentane-1,3-diol<br>CAS: 25265-77-4 | LD50 oral              | 6517 mg/kg  | Rat    |
|  | LD50 dermal            | 15200 mg/kg | Rabbit |
|  | LC50 inhalation vapour |             |        |
| methanol<br>CAS: 67-56-1   | LD50 oral              | 100 mg/kg   |        |
|  | LD50 dermal            | 300 mg/kg   |        |
|  | LC50 inhalation vapour | 3 mg/L      |        |
| Calcium Carbonate<br>CAS: 471-34-1   | LD50 oral              | >5000 mg/kg | Rat    |
|  | LD50 dermal            |             |        |
|  | LC50 inhalation dust   |             |        |

**Acute Toxicity Estimate (ATE mix):**

| ATE mix                |                                    | Ingredient(s) of unknown toxicity |
|------------------------|------------------------------------|-----------------------------------|
| Oral                   | 2480.83 mg/kg (Calculation method) | 34.01 %                           |
| Dermal                 | 6690.23 mg/kg (Calculation method) | 40.68 %                           |
| LC50 inhalation vapour | 60 mg/L (4 h) (Calculation method) | 46.8 %                            |

**SECTION 12: ECOLOGICAL INFORMATION**

The experimental information related to the eco-toxicological properties of the product itself is not available

- CONTINUED ON NEXT PAGE -



**SF-293 - SUPER FLOOR ANTI SLIP SILVER**



**SECTION 12: ECOLOGICAL INFORMATION (continued)**

Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

**12.1 Ecotoxicity (aquatic and terrestrial, where available):**

**Acute toxicity:**

| Identification   | Concentration |                   | Species                   | Genus      |
|--|---------------|-------------------|---------------------------|------------|
| Calcium Carbonate<br>CAS: 471-34-1   | LC50          | 56000 mg/L (96 h) | Gambusia affinis          | Fish       |
|  | EC50          | Non-applicable    |                           |            |
|  | EC50          | Non-applicable    |                           |            |
| methanol<br>CAS: 67-56-1   | LC50          | 15400 mg/L (96 h) | Lepomis macrochirus       | Fish       |
|  | EC50          | Non-applicable    |                           |            |
|  | EC50          | Non-applicable    |                           |            |
| Isobutyric acid, monoester with 2,2,4-trimethylpentane-1,3-diol<br>CAS: 25265-77-4 | LC50          | 30 mg/L (96 h)    | Pimephales promelas       | Fish       |
|  | EC50          | 95 mg/L (96 h)    | Daphnia magna             | Crustacean |
|  | EC50          | 18.4 mg/L (72 h)  | Selenastrum capricornutum | Algae      |

**12.2 Persistence and degradability:**

**Substance-specific information:**

| Identification   | Degradability |                | Biodegradability |                |
|--|---------------|----------------|------------------|----------------|
|  |               |                |                  |                |
| methanol<br>CAS: 67-56-1   | BOD5          | 1236 g O2/g    | Concentration    | Non-applicable |
|  | COD           | Non-applicable | Period           | Non-applicable |
|  | BOD5/COD      | Non-applicable | % Biodegradable  | Non-applicable |
| Isobutyric acid, monoester with 2,2,4-trimethylpentane-1,3-diol<br>CAS: 25265-77-4 | BOD5          | 2.2 g O2/g     | Concentration    | Non-applicable |
|  | COD           | Non-applicable | Period           | 19 days        |
|  | BOD5/COD      | Non-applicable | % Biodegradable  | 33 %           |

**12.3 Bioaccumulative potential:**

**Substance-specific information:**

| Identification   | Bioaccumulation potential |       |
|--|---------------------------|-------|
|  |                           |       |
| methanol<br>CAS: 67-56-1   | BCF                       |       |
|  | Pow Log                   | -0.77 |
|  | Potential                 |       |
| Isobutyric acid, monoester with 2,2,4-trimethylpentane-1,3-diol<br>CAS: 25265-77-4 | BCF                       |       |
|  | Pow Log                   | 3.47  |
|  | Potential                 |       |

**12.4 Mobility in soil:**

| Identification           | Absorption/desorption |                      | Volatility |                                |
|--------------------------|-----------------------|----------------------|------------|--------------------------------|
|                          |                       |                      |            |                                |
| methanol<br>CAS: 67-56-1 | Koc                   | Non-applicable       | Henry      | 4.61E-1 Pa·m <sup>3</sup> /mol |
|                          | Conclusion            | Non-applicable       | Dry soil   | Yes                            |
|                          | Surface tension       | 2.355E-2 N/m (77 °F) | Moist soil | Yes                            |

**12.5 Results of PBT and vPvB assessment:**

Non-applicable

**12.6 Other adverse effects:**

Not described

**SECTION 13: DISPOSAL CONSIDERATIONS**

**13.1 Disposal methods:**

Wastes generated by normal household activities (e.g., routine house and yard maintenance) are excluded from the definition of hazardous waste ( Title 40 of the Code of Federal Regulations Part 261.4)

**Waste management (disposal and evaluation):**

Follow RCRA framework and EPA regulation for to ensure that hazardous waste is managed safely and properly. Waste should not be disposed of to drains. Remind, It is the responsibility of the waste generator to evaluate whether his wastes are hazardous by characteristics or listing. See section 6 for further information about Accidental release measures.

**Regulations related to waste management:**

- CONTINUED ON NEXT PAGE -



SECTION 13: DISPOSAL CONSIDERATIONS (continued)

Legislation related to waste management:

40 CFR Solid Wastes - Part 239 through 282.

State regulatory requirements for generators may be more stringent than those in the federal program. Be sure to check the state's policies.

SECTION 14: TRANSPORT INFORMATION

**Transport of dangerous goods by land:**

With regard to 49 CFR on the Transport of Dangerous Goods:

- 14.1 **UN number:** Non-applicable
- 14.2 **UN proper shipping name:** Non-applicable
- 14.3 **Transport hazard class(es):** Non-applicable
- Labels: Non-applicable
- 14.4 **Packing group, if applicable:** Non-applicable
- 14.5 **Marine pollutant:** No
- 14.6 **Special precautions which a user needs to be aware of, or needs to comply with, in connection with transport or conveyance either within or outside their premises**  
Physico-Chemical properties: see section 9
- 14.7 **Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code):** Non-applicable

**Transport of dangerous goods by sea:**

With regard to IMDG 42-24:

- 14.1 **UN number:** Non-applicable
- 14.2 **UN proper shipping name:** Non-applicable
- 14.3 **Transport hazard class(es):** Non-applicable
- Labels: Non-applicable
- 14.4 **Packing group, if applicable:** Non-applicable
- 14.5 **Marine pollutant:** No
- 14.6 **Special precautions which a user needs to be aware of, or needs to comply with, in connection with transport or conveyance either within or outside their premises**  
Special regulations: Non-applicable  
EmS Codes:  
Physico-Chemical properties: see section 9  
Limited quantities: Non-applicable  
Segregation group: Non-applicable
- 14.7 **Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code):** Non-applicable

**Transport of dangerous goods by air:**

With regard to IATA/ICAO 2026:

- 14.1 **UN number:** Non-applicable
- 14.2 **UN proper shipping name:** Non-applicable
- 14.3 **Transport hazard class(es):** Non-applicable
- Labels: Non-applicable
- 14.4 **Packing group, if applicable:** Non-applicable
- 14.5 **Marine pollutant:** No
- 14.6 **Special precautions which a user needs to be aware of, or needs to comply with, in connection with transport or conveyance either within or outside their premises**  
Physico-Chemical properties: see section 9
- 14.7 **Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code):** Non-applicable

- CONTINUED ON NEXT PAGE -



## SECTION 15: REGULATORY INFORMATION

### 15.1 Safety, health and environmental regulations specific for the product in question:

- CALIFORNIA LABOR CODE - The Hazardous Substances List: *methanol (67-56-1)*
- California Proposition 65 (the Safe Drinking Water and Toxic Enforcement Act of 1986) - Birth defects or other reproductive harm: *methanol (67-56-1)*
- California Proposition 65 (the Safe Drinking Water and Toxic Enforcement Act of 1986) - Cancer: *Quartz (RCS > 10%) (14808-60-7) - silica, crystalline (airborne particles of respirable size); Titanium dioxide (aerodynamic diameter  $\leq 10 \mu\text{m}$ ) (13463-67-7)*
- CANADA-Domestic Substances List (DSL): *Water (7732-18-5); Quartz (RCS > 10%) (14808-60-7); Calcium Carbonate (471-34-1); Titanium dioxide (aerodynamic diameter  $\leq 10 \mu\text{m}$ ) (13463-67-7); methanol (67-56-1); Isobutyric acid, monoester with 2,2,4-trimethylpentane-1,3-diol (25265-77-4)*
- CANADA-Non-Domestic Substances List (NDSL): Non-applicable
- Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA) - Reportable Quantities: *methanol (67-56-1) - U154*
- Hazardous Air Pollutants (Clean Air Act): *methanol (67-56-1)*
- Massachusetts RTK - Substance List: *Quartz (RCS > 10%) (14808-60-7); Titanium dioxide (aerodynamic diameter  $\leq 10 \mu\text{m}$ ) (13463-67-7); methanol (67-56-1)*
- Minnesota - Hazardous substances ERTK: *Quartz (RCS > 10%) (14808-60-7); Titanium dioxide (aerodynamic diameter  $\leq 10 \mu\text{m}$ ) (13463-67-7); methanol (67-56-1)*
- New Jersey Worker and Community Right-to-Know Act: *Quartz (RCS > 10%) (14808-60-7); Titanium dioxide (aerodynamic diameter  $\leq 10 \mu\text{m}$ ) (13463-67-7); methanol (67-56-1)*
- New York RTK - Substance list: *Titanium dioxide (aerodynamic diameter  $\leq 10 \mu\text{m}$ ) (13463-67-7); methanol (67-56-1)*
- NTP (National Toxicology Program): *Quartz (RCS > 10%) (14808-60-7)*
- OSHA Specifically Regulated Substances (29 CFR 1910.1001-1096): *Quartz (RCS > 10%) (14808-60-7)*
- Pennsylvania Worker and Community Right-to-Know Law: *Quartz (RCS > 10%) (14808-60-7); Titanium dioxide (aerodynamic diameter  $\leq 10 \mu\text{m}$ ) (13463-67-7)*
- Protective Action Criteria (PAC) with AEGLs, ERPGs, & TEELs: *Quartz (RCS > 10%) (14808-60-7); Calcium Carbonate (471-34-1); Titanium dioxide (aerodynamic diameter  $\leq 10 \mu\text{m}$ ) (13463-67-7); methanol (67-56-1); Isobutyric acid, monoester with 2,2,4-trimethylpentane-1,3-diol (25265-77-4)*
- Rhode Island - Hazardous substances RTK: *methanol (67-56-1)*
- SB-258 Cleaning Product Right to Know Act : *Quartz (RCS > 10%) (14808-60-7); Titanium dioxide (aerodynamic diameter  $\leq 10 \mu\text{m}$ ) (13463-67-7); methanol (67-56-1)*
- The Toxic Substances Control Act (TSCA) : *Water (7732-18-5); Quartz (RCS > 10%) (14808-60-7); Calcium Carbonate (471-34-1); Titanium dioxide (aerodynamic diameter  $\leq 10 \mu\text{m}$ ) (13463-67-7); methanol (67-56-1); Isobutyric acid, monoester with 2,2,4-trimethylpentane-1,3-diol (25265-77-4)*
- Toxic chemical release reporting under EPCRA section 313 (40 CFR Part 372): *methanol (67-56-1)*

#### Specific provisions in terms of protecting people or the environment:

It is recommended to use the information provided in this safety data sheet as a foundation for conducting workplace-specific risk assessments. These assessments will help establish the appropriate risk prevention measures for handling, using, storing, and disposing of this product.

#### Other legislation:

Take into consideration other applicable federal, state, and local laws and local regulations.

## SECTION 16: OTHER INFORMATION

#### Legislation related to safety data sheets:

This safety data sheet has been designed in accordance with Appendix d to §1910.1200 - Safety data sheets

#### Texts of the legislative phrases mentioned in section 2:

H350: May cause cancer.

H372: Causes damage to organs through prolonged or repeated exposure (Inhalation).

#### Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

#### 29 CFR 1910.1200:

Acute Tox. 3: H301+H311+H331 - Toxic if swallowed, in contact with skin or if inhaled.

Carc. 1B: H350 - May cause cancer.

Carc. 2: H351 - Suspected of causing cancer (Inhalation).

Flam. Liq. 2: H225 - Highly flammable liquid and vapour.

STOT RE 1: H372 - Causes damage to organs through prolonged or repeated exposure (Inhalation).

STOT SE 1: H370 - Causes damage to organs.

#### Advice related to training:

- CONTINUED ON NEXT PAGE -



SECTION 16: OTHER INFORMATION (continued)

According to 29 CFR 1910.1200, training on chemical hazards is necessary for employees using this product. This training will facilitate their understanding and interpretation of the safety data sheet, as well as the product label.

**Principal bibliographical sources:**

Occupational Safety & Health Administration (OSHA).

**Abbreviations and acronyms:**

IMDG: International maritime dangerous goods code

IATA: International Air Transport Association

ICAO: International Civil Aviation Organisation

COD: Chemical Oxygen Demand

BOD5: 5-day biochemical oxygen demand

BCF: Bioconcentration factor

LD50: Lethal Dose 50

CL50: Lethal Concentration 50

EC50: Effective concentration 50

Log-POW: Octanol-water partition coefficient

Koc: Partition coefficient of organic carbon

IARC: International Agency for Research on Cancer

Date of compilation: 8/8/2025

Revised: 1/29/2026



Manufacturer Disclaimer: The information contained in this safety data sheet ("SDS") is based on sources, technical knowledge and current legislation. Furthermore, is based on data believed to be accurate; thus, the company does not assume any liability for its accuracy. The information provided herein cannot be considered a guarantee of the properties of this product and the same is simply a description of the security requirements. The use, occupational methodology and/or conditions for users of this product are not within our awareness or control. It is ultimately the responsibility of the user(s) to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information of this SDS only refers to this product, which should not be used for purposes other than those specified. Finally, the manner in which this product is used and whether there is any infringement of patents is the sole responsibility of the user(s).

END OF SAFETY DATA SHEET