



Acrylic Painter's Caulk™ cc-753

Acrylic Sealant for Windows and Doors

Description:

Acrylic Painter's Caulk™ is an acrylic resin sealant of good performance. Ideal to seal joints in doors, windows and moldings to be painted. Creates a tight seal, highly flexible and durable to protect against penetration of air and moisture.

Meets requirement for:

Regulation 8 Organic Compounds Rule 51 (VOC)

Product Advantages:

- Good adhesion to construction materials
- Can be painted
- Mildew resistant
- Can be used to seal cracks
- 7 year warranty
- Moisture resistant
- Cleans with water
- Multi-purpose

Uses:

Acrylic Painter's Caulk™ can be used to caulk cracks around door and window frames, baseboard trim and other areas where joint movement is minimal.

Adheres to painted or unpainted surfaces:

- Wood
- Plaster
- Drywall
- Masonry

For use to seal in:

- Windows
- Doors frames
- Corner joints
- Moldings
- Siding / trim

Coverage:

Joint size in inches.

		Depth	
	Inch	1/4"	1/2"
Width	1/4"	24.8'	
	1/2"	12.4'	6.1'
	3/4"	8.1'	4'
	1"	6.1'	3'

Linear feet of sealant per 10.1 fl.oz.

Product Data:

Product Type:	Acrylic Resin
Finish color:	White
Solids (%):	73 ± 2% by weight 59 ± 2% by volume
Weight/Gallon:	12.75 ± 0.05lbs. (5.782 ± 0.02kg.)
Drying time:	
Tack free:	12-15 minutes
Final Cure:	24 hours
Sizes:	10.1 fl.oz. cartridge 5.5 fl.oz tube
Viscosity:	300,000-350000 CPS
Percent Pigment by weight:	50 ± 2%
VOC:	<100 g/L

Notice: The technical data contained herein are true and accurate to the best of our knowledge. Published technical data and instructions are subject to change without prior notice.

S.D.S.: Available upon request.

Application Method:

- 1- Surface must be free of dust, dirt and grease. Remove all loose sealant.
- 2- Apply at temperatures above 40°F (5°C) when no precipitation is expected for 72 hours.
- 3- Cut nozzle to desired bead size.
- 4- Hold gun at a 45° degree angle to the seam.
- 5- Wipe away excess with a damp cloth before surface skins.
- 6- Wait 2 hours before painting with latex paint, 24 hours if using alkyd (oil) based paint.

Note: Not recommended for use on horizontal surfaces where water may collect, or for marine use areas below water grade level.

Surface Preparation:

The surface and edges of the joint must be sound, clean, dry and free of oil, grease or other contaminants that may prevent adhesion.

Mildewed Surfaces: Any existing mildew on the surface must be completely killed and removed prior to the application of new caulk. Using a long-handled brush, scrub mildewed surface with a mixture of one quart of household bleach and three quarts of warm water. Rinse thoroughly and let dry completely.

Previously Caulked Surfaces: It is critical to remove as much old sealant as possible before applying new caulk, especially if it is cracked, eroded or pulled away from the joint.

Additional Label Information :

Cleanup: Clean up excess with damp cloth before caulk cures.

Storage: Protect from freezing; store in a cool, dry place at room temperature. Product must be used within one year of purchase.

Notice: The technical data contained herein are true and accurate to the best of our knowledge. Published technical data and instructions are subject to change without prior notice.

S.D.S.: Available upon request.

Warning!: Keep out of reach of children. Do not take internally.

For chemical emergency call ChemTrec 1-800-424-9300 (USA) or 1-703-527-3887 (International).

7-Year Limited Warranty: Satisfaction guaranteed. If product cracks, peels or separates during period of guarantee when used as directed, return sales receipt and used container to Lanco® Mfg. Corp. for product replacement. The seller will not accept liability for more than product replacement or purchase price.

LIMITATIONS & MORE INFORMATION:

Read Safety Data Sheet prior to use.

Go to www.lancopaints.com.

Protect from freezing.

