



## Fast Remover PR-110 Liquid Paint & Lacquer Remover

### Description:

**Fast Remover** is a powerful blend of strong chlorinated solvents and low range evaporation rate solvents, plus deep acting and wetting agents, to achieve a fast-acting liquid-type coating remover specially designed for dipping.

### Product Advantages:

- Liquid type
- Non-caustic
- Easy to clean
- Fast-acting
- Non-staining

### Use:

Designed for a fast-acting and quick removal of polyurethanes, enamels, lacquers, primers, and clear coats over base coat systems from wood, metal, concrete and other surfaces. Not for use on plastics.

### Surface Preparation:

All surfaces must be clean, dry prior to apply this product.

### Product Data:

Weight/Gallon:	8.68 ± 0.05 lb. (3.94 ± 0.02 kg.)
Sizes:	55 gallons 5 gallons 1 gallon 1 quart
Viscosity:	Liquid
Flash Point:	< 11°F TCC

Notice: The technical data contained herein are true and accurate to the best of our knowledge. Published technical data and instructions are subject to change without prior notice.

S.D.S.: Available upon request.

### Storage:

Protect from freezing; store in a cool, dry place at room temperature. Product must be used within one year of purchase.

### Application Method:

For best results, follow these steps:

1. Allow Lanco® Fast Remover™ PR-110 to penetrate into the old finish and do the work for you.

**Note:** Watch for the following signs;

- Softening (approximately 10 minutes for acrylic lacquers),
- Blistering (approximately 20-30 minutes for acrylic enamels, urethane enamels or epoxies).

2. When action is completed, scrape off with a flexible putty knife or squeegee, and rinse thoroughly either with water from a hose, water dipped rags or steel wool solvent-dipped rags.

3. Allow stripped and cleaned surface to dry before applying new finish. On metal and aluminum surfaces, apply to prevent rust or oxidation.

**Brushing:** Use a soft natural nylon brush, apply a heavy coat of Lanco® Fast Remover in one direction only. Let it stand for 15 to 30 minutes.

**Spraying:** Use a high-pressure spray gun.

**Dipping:** Dip the entire piece into Lanco® Fast Remover for a period of 15 to 30 minutes. Allow the remover to penetrate into the old finish and do the work for you.

**Danger/Warning:**

Do not store in heated areas or in strong sunlight.

**Precautions:** Use only in well ventilated areas. Ventilation should be enough for the limits of exposure to be less than those on the Material Safety Data Sheet. Eye irritation or dizziness are indications of over exposure. For more information refer to Lanco® Material Safety Data Sheet.

**First aid:** avoid prolonged or repeated breathing of vapor. High vapor concentrations may cause unconsciousness or even asphyxiation. Do not take internally. Swallowing may cause injury, illness or death. If swallowed do not induce vomiting; consult a physician immediately. Avoid prolonged or repeated contact with skin. Contact may cause skin irritation and dermatitis. Do not get in eyes. Keep out reach of children.

