



Tile Grout Adhesive TP-875

Adhesive and Grout for Tiles

Description:

Tile Grout Adhesive is an acrylic compound adhesive to bonds, fill, repair and seal ceramic tiles in walls and floors, available in seven different colors.

Product Advantages:

- Does not crack, shrink or fade
- To adhere loose tiles
- To seal joint in tiles
- To seal joints between equipments and tiles
- Waterproof and mildew resistant
- It will adhere permanently
- Easy to clean with water

Use:

To seal joints between tiles installed in floors or walls in kitchen and bath areas.

Colors Available:

White	TP875	Champagne	TP880
Gray	TP881	Almond	TP882
Brown	TP883	Bronze	TP884
Black	TP885		

Surface Preparation:

Surface must be free of dust, dirt, grease and mildew. Remove all loose or badly cracked sealant and paint. All surfaces must be clean, dry and free of contaminants.

Technical Data:

Product Type:	Acrylic Resin
Solids (%):	76 ± 2% by weight 58 ± 2% by volume
Weight/Gallon:	13.82 ± 0.05 lbs. (6.27 ± 0.02 kg.)
Drying Time:	To touch: 30 - 60 min. To recoat: 24 hrs.
Sizes:	5.5 oz. tube
Viscosity:	230,000 - 250,000 cps
Coverage:	Theoretical: 7 lineal feet @1/4" per tube
Pigments percent by weight:	61.90 ± 2%

Notice: The technical data contained herein are true and accurate to the best of our knowledge. Published technical data and instructions are subject to change without prior notice.

S.D.S.: Available upon request.

Storage Information:

Protect from freezing; store in a cool, dry place at room temperature. Product must be used within one year of purchase.

Application Instructions:

Mildewed surfaces: Any existing mildew on the surface must be completely killed and removed prior to the application of new product. To remove mildew scrub surface with a long-handled brush and a mixture of one quart of household bleach and three quarts of warm water. Rinse completely and let dry.

1. Thoroughly knead the tube of this product before use.
2. Apply at temperatures greater than 40 ° F (5° C).
3. Cut the tip of the tube for the size of the bead you want (we recommend 1/4 ").
4. Hold the tube at a 45 ° angle and tighten by applying even pressure to a heel seal.
5. Install the tile, depending on the case.
6. Apply again around the tile. Be sure to completely fill the area around the tile installed using your finger or a damp cloth.
7. Wait 2 minutes. Remove excess product with a damp sponge.
8. Allow to dry between 16 and 24 hours before it is exposed to water.

Cleanup: Excess uncured sealant can be cleaned with sealant with water.

Danger / Warning:

Use only with adequate ventilation. Ventilation should be sufficient to limit exposure below the limits of S.D.S.

Warning !: Keep out of the reach of children. Do not eat.

In the event of chemical emergencies, call ChemTrec 1-800-424-9300 (USA) or 1-703-527-3887 (International).

Limitations & more information:

Read Safety Data Sheet prior to use.

Go to www.lancopaints.com.

Protect from freezing.

