

WX1000
Code: DE052

DESCRIPTION: CROSSCO – WX1000 an effective floor finish emulsifier “stripper” that provides unmatched results. Will solubilize aged and built-up finishes almost instantly. May be used as a no-scrub stripper or with a conventional floor machine and pad depending on the concentration of the product and the condition of the floor.

RECOMMENDED USES: CROSSCO – WX1000 was developed to penetrate and remove multiple coats of burnished floor finish with a minimum of labor. This powerful professional stripper actually “unlocks” the Chemical bonds of acrylic and urethane fortified floor finishes.

ADVANTAGES:

- Aggressive Finish Remover
- Penetrating power
- Low Foaming
- Non-Amoniated
- No harsh odors
- Easy Rinse Formula

PRODUCT CHARACTERISTICS

Solids.....	8.0 ± 0.5%	Emulsification.....	Excellent
Color.....	Transparent Purple	Detergency	Excellent
Odor.....	None	Risibility	Excellent
pH	10.5 – 11.5	Flash Point	145oF (TCC)
Viscosity	Water thin	Biodegradability	Complete
Abrasives	None	Storage/Stability	2 years
Phosphate Content	None	Weight per Gallon	8.27 lbs./gal.
Solubility	Water	Freeze / Thaw Stability ..	Keep from freezing

WX1000

GENERAL PRODUCT INFORMATION

FOR USE	SAFETY INFORMATION								
<ul style="list-style-type: none"> - Vinyl Tile - Asphalt Tile* - Rubber Tile* - Flagstone - Ceramic Tile <ul style="list-style-type: none"> - Vinyl Asbestos - Linoleum - Concrete - Terrazzo <p>*NOTE: Asphalt tile and rubber flooring could be affected by stripping solution in high concentrations. Always test floor before proceeding.</p>	<p>Avoid contact with eyes, skin and clothing. Wear protective eyewear, gloves and footwear when handling. Avoid breathing of vapors. Combustible liquid- Avoid contact with heat, spark or open flame. Keep out of reach of children. For use by trained personnel only. Keep unauthorized personnel away when applying to floor. Keep container closed during storage. For institutional and industrial use only.</p> <p>Refer to product Material Safety Data Sheet (MSDS) prior to product use.</p>								
DIRECTIONS	AVAILABILITY								
<p>The desired concentration will depend on the build-up and age of the polish film. As a starting point dilute with cold water as follows:</p> <p><i>For Average Build Ups - Dilute 1 to 3 with cold water.</i></p> <p><i>For Moderate Build Ups - Dilute 1 to 2 with cold water.</i></p> <p><i>For Heavy Build Ups - Dilute 1 to 1 with cold water.</i></p> <p>Mop a generous solution onto the floor to be stripped. Allow solution to stand about 5 minutes keeping the floor wet at all times. If mop stripping... agitate with the mop. If using an automatic scrubber or rotary floor machine, no mop agitation is required. Pick-up the solution with a wet vacuum, automatic scrubber or clean mop. Allow floor to dry thoroughly prior to applying any sealer or finish. If desired, a rinsing step can be added.</p>	<table border="1"> <tr> <td>DE052-1</td> <td>55 GAL</td> </tr> <tr> <td>DE052-2</td> <td>5 GAL</td> </tr> <tr> <td>DE052-4</td> <td>4/ 1 GAL</td> </tr> <tr> <td>DE052-5</td> <td>12/ 32oz Bottle</td> </tr> </table>	DE052-1	55 GAL	DE052-2	5 GAL	DE052-4	4/ 1 GAL	DE052-5	12/ 32oz Bottle
DE052-1	55 GAL								
DE052-2	5 GAL								
DE052-4	4/ 1 GAL								
DE052-5	12/ 32oz Bottle								
WARANTY									
<p>Max Chemical, Inc. warrant only that this product is free of defects, since many factors which affects the results obtained from this product (such as weather, workmanship, equipment used and prior conditions of substrate) are beyond our control. We will replace at no charge any product proven to be defective within 90 days of purchase, provided it has been applied as manufacturer's specifications.</p>									