

HARRIS®

Tung • O • Var Varnish Stain

Basic Uses: interior/exterior wood surfaces



TECHNICAL DATA

VISCOSITY: 60 ± 5 KU's
WEIGHT/GALLON: 7.40 ± 5 lbs/gal
FLASH POINT: Above 100°F
SOLIDS (WEIGHT): 38%
SOLIDS (VOLUME): 27%

SIZES

1 gallon (3.785 Liters)
1 quart (.95 Liters)
½ pint (236 ML)

FINISH

Gloss (90% @ 60°)

COLOR

Light Oak
Medium Oak
Dark Oak
Mahogany
Walnut
Maple

DESCRIPTION

BASIC USES:

Tung-O-Var Varnish Stain is a highly pigmented coating for use on interior-exterior wooden surfaces such as paneling, furniture, cabinets, trim, doors, etc.

COMPOSITION AND PROPERTIES:

Tung-O-Var Varnish Stain is based on a Soya-Alkyd Resin. It dries to a very uniform color with excellent resistance to water, grease, detergents, etc.

APPLICATION

SURFACE PREPARATION:

New surfaces-sand smooth and wipe clean before starting application. Apply two (2) or three (3) coats until color desired is obtained. (Can be wiped off with a clean, lint-free cloth).

PREVIOUSLY FINISHED SURFACES:

For best results, remove all finishes back to bare wood and refinish as for new work. For recoating over sound, aged finishes, first remove all wax, grease, oil, or other foreign matter by washing with paint thinner and then with water and detergent. When surface dries, sand well with medium fine sandpaper and wipe clean. Apply one (1) or two (2) coats of this product.

METHOD OF APPLICATION:

Spray, cloth or brush. (Apply in uniform coats).

THINNING:

Normally no thinning is required. If required, use up to 1/2 pint of mineral spirits per gallon.

COVERAGE:

Approximately 500 sq.ft. per gallon, depending on surface porosity.

DRY:

At 60°-80°F and 50% R.H. it dries to touch in two (2) to three (3) hours; [one (1) hour when wiped]; hard in six (6) hours.

CLEANUP:

Clean up drips, spatters and equipment with Harris Paints mineral spirits.

PRECAUTIONS

CAUTION! Combustible. HARMFUL IF INHALED

Keep away from heat and open flame. Do not smoke. Avoid prolonged contact with skin and breathing of vapor or spray mist. Close container after each use. Use with adequate

ventilation.

Do not take internally.

KEEP OUT OF THE REACH OF CHILDREN.