SECTION 1: IDENTIFICATION

1.1 Product identifier: CC-821 - ULTRATHANE-WB WHITE

Other means of identification:

Non-applicable

1.2 Recommended use of the chemical and restrictions on use:

Relevant uses (Consumer use): Sealant
Relevant uses (Professional users): Sealant
Relevant uses (Industrial user): Sealant
Uses advised against: All uses not specified in this section or in section 7.3

1.3 Name, U.S. address, and U.S. telephone number of the chemical manufacturer, importer, or other responsible party:

Lanco Manufacturing Corp.
Urb. Aponte #5
00754 San Lorenzo - Puerto Rico - Estados Unidos
Phone: +1-787-736-4221 - Fax: +1-787-736-5313
info@lancopaints.com
http://www.lancopaints.com

1.4 Emergency phone number: CHEMTREC (US Transportation) +1-800-424-9300 | CHEMTREC (International Transportation) +1 -703-527-3887

SECTION 2: HAZARD(S) IDENTIFICATION

2.1 Classification of the substance or mixture:

29 CFR 1910.1200:

Classification of the chemical in accordance with paragraph (d)(1)(i) of §1910.1200
Carc. 2: Carcinogenicity, Category 2, H351
Repr. 1B: Reproductive toxicity, Category 1B, H360
STOT RE 1: Specific target organ toxicity, repeated exposure, Category 1, H372

2.2 Label elements:

29 CFR 1910.1200:

Danger

Hazard statements:

H351 - Suspected of causing cancer (Inhalation).
H360 - May damage fertility or the unborn child.
H372 - Causes damage to organs through prolonged or repeated exposure.

Precautionary statements:

P101: If medical advice is needed, have product container or label at hand.
P102: Keep out of reach of children.
P201: Obtain special instructions before use.
P260: Do not breathe vapours
P264: Wash thoroughly after use.
P280: Wear protective gloves/face protection/protective clothing/respiratory protection/protective footwear.
P308+P313: IF exposed or concerned: Get medical advice/attention.
P501: Dispose of the contents/containers according to the local, state and federal regulations.

Substances that contribute to the classification

BBP; Titanium dioxide (aerodynamic diameter ≤ 10 µm); Stoddard solvent, < 0.1 % EC 200-753-7; N-methyl-2-pyrrolidone

Additional labeling:

WARNING

- CONTINUED ON NEXT PAGE -

SECTION 2: HAZARD(S) IDENTIFICATION (continued)

Federal Hazardous Substances Act (FHSA) >> Chronic toxicity (Reproductive Toxicants)
May damage fertility or the unborn child. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep out of reach of children. Store locked up.
FIRST AID TREATMENT
IF exposed or concerned: Get medical advice/attention.
Contains : BBP; Titanium dioxide (aerodynamic diameter ≤ 10 µm); Stoddard solvent, < 0.1 % EC 200-753-7; N-methyl-2-pyrrolidone.
This product can expose you to chemicals including BBP; N-methyl-2-pyrrolidone, which is [are] known to the State of California to cause cancer, and Titanium dioxide (aerodynamic diameter ≤ 10 µm), which is [are] known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

2.3 Hazards not otherwise classified (HNOC):

Non-applicable

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substances:

Non-applicable

3.2 Mixtures:

Chemical description: Aqueous emulsion

Components:

Remaining components are non-hazardous and/or present at amounts below reportable limits. The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200.Therefore, in accordance with Appendix D to § 1910.1200, the product contains:

Identification	Chemical name/Classification	Concentration
CAS: 1317-65-3	**Limestone**	**25 - <50%**
CAS: 471-34-1	**Calcium Carbonate**	**10 - <25%**
CAS: 7732-18-5	**Water**	**10 - <25%**
CAS: Non-applicable	**Acrylic polymer**	**10 - <25%**
CAS: 85-68-7	**BBP** Repr. 1B: H360 - Danger	**2.5 - <10%**
CAS: 13463-67-7	**Titanium dioxide (aerodynamic diameter ≤ 10 µm)** Carc. 2: H351 - Warning	**2.5 - <10%**
CAS: 8052-41-3	**Stoddard solvent, < 0.1 % EC 200-753-7** Asp. Tox. 1: H304; Flam. Liq. 3: H226; Skin Irrit. 2: H315; STOT RE 1: H372 - Danger	**1 - <2.5%**
CAS: 872-50-4	**N-methyl-2-pyrrolidone** Eye Irrit. 2A: H319; Flam. Liq. 4: H227; Repr. 1B: H360; Skin Irrit. 2: H315; STOT SE 3: H335 - Danger	**<1%**

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

SECTION 4: FIRST-AID MEASURES

4.1 Description of necessary measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

By inhalation:

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance.

By skin contact:

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

- CONTINUED ON NEXT PAGE -

SECTION 4: FIRST-AID MEASURES (continued)

By eye contact:

Rinse eyes thoroughly with water for at least 15 minutes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, as this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

By ingestion/aspiration:

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

4.2 Most important symptoms/effects, acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of immediate medical attention and special treatment needed, if necessary:

Non-applicable

SECTION 5: FIRE-FIGHTING MEASURES

5.1 Suitable (and unsuitable) extinguishing media:

Suitable extinguishing media:

Product is non-flammable under normal conditions of storage, handling and use. In the case of combustion as a result of improper handling, storage or use preferably use polyvalent powder extinguishers (ABC powder), in accordance with the Regulation on fire protection systems.

Unsuitable extinguishing media:

Non-applicable

5.2 Specific hazards arising from the chemical:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Special protective equipment and precautions for fire-fighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and Self Contained Breathing Apparatus. Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...)

Additional provisions:

As in any fire, prevent human exposure to fire, smoke, fumes or products of combustion. Only properly trained personnel should be involved in firefighting. Evacuate nonessential personnel from the fire area. Destroy any source of ignition. In case of fire, refrigerate the storage containers and tanks for products susceptible to inflammation. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:

For non-emergency personnel:

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Remove any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

For emergency responders:

Wear protective equipment. Keep unprotected persons away. See section 8.

6.2 Environmental precautions:

This product is not classified as hazardous to the environment. Keep product away from drains, surface and underground water.

6.3 Methods and materials for containment and cleaning up:

For accidental releases in excess of reportables quantities (RQ) (Table 302.4), refer to 40 CFR 302 for detailed instructions concerning reporting requirements and notify the National Response Center (800) 424-8802.

- CONTINUED ON NEXT PAGE -

SECTION 6: ACCIDENTAL RELEASE MEASURES (continued)

Prevent the entrance of product in drains, sewers or watercourses. Absorb the spill using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. Collect the product in appropriate containers and manage it according to current legislation.
Spillages in water or sea:
Small spillages:
Contain spillage using barriers or similar equipment. Use suitable absorbents for collection and treat the waste in accordance with current regulations.
Large spillages:
If possible, contain spillage in open water using barriers or similar equipment. If this is not possible, try to control its spread and collect the product with suitable mechanical means. Always consult experts before using dispersants and make sure you have the necessary approvals if they are to be used. Treat the waste according to current regulations.

6.4 Reference to other sections:

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:

A.- General precautions for safe use

Comply with the current legislation concerning the prevention of industrial risks with regards manually handling weights. Maintain order, cleanliness and dispose of using safe methods (section 6).

B.- Technical recommendations for the prevention of fires and explosions

Avoid the evaporation of the product as it contains flammable substances, which could form flammable vapour/air mixtures in the presence of sources of ignition. Control sources of ignition (mobile phones, sparks,...) and transfer at slow speeds to avoid the creation of electrostatic charges. Consult section 10 for conditions and materials that should be avoided.

C.- Technical recommendations on general occupational hygiene

PREGNANT WOMEN SHOULD NOT BE EXPOSED TO THIS PRODUCT. Transfer in fixed places that comply with the necessary security conditions (emergency showers and eyewash stations in close proximity), using personal protection equipment, especially on the hands and face (See section 8). Limit manual transfers to containers of small amounts. Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

It is recommended to have absorbent material available at close proximity to the product (See subsection 6.3)

7.2 Conditions for safe storage, including any incompatibilities:

A.- Specific storage requirements

Minimum Temp.:	45 ºF
Maximum Temp.:	100 ºF
Maximum time:	24 Months
NFPA 30:	IIIB

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters:

Substances whose occupational exposure limits have to be assessed in the workplace:

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000):

Identification	Occupational exposure limits		
Limestone	8-hour TWA PEL		5 mg/m³
CAS: 1317-65-3	Ceiling Values - TWA PEL		
Titanium dioxide (aerodynamic diameter ≤ 10 µm)	8-hour TWA PEL		15 mg/m³
CAS: 13463-67-7	Ceiling Values - TWA PEL		

- CONTINUED ON NEXT PAGE -

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000):

Identification	Occupational exposure limits		
Stoddard solvent, < 0.1 % EC 200-753-7	8-hour TWA PEL	500 ppm	2900 mg/m³
CAS: 8052-41-3	Ceiling Values - TWA PEL		

US. ACGIH Threshold Limit Values (2022):

Identification	Occupational exposure limits		
Limestone	TLV-TWA		10 mg/m³
CAS: 1317-65-3	TLV-STEL		20 mg/m³
Titanium dioxide (aerodynamic diameter ≤ 10 µm)	TLV-TWA		10 mg/m³
CAS: 13463-67-7	TLV-STEL		
Stoddard solvent, < 0.1 % EC 200-753-7	TLV-TWA		290 mg/m³
CAS: 8052-41-3	TLV-STEL		580 mg/m³

CALIFORNIA- TABLE AC-1 PERMISSIBLE EXPOSURE LIMITS FOR CHEMICAL CONTAMINANTS:

Identification	Occupational exposure limits		
Limestone	PEL		10 mg/m³ (Total) 5 mg/m³ (Respirable)
CAS: 1317-65-3	STEL		
Calcium Carbonate	PEL		10 mg/m³ (Total) 5 mg/m³ (Respirable)
CAS: 471-34-1	STEL		
Titanium dioxide (aerodynamic diameter ≤ 10 µm)	PEL		10 mg/m³ (Total) 5 mg/m³ (Respirable)
CAS: 13463-67-7	STEL		
Stoddard solvent, < 0.1 % EC 200-753-7	PEL	100 ppm	525 mg/m³
CAS: 8052-41-3	STEL		
N-methyl-2-pyrrolidone (1)	PEL	1 ppm	4 mg/m³
CAS: 872-50-4	STEL		

NIOSH: Immediately Dangerous To Life or Health (IDLH) Values:

Identification	Occupational exposure limits		
Titanium dioxide (aerodynamic diameter ≤ 10 µm)	TWA		
CAS: 13463-67-7	IDLH Value		5000 mg/m³
Stoddard solvent, < 0.1 % EC 200-753-7	TWA		
CAS: 8052-41-3	IDLH Value		20000 mg/m³

(1) Skin

Biological limit values:

Biological Exposure Indices (BEIs®) - ACGIH

Identification	BEIs®	Determinant	Sampling Time
N-methyl-2-pyrrolidone CAS: 872-50-4	100 mg/L	5-Hydroxy-N-methyl-2-pyrrolidone in urine	End of shift

8.2 Appropriate engineering controls:

A.- Individual protection measures, such as personal protective equipment

Always provide effective general and, when necessary, local exhaust ventilation to maintain the ambient workplace atmosphere below the exposure limits.. For more information on Personal Protection Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For additional information see subsection 7.1. All information contained herein is a recommendation, the information on clothing performance must be combined with professional judgment, and a clear understanding of the clothing application, to provide the best protection to the worker. All chemical protective clothing use must be based on a hazard assessment to determine the risks for exposure to chemicals and other hazards. Conduct hazard assessments in accordance with 29 CFR 1910.132.

B.- Respiratory protection

Pictogram	PPE	Remarks
 Mandatory respiratory tract protection	Filter mask for gases and vapours (Filter type: A)	Replace when there is a taste or smell of the contaminant inside the face mask. If the contaminant comes with warnings it is recommended to use isolation equipment. Use respirator in accordance with manufacturer´s use limitations and OSHA standard 1910.134 (29CFR)

- CONTINUED ON NEXT PAGE -

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

C.- Specific protection for the hands

Pictogram	PPE	Remarks
Mandatory hand protection	Chemical protective gloves (Material: Linear low -density polyethylene (LLDPE), Breakthrough time: > 480 min, Thickness: 0.062 mm)	The Breakthrough Time indicated by the manufacturer must exceed the period during which the product is being used. Do not use protective creams after the product has come into contact with skin. Use gloves in accordance with manufacturer´s use limitations and OSHA standard 1910.138 (29CFR)

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.

D.- Eye and face protection

Pictogram	PPE	Remarks
Mandatory face protection	Face shield	Clean daily and disinfect periodically according to the manufacturer´s instructions. Use if there is a risk of splashing. Use this PPE in accordance with manufacturer´s use limitations and OSHA standard 1910.133 (29CFR)

E.- Bodily protection

Pictogram	PPE	Remarks
Mandatory complete body protection	Disposable clothing for protection against chemical risks	For professional use only. Clean periodically according to the manufacturer´s instructions.
Mandatory foot protection	Safety footwear for protection against chemical risk	Replace boots at any sign of deterioration. Use foot protection in accordance with manufacturer´s use limitations and OSHA standard 1910.136 (29CFR)

F.- Additional emergency measures

It is advised to implement additional emergency equipments in workplaces that are particularly exposed to the product or in situations where risk assessments highlight the necessity of such equipments.

Emergency measure	Standards	Emergency measure	Standards
Emergency shower	ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011	Eyewash stations	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011

Environmental exposure controls:

To comply with environmental protection regulations, it is recommended to prevent any spillage of the product and its container. For more detailed information, please refer to subsection 7.1.D.

40 CFR Part 59 (VOC):

V.O.C.(weight-percent): 3.53 % weight

V.O.C. at 68 ºF: 57 kg/m³ (57 g/L)

California Air Resources Board (CARB) - VOC Regulatory:

V.O.C.(weight-percent): 3.53 % weight

V.O.C. at 68 ºF: Non-applicable

South Coast Air Quality Management District (AQMD) - VOC Regulatory:

V.O.C.(weight-percent): 3.53 % weight

V.O.C. at 68 ºF: Non-applicable

Ozone Transport Commission (OTC) Rules - VOC Regulatory:

V.O.C.(weight-percent): 3.53 % weight

V.O.C. at 68 ºF: Non-applicable

- CONTINUED ON NEXT PAGE -

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties:

For complete information see the product datasheet.

Appearance:

Physical state at 68 ºF:	Liquid
Appearance:	Non-applicable *
Color:	White
Odor:	Non-applicable *

Volatility:

Boiling point at atmospheric pressure:	226 ºF
Vapour pressure at 68 ºF:	Non-applicable *
Vapour pressure at 122 ºF:	Non-applicable *
Evaporation rate at 68 ºF:	Non-applicable *

Product description:

Density at 68 ºF:	Non-applicable *
Relative density at 68 ºF:	Non-applicable *
Dynamic viscosity at 68 ºF:	Non-applicable *
Kinematic viscosity at 68 ºF:	Non-applicable *
Kinematic viscosity at 104 ºF:	Non-applicable *
Concentration:	Non-applicable *
pH:	7.5 - 8.5
Vapour density at 68 ºF:	Non-applicable *
Partition coefficient n-octanol/water 68 ºF:	Non-applicable *
Solubility in water at 68 ºF:	Non-applicable *
Solubility properties:	Non-applicable *
Decomposition temperature:	Non-applicable *
Melting point/freezing point:	Non-applicable *

Flammability:

Flash Point:	Non Flammable (>199.4 ºF)
Flammability (solid, gas):	Non-applicable *
Autoignition temperature:	545 ºF
Lower flammability limit:	Non-applicable *
Upper flammability limit:	Non-applicable *

Particle characteristics:

Median equivalent diameter:	Non-applicable *

9.2 Other information:

Information with regard to physical hazard classes:

Explosive properties:	Non-applicable *
Oxidising properties:	Non-applicable *
Corrosive to metals:	Non-applicable *
Heat of combustion:	Non-applicable *
Aerosols-total percentage (by mass) of flammable components:	Non-applicable *

Other safety characteristics:

Surface tension at 68 ºF:	Non-applicable *
Refraction index:	Non-applicable *

*Non-applicable due to the nature of the product, not providing information property of its hazards.

- CONTINUED ON NEXT PAGE -

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)

MIR (Maximum Incremental Reactivity): 0.03

*Non-applicable due to the nature of the product, not providing information property of its hazards.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7 from Safety Data Sheet.

10.2 Chemical stability:

Chemically stable under the indicated conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Precaution	Precaution	Not applicable

10.5 Incompatible materials:

Acids	Water	Oxidising materials	Combustible materials	Others
Avoid strong acids	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases

10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO_2), carbon monoxide and other organic compounds.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects:

The experimental information related to the toxicological properties of the product itself is not available

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than recommended by the occupational exposure limits, it may result in adverse effects on health depending on the means of exposure:

A- Ingestion (acute effect):

- Acute toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for consumption. For more information see section 3
- Corrosivity/Irritability: Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.

B- Inhalation (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for inhalation. For more information see section 3.
- Corrosivity/Irritability: Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for inhalation. For more information see section 3.

C- Contact with the skin and the eyes (acute effect):

- Contact with the skin: Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for skin contact. For more information see section 3.
- Contact with the eyes: Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.

D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):

- CONTINUED ON NEXT PAGE -

SECTION 11: TOXICOLOGICAL INFORMATION (continued)

- Carcinogenicity: Exposure to this product can cause cancer. For more specific information on the possible health effects see section 2.
  IARC: BBP (3: Not classifiable as to its carcinogenicity to humans); Stoddard solvent, < 0.1 % EC 200-753-7 (3: Not classifiable as to its carcinogenicity to humans); Titanium dioxide (aerodynamic diameter ≤ 10 µm) (2B: Possibly carcinogenic to humans)
- Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- Reproductive toxicity: May damage fertility or the unborn child

E- Sensitizing effects:

- Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous with sensitising effects. For more information see section 3.
- Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

F- Specific target organ toxicity (STOT) - single exposure:

Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for inhalation. For more information see section 3.

G- Specific target organ toxicity (STOT)-repeated exposure:

- Specific target organ toxicity (STOT)-repeated exposure: Serious health effects in the case of prolonged consumption, including death, serious functional disorders or morphological changes of toxicological importance.
- Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

H- Aspiration hazard:

Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.

Other information:

CAS 13463-67-7 Titanium dioxide (aerodynamic diameter ≤ 10 µm): The classification as a carcinogen by inhalation applies only to mixtures in powder form containing 1 % or more of titanium dioxide which is in the form of or incorporated in particles with aerodynamic diameter ≤ 10 µm

Specific toxicology information on the substances:

Identification	Acute toxicity		Genus
BBP CAS: 85-68-7	LD50 oral	6160 mg/kg	Mouse
	LD50 dermal		
	LC50 inhalation vapour		
Calcium Carbonate CAS: 471-34-1	LD50 oral	>5000 mg/kg	Rat
	LD50 dermal		
	LC50 inhalation dust		
Limestone CAS: 1317-65-3	LD50 oral	>5000 mg/kg	Rat
	LD50 dermal		
	LC50 inhalation dust		
Titanium dioxide (aerodynamic diameter ≤ 10 µm) CAS: 13463-67-7	LD50 oral	10000 mg/kg	Rat
	LD50 dermal	10000 mg/kg	Rabbit
	LC50 inhalation dust		
N-methyl-2-pyrrolidone CAS: 872-50-4	LD50 oral	>5000 mg/kg	Rat
	LD50 dermal	>5000 mg/kg	Rat
	LC50 inhalation vapour		

Acute Toxicity Estimate (ATE mix):

ATE mix		Ingredient(s) of unknown toxicity
Oral	>5000 mg/kg (Calculation method)	0 %
Dermal	>5000 mg/kg (Calculation method)	0 %
LC50 inhalation vapour	>20 mg/L (4 h) (Calculation method)	0 %

SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

- CONTINUED ON NEXT PAGE -

SECTION 12: ECOLOGICAL INFORMATION (continued)

Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect.
For more information see section 3.

12.1 Ecotoxicity (aquatic and terrestrial, where available):

Acute toxicity:

Identification	Concentration		Species	Genus
Calcium Carbonate	LC50	56000 mg/L (96 h)	Gambussia afinis	Fish
CAS: 471-34-1	EC50	Non-applicable		
	EC50	Non-applicable		
BBP	LC50	0.51 mg/L (96 h)	Cymatogaster aggregata	Fish
CAS: 85-68-7	EC50	1.7 mg/L (48 h)	Daphnia magna	Crustacean
	EC50	Non-applicable		
Stoddard solvent, < 0.1 % EC 200-753-7	LC50	>10 - 100 mg/L (96 h)		Fish
CAS: 8052-41-3	EC50	>10 - 100 mg/L (48 h)		Crustacean
	EC50	>10 - 100 mg/L (72 h)		Algae
N-methyl-2-pyrrolidone	LC50	832 mg/L (96 h)	Lepomis macrochirus	Fish
CAS: 872-50-4	EC50	4897 mg/L (48 h)	Daphnia magna	Crustacean
	EC50	500 mg/L (72 h)	Scenedesmus subspicatus	Algae

Chronic toxicity:

Identification	Concentration		Species	Genus
BBP	NOEC	0.2 mg/L	Oncorhynchus mykiss	Fish
CAS: 85-68-7	NOEC	0.28 mg/L	Daphnia magna	Crustacean
N-methyl-2-pyrrolidone	NOEC	Non-applicable		
CAS: 872-50-4	NOEC	12.5 mg/L	Daphnia magna	Crustacean

12.2 Persistence and degradability:

Substance-specific information:

Identification	Degradability		Biodegradability	
BBP	BOD5	Non-applicable	Concentration	100 mg/L
CAS: 85-68-7	COD	Non-applicable	Period	14 days
	BOD5/COD	Non-applicable	% Biodegradable	88 %
N-methyl-2-pyrrolidone	BOD5	1.09 g O2/g	Concentration	100 mg/L
CAS: 872-50-4	COD	1.6 g O2/g	Period	28 days
	BOD5/COD	0.68	% Biodegradable	73 %

12.3 Bioaccumulative potential:

Substance-specific information:

Identification	Bioaccumulation potential	
BBP	BCF	255
CAS: 85-68-7	Pow Log	4.91
	Potential	High
N-methyl-2-pyrrolidone	BCF	0.23
CAS: 872-50-4	Pow Log	-0.46
	Potential	Low

12.4 Mobility in soil:

Identification	Absorption/desorption		Volatility	
BBP	Koc	2572	Henry	1.27E-1 Pa·m³/mol
CAS: 85-68-7	Conclusion	Low	Dry soil	Yes
	Surface tension	Non-applicable	Moist soil	Yes
N-methyl-2-pyrrolidone	Koc	Non-applicable	Henry	Non-applicable
CAS: 872-50-4	Conclusion	Non-applicable	Dry soil	Non-applicable
	Surface tension	4.007E-2 N/m (77 ºF)	Moist soil	Non-applicable

12.5 Results of PBT and vPvB assessment:

Non-applicable

12.6 Other adverse effects:

- CONTINUED ON NEXT PAGE -

SECTION 12: ECOLOGICAL INFORMATION (continued)

Not described

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Disposal methods:

Wastes generated by normal household activities (e.g., routine house and yard maintenance) are excluded from the definition of hazardous waste (Title 40 of the Code of Federal Regulations Part 261.4)

Waste management (disposal and evaluation):

Follow RCRA framework and EPA regulation for to ensure that hazardous waste is managed safely and properly.Waste should not be disposed of to drains. Remind, It is the responsibility of the waste generator to evaluate whether his wastes are hazardous by characteristics or listing.See section 6 for further information about Accidental release measures.

Regulations related to waste management:

Legislation related to waste management:

40 CFR Solid Wastes - Part 239 through 282.
State regulatory requirements for generators may be more stringent than those in the federal program. Be sure to check the state´s policies.

SECTION 14: TRANSPORT INFORMATION

Transport of dangerous goods by land:

With regard to 49 CFR on the Transport of Dangerous Goods:



14.1	**UN number:**	UN3082
14.2	**UN proper shipping name:**	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (BBP)
14.3	**Transport hazard class(es):**	9
	Labels:	9
14.4	**Packing group, if applicable:**	III
14.5	**Marine pollutant:**	Yes

14.6 Special precautions which a user needs to be aware of, or needs to comply with, in connection with transport or conveyance either within or outside their premises

Physico-Chemical properties: see section 9

Limited quantities: 5 L

Under 49 CFR 171.4, Except when transporting aboard a vessel, the requirements of this subchapter specific to marine pollutants do not apply to non-bulk packagings transported by motor vehicles, rail cars, and aircraft

14.7 Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code): Non-applicable

Transport of dangerous goods by sea:

With regard to IMDG 42-24:

- CONTINUED ON NEXT PAGE -

SECTION 14: TRANSPORT INFORMATION (continued)

14.1	**UN number:**	UN3082
14.2	**UN proper shipping name:**	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (BBP)
14.3	**Transport hazard class(es):**	9
	Labels:	9
14.4	**Packing group, if applicable:**	III
14.5	**Marine pollutant:**	Yes
14.6	**Special precautions which a user needs to be aware of, or needs to comply with, in connection with transport or conveyance either within or outside their premises**	
	Special regulations:	375, 335, 274, 969
	EmS Codes:	F-A, S-F
	Physico-Chemical properties:	see section 9
	Limited quantities:	5 L
	Segregation group:	Non-applicable
14.7	**Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code):**	Non-applicable

Transport of dangerous goods by air:

With regard to IATA/ICAO 2026:

14.1	**UN number:**	UN3082
14.2	**UN proper shipping name:**	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (BBP)
14.3	**Transport hazard class(es):**	9
	Labels:	9
14.4	**Packing group, if applicable:**	III
14.5	**Marine pollutant:**	Yes
14.6	**Special precautions which a user needs to be aware of, or needs to comply with, in connection with transport or conveyance either within or outside their premises**	
	Physico-Chemical properties:	see section 9
14.7	**Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code):**	Non-applicable

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations specific for the product in question:

- CONTINUED ON NEXT PAGE -

SECTION 15: REGULATORY INFORMATION (continued)

- CALIFORNIA LABOR CODE - The Hazardous Substances List: *BBP (85-68-7)* ; *Stoddard solvent, < 0.1 % EC 200-753-7 (8052-41-3)*
- California Proposition 65 (the Safe Drinking Water and Toxic Enforcement Act of 1986) - Birth defects or other reproductive harm: *BBP (85-68-7)* ; *N-methyl-2-pyrrolidone (872-50-4)*
- California Proposition 65 (the Safe Drinking Water and Toxic Enforcement Act of 1986) - Cancer: *Titanium dioxide (aerodynamic diameter ≤ 10 µm) (13463-67-7)*
- CANADA-Domestic Substances List (DSL): *Calcium Carbonate (471-34-1)* ; *Water (7732-18-5)* ; *BBP (85-68-7)* ; *Titanium dioxide (aerodynamic diameter ≤ 10 µm) (13463-67-7)* ; *Stoddard solvent, < 0.1 % EC 200-753-7 (8052-41-3)* ; *N-methyl-2-pyrrolidone (872-50-4)*
- CANADA-Non-Domestic Substances List (NDSL): *Limestone (1317-65-3)*
- Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA) - Reportable Quantities: *BBP (85-68-7) - 100 lb*
- Hazardous Air Pollutants (Clean Air Act): Non-applicable
- Massachusetts RTK - Substance List: *Limestone (1317-65-3)* ; *BBP (85-68-7)* ; *Titanium dioxide (aerodynamic diameter ≤ 10 µm) (13463-67-7)* ; *Stoddard solvent, < 0.1 % EC 200-753-7 (8052-41-3)* ; *N-methyl-2-pyrrolidone (872-50-4)*
- Minnesota - Hazardous substances ERTK: *Limestone (1317-65-3)* ; *Titanium dioxide (aerodynamic diameter ≤ 10 µm) (13463-67-7)* ; *Stoddard solvent, < 0.1 % EC 200-753-7 (8052-41-3)*
- New Jersey Worker and Community Right-to-Know Act: *Limestone (1317-65-3)* ; *BBP (85-68-7)* ; *Titanium dioxide (aerodynamic diameter ≤ 10 µm) (13463-67-7)* ; *Stoddard solvent, < 0.1 % EC 200-753-7 (8052-41-3)* ; *N-methyl-2-pyrrolidone (872-50-4)*
- New York RTK - Substance list: *BBP (85-68-7)* ; *Titanium dioxide (aerodynamic diameter ≤ 10 µm) (13463-67-7)* ; *Stoddard solvent, < 0.1 % EC 200-753-7 (8052-41-3)*
- NTP (National Toxicology Program): *Stoddard solvent, < 0.1 % EC 200-753-7 (8052-41-3)*
- OSHA Specifically Regulated Substances (29 CFR 1910.1001-1096): Non-applicable
- Pennsylvania Worker and Community Right-to-Know Law: *Limestone (1317-65-3)* ; *Titanium dioxide (aerodynamic diameter ≤ 10 µm) (13463-67-7)* ; *Stoddard solvent, < 0.1 % EC 200-753-7 (8052-41-3)* ; *N-methyl-2-pyrrolidone (872-50-4)*
- Protective Action Criteria (PAC) with AEGLs, ERPGs, & TEELs: *Calcium Carbonate (471-34-1)* ; *BBP (85-68-7)* ; *Titanium dioxide (aerodynamic diameter ≤ 10 µm) (13463-67-7)* ; *Stoddard solvent, < 0.1 % EC 200-753-7 (8052-41-3)* ; *N-methyl-2-pyrrolidone (872-50-4)*
- Rhode Island - Hazardous substances RTK: *BBP (85-68-7)*
- SB-258 Cleaning Product Right to Know Act : *Titanium dioxide (aerodynamic diameter ≤ 10 µm) (13463-67-7)* ; *Stoddard solvent, < 0.1 % EC 200-753-7 (8052-41-3)* ; *N-methyl-2-pyrrolidone (872-50-4)*
- The Toxic Substances Control Act (TSCA) : *Limestone (1317-65-3)* ; *Calcium Carbonate (471-34-1)* ; *Water (7732-18-5)* ; *BBP (85-68-7)* ; *Titanium dioxide (aerodynamic diameter ≤ 10 µm) (13463-67-7)* ; *Stoddard solvent, < 0.1 % EC 200-753-7 (8052-41-3)* ; *N-methyl-2-pyrrolidone (872-50-4)*
- Toxic chemical release reporting under EPCRA section 313 (40 CFR Part 372): *N-methyl-2-pyrrolidone (872-50-4)*

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information provided in this safety data sheet as a foundation for conducting workplace-specific risk assessments. These assessments will help establish the appropriate risk prevention measures for handling, using, storing, and disposing of this product.

Other legislation:

Take into consideration other applicable federal, state, and local laws and local regulations.

SECTION 16: OTHER INFORMATION

Legislation related to safety data sheets:

This safety data sheet has been designed in accordance with Appendix d to §1910.1200 - Safety data sheets

Texts of the legislative phrases mentioned in section 2:

H360: May damage fertility or the unborn child.
H372: Causes damage to organs through prolonged or repeated exposure.
H351: Suspected of causing cancer (Inhalation).

Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

29 CFR 1910.1200:

- CONTINUED ON NEXT PAGE -

SECTION 16: OTHER INFORMATION (continued)

Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways.
Carc. 2: H351 - Suspected of causing cancer (Inhalation).
Eye Irrit. 2A: H319 - Causes serious eye irritation.
Flam. Liq. 3: H226 - Flammable liquid and vapour.
Flam. Liq. 4: H227 - Combustible liquid.
Repr. 1B: H360 - May damage fertility or the unborn child.
Skin Irrit. 2: H315 - Causes skin irritation.
STOT RE 1: H372 - Causes damage to organs through prolonged or repeated exposure.
STOT SE 3: H335 - May cause respiratory irritation.

Advice related to training:

According to 29 CFR 1910. 1200, training on chemical hazards is necessary for employees using this product. This training will facilitate their understanding and interpretation of the safety data sheet, as well as the product label.

Principal bibliographical sources:

Occupational Safety & Health Administration (OSHA).

Abbreviations and acronyms:

IMDG: International maritime dangerous goods code
IATA: International Air Transport Association
ICAO: International Civil Aviation Organisation
COD: Chemical Oxygen Demand
BOD5: 5-day biochemical oxygen demand
BCF: Bioconcentration factor
LD50: Lethal Dose 50
CL50: Lethal Concentration 50
EC50: Effective concentration 50
Log-POW: Octanol-water partition coefficient
Koc: Partition coefficient of organic carbon
IARC: International Agency for Research on Cancer

Date of compilation: 7/11/2019
Revised: 1/29/2026

Manufacturer Disclaimer: The information contained in this safety date sheet ("SDS") is based on sources, technical knowledge and current legislation. Furthermore, is based on data believed to be accurate; thus, the company does not assume any liability for its accuracy. The information provided herein cannot be considered a guarantee of the properties of this product and the same is simply a description of the security requirements. The use, occupational methodology and/or conditions for users of this product are not within our awareness or control. It is ultimately the responsibility of the user(s) to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information of this SDS only refers to this product, which should not be used for purposes other than those specified. Finally, the manner in which this product is used and whether there is any infringement of patents is the sole responsibility of the user(s).

END OF SAFETY DATA SHEET