



Contact Cement TP-878

Consumer Grade Contact Adhesive

Description:

Contact Cement TP-878 is a fast drying, high solids, high strength, contact cement for small applications, formulated with solvent based Chloroprene Rubber, for hand craft and repairs in natural color. Brush-grade rubber in a volatile solvent that resists water, heat, oil, grease and most chemical.

Product Advantages:

- Self curing and air-drying
- Brush grade
- Fast dry
- Permanent bond
- Resistant to heat, water and oil
- Resists most chemicals

Use:

For residential use, to repair and bond decorative laminates, jewelry, leather and many other similar and dissimilar materials.

Surface Preparation:

All surfaces to be bonded must be clean, dry and free of contaminants such as dirt, oil and grease films.

Product Data:

Product Type:	Chloroprene Rubber
Finish Color:	Clear
Solids (%):	25 ± 2% by weight 17 ± 2% by volume
Weight/Gallon:	6.78 ± 0.05 lbs. (2.90 ± 0.02 kg.)
Open Time:	Up to 30 minutes
Drying Time:	10-15 minutes
Sizes:	1 FL. OZ.
Viscosity:	1,900 - 2,100 CPS
Specific Gravity:	0.81

Notice: The technical data contained herein are true and accurate to the best of our knowledge. Published technical data and instructions are subject to change without prior notice.

S.D.S.: Available upon request.

Storage Information:

Protect from freezing; store in a cool, dry place at room temperature. Product must be used within one year of purchase.

Method of Application:

For best results, follow these steps:

1. Stir thoroughly. Apply at temperatures above 65 °F (18 °C).
2. Surfaces must be clean, dry and free from loose or foreign matter.
3. Apply Lanco® Contact Cement to both surfaces and allow ten to fifteen minutes to dry. Avoid excessive drying.
4. Align parts exactly before pressing surfaces together; repositioning is impossible once contact is made.
5. Press parts firmly together by hand or mechanical roller.
6. Keep container tightly closed when contact cement is not in use. Avoid storage at temperatures above 100 °F (38 °C) or over six months.

Danger / Warning:

Use only with adequate ventilation. Ventilation must be sufficient to limit exposure below S.D.S. limits.

Caution: Contains petroleum distillates, acetone, toluene, M.E.K. (methyl ethyl ketone), heptane and hexane. Flammable vapors may cause flash fire. Before applying, extinguish pilot lights, shut off electrically operated appliances and eliminate other sources of flame or sparks and leave off until area is clear of vapors. Do not smoke. Close container tightly after each use. Provide adequate ventilation during application and drying cycle.

Warning!: Keep out of reach of children. Do not take internally.

For chemical emergency call ChemTrec 1-800-424-9300 (USA) or 1-703-527-3887 (International).

Limitations & more information:

Read Safety Data Sheet prior to use.
Go to www.lancopaints.com.
Protect from freezing.



-
- **NORTH AMERICA** • 600 Mid Florida Drive Airport Industrial Park of Orlando, Florida 32824 • Tel. (407) 240-4000 Fax (407) 240-4046
 - **CARIBBEAN & SOUTH AMERICA** • Urb. Aponte #5, San Lorenzo, Puerto Rico USA 00754 • Tel. (787) 736-4221 Fax (787) 736-5313
 - **CENTRAL AMERICA** • Zona Industrial Bes, lote #4, El Coyol de Alajuela, Costa Rica • Tel. (506) 2438-2257 Fax (506) 2438-2162