



Lacquer Thinner LT-100

Fast Evaporating Lacquer Thinner

Description:

Lacquer Thinner LT-100 is a high performance thinner for use with nitrocellulose, acrylic and vinyl lacquers. Used for cleaning spray equipment and tools. Recommended for cleaning of contact cement.

Product Advantages:

- 100% virgin
- High Quality
- Crystal Clear
- Non-staining

Uses:

To reduce nitrocellulose lacquer and lacquer base sealers. Excellent for cleaning pure bristle brushes and spray equipment and tools. Also recommended for cleaning of contact cements.

Storage:

Protect from freezing; store in a cool, dry place at room temperature. Product must be used within one year of purchase.

Product Data:

Weight/Gallon:	7.08 ± 0.05 lb. (3.21 ± 0.02 kg.)
Sizes:	55 gallons 5 gallons 1 gallon
Viscosity:	Liquid
Flash Point:	< 20°F TCC

Notice: The technical data contained herein are true and accurate to the best of our knowledge. Published technical data and instructions are subject to change without prior notice.

S.D.S.: Available upon request.

Warning!:

Prior to use refer to S.D.S. For safety data and summary of HMIS rating code. For S.D.S. Sheet, please visit www.lancopaints.com.

Hazard Statement:

Important: Contains petroleum distillates. Use only in well ventilated area. Keep away from heat and open flame. Avoid prolonged contact with skin eyes, if swallowed, do not induce vomiting. Call physician immediately.

Danger: In the event, of contact with eyes flush with water for 15 minutes. Get prompt medical attention. Keep out of reach of children. Keep away from heat, sparks and open flame. Vapor is heavier than air. Prevent build up of vapors - open all windows and door - use only with cross ventilation. Extinguish all flames and pilot lights and turn off stoves, heaters, electric motors and eliminate all other sources of ignition (including static sparks) during use and until all vapors are gone. Keep container closed when not in use.

Precautionary Statements:

Important: Use only with adequate ventilation. Ventilation must be sufficient to limit exposure below MSDS limits.

Warning!: Eye irritation and dizziness are indications of overexposure. Refer to Lanco® materials safety data sheet. Avoid prolonged or repeated breathing of vapor. It is important to use adequate ventilation as high vapor concentration may cause unconsciousness or even asphyxiation. Do not take internally. Swallowing may cause injury, illness or death.

Caution: Avoid prolonged or repeated contact with skin. Contact may cause skin irritation and dermatitis. Do not get in eyes. Will cause discomfort and irritation. Do not eat, drink or smoke in work area.

Notice: Reports have associated repeated and prolonged occupational over exposure to solvents with permanent brain and nervous system damage, peripheral nervous tissue damage and liver abnormalities. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

Warning: May be harmful if inhaled or ingested. Irritating to skin and eyes. Always wear respiratory protection (NIOSH MSHA TC 23C or equivalent). Vapors are harmful.

First Aid:

Inhalation overexposure: Remove patient to fresh air, if breathing stops, give artificial respiration. Call a physician.

Swallowing: Seek medical attention immediately. Do not induce vomiting.

Skin contact: Remove contaminated clothing and shoes. Wash skin with warm water and soap. Wash clothes and air out shoes.

Precaution: Consult material safety data sheet for additional information. Keep out of reach of children.

