



M.I.K. Methyl Isobutyl Ketone MI-100

Solvent for Nitrocellulose, High Solids Coating and Paints

Description:

M.I.K. Methyl Ethyl Ketone is a colorless liquid solvent with a pleasant odor. It is both a medium-boiling and a medium-evaporating solvent.

Product Advantages:

- High solvency power
- Viscosity reducer
- Ketone volume-to-weight advantage
- Prevents gelatinization in vinyl resin-based coatings

Use:

To thin high solids coatings, nitrocellulose lacquers, traffic paints, automotive, industrial and marine coatings.

Storage Information:

Consult the appropriate Material Safety Data Sheet for safety and handling guidelines for this product.

Product Data:

Weight/Gallon:	6.67 ± 0.05 lbs. (3.03 ± 0.02 kg.)
Sizes:	55 gallons 5 gallons 1 gallon
Viscosity:	0.6 cP Liquid
Boiling Point:	116.1°C @ 760mm Hg
Flash Point:	61°F (closed cup)

Notice: The technical data contained herein are true and accurate to the best of our knowledge. Published technical data and instructions are subject to change without prior notice.

S.D.S.: Available upon request.

Warning!:

Prior to use refer to S.D.S. For safety data and summary of HMIS rating code. For S.D.S. Sheet, please visit www.lancopaints.com.

Hazard Statement:

Important: Highly flammable liquid and vapor. Causes serious eye irritation. May cause drowsiness or dizziness.

Precautionary Statements:

Caution: Keep away from heat, sparks, open flames or hot surfaces. No smoking. Keep container tightly closed. Ground bond container and receiving equipment. Use explosion-proof electrical, ventilating, lighting, equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing dust, fume, gas, mist, vapors, and spray. Wash skin thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves, eye protection/face protection.

First Aid:

If on skin (or hair): Remove, take off immediately all contaminated clothing. Rinse skin with water shower.

If inhaled: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a poison center or doctor-physician if you feel unwell. If eye irritation persists: Get medical advice and attention.

In case of fire: Use water fog, foam, dry chemical or carbon dioxide (CO₂) to extinguish.

Disposal Information:

Disposal: Dispose of contents, container in accordance with local, regional, national, and international regulations.

Warning!: Keep out of the reach of children. For industrial use only.



- **NORTH AMERICA** • 600 Mid Florida Drive Airport Industrial Park of Orlando, Florida 32824 • Tel. (407) 240-4000 Fax (407) 240-4046
- **CARIBBEAN & SOUTH AMERICA** • Urb. Aponte #5, San Lorenzo, Puerto Rico USA 00754 • Tel. (787) 736-4221 Fax (787) 736-5313
- **CENTRAL AMERICA** • Zona Industrial Bes, lote #4, El Coyal de Alajuela, Costa Rica • Tel. (506) 2438-2257 Fax (506) 2438-2162
- **DOMINICAN REPUBLIC** • Parque Industrial Duarte, autopista Duarte Km 22.5 Santo Domingo Oeste, RD • Tel. (809) 826-2626