



# Wood Filler™ WF-827

## Acrylic Wood Filler in Wood Colors

### Description:

Wood Filler™ is a water based filler for wood to repair surface holes, dents and scratches on any type of wood. It's sandable, stainable and won't shrink nor crack and any excess can be easily cleaned with water.

### Product Advantages:

- Excellent anchoring to the surface
- Do not shrink or cack
- Available in 5 natural wood colors
- Strong finish
- 100% stainable
- 100% sandable
- Easy water cleanup

### Uses:

Wood Filler™ especially formulated to repair surface holes, dents and scratches on wood.

### Technical Data:

Product Type:	Acrylic
Finish:	Flat (1° - 3°) *Geometry 60°
Solids (%):	76 ± 2% by weight
Weight/Gallon:	14.85 ± 0.05 lbs. ( 6.74 ± 0.02 kg.)
Drying Time:	To touch: 15 - 20 min. To recoat: 30 - 40 min.
Sizes:	8 oz. 4 oz. 3.25 oz.
Thinning:	Is not recommended.
Viscosity:	275,000 - 290,000 cps

Notice: The technical data contained herein are true and accurate to the best of our knowledge. Published technical data and instructions are subject to change without prior notice.

S.D.S.: Available upon request.

### Surface Preparation:

All surfaces must be dry, clean, sound and free of contaminants. Remove all dirt, grease, mildew, oil, dust, and other soluble contaminants. Remove all loose detrimental foreign matter by scraping, sanding or power sanding.

### Application:

Sand down to a smooth finish with fine sandpaper following the grain. Remove all sanding dust by vacuuming or dusting the surface with a "tack" cloth.

Fill knot holes and cracks and imperfections with Lanco® wood filler; let dry. Sand the filled areas smooth and remove dust.

### Colors Available:

Pine	WF827	Mahogany	WF828
Walnut	WF829	Cedar	WF830
Oak	WF831		

