MA-3910 - MAXIMA PREMIUM WHITE/PASTEL FLAT INT/EXT



SECTION 1: IDENTIFICATION

1.1 **GHS Product identifier:** MA-3910 - MAXIMA PREMIUM WHITE/PASTEL FLAT INT/EXT

Other means of identification:

Not applicable (N/A)

Recommended use of the chemical and restrictions on use: 1.2

Relevant uses: Acrylic paint

Uses advised against: All uses not specified in this section or in section 7.3

1.3 Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party:

Lanco Manufacturing Corp.

Urb. Aponte #5

00754 San Lorenzo - Puerto Rico - Estados Unidos Phone: +1-787-736-4221 - Fax: +1-787-736-5313

info@lancopaints.com http://www.lancopaints.com

1.4 Emergency phone number: CHEMTREC (US Transportation) +1-800-424-9300 | CHEMTREC (International Transportation) +1

-703-527-3887

SECTION 2: HAZARD(S) IDENTIFICATION

2.1 Classification of the substance or mixture:

NFPA:

Health Hazards: 1 Flammability Hazards: 0 Instability Hazards: 0

Special Hazards: Not applicable (N/A)

29 CFR 1910.1200:

Classification of this product has been carried out in accordance with paragraph (d) of § 1910.1200.

Carc. 1B: Carcinogenicity, Category 1B, H350

STOT RE 1: Specific target organ toxicity, repeated exposure, Category 1, H372

2.2 Label elements:

NFPA:



29 CFR 1910.1200:

Danger



Hazard statements:

Carc. 1B: H350 - May cause cancer.

STOT RE 1: H372 - Causes damage to organs through prolonged or repeated exposure.

Precautionary statements:

P101: If medical advice is needed, have product container or label at hand.

P102: Keep out of reach of children.

P201: Obtain special instructions before use.

P260: Do not breathe vapours

P264: Wash thoroughly after use.

P308+P313: IF exposed or concerned: Get medical advice/attention.

P314: Get medical advice/attention if you feel unwell.

P501: Dispose of the contents/containers according to the local, state and federal regulations.

Substances that contribute to the classification

Titanium dioxide (aerodynamic diameter ≤ 10 µm); Kieselguhr, soda ash flux-calcined (RCS >= 10 %)

Additional labeling:

Page 1/12

Safety data sheet according to 29 CFR 1910.1200

MA-3910 - MAXIMA PREMIUM WHITE/PASTEL FLAT INT/EXT



SECTION 2: HAZARD(S) IDENTIFICATION (continued)



WARNING

Federal Hazardous Substances Act (FHSA) >> Chronic toxicity (Carcinogens)

May cause cancer. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep out of reach of children. Store locked up.

FIRST AID TREATMENT

IF exposed or concerned: Get medical advice/attention.

Contains : Titanium dioxide (aerodynamic diameter \leq 10 µm); Kieselguhr, soda ash flux-calcined (RCS >= 10 %). This product can expose you to chemicals including Titanium dioxide (aerodynamic diameter \leq 10 µm), Nepheline syenite, Kieselguhr, soda ash flux-calcined (RCS >= 10 %), which is [are] known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

2.3 Hazards not otherwise classified (HNOC):

Not applicable (N/A)

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substances:

Non-applicable

3.2 Mixtures:

Chemical description: Aqueous mixture composed of chemical products for coatings

Components:

Remaining components are non-hazardous and/or present at amounts below reportable limits. The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200. Therefore, in accordance with Appendix D to § 1910.1200, the product contains:

	Identification	Chemical name/Classification	Concentration
CAS:	7732-18-5	Water	25 - <50 %
CAS:	13463-67-7	Titanium dioxide (aerodynamic diameter ≤ 10 μm) Carc. 2: H351 - Warning	10 - <25 %
CAS:	Non-applicab <mark>le</mark>	Acrylic polymer	10 - <25 %
CAS:	37244-96-5	Nepheline syenite	10 - <25 %
CAS:	25265-77-4	Isobutyric acid, monoester with 2,2,4-trimethylpentane-1,3-diol	10 - <25 %
CAS:	68855-54-9	Kieselguhr, soda ash flux-calcined (RCS >= 10 %) Carc. 1B: H350; STOT RE 1: H372 - Danger	1 - <2.5 %

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

SECTION 4: FIRST-AID MEASURES

4.1 Description of necessary measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

By inhalation:

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance.

By skin contact:

Date of compilation: 1/22/2019 Revised: 11/14/2023 Version: 10 (Replaced 9) Page 2/12



MA-3910 - MAXIMA PREMIUM WHITE/PASTEL FLAT INT/EXT



SECTION 4: FIRST-AID MEASURES (continued)

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

By eye contact:

This product does not contain substances classified as hazardous for eye contact. Rinse eyes thoroughly for at least 15 minutes with lukewarm water, ensuring that the person affected does not rub or close their eyes.

By ingestion/aspiration:

In case of consumption, seek immediate medical assistance showing the SDS of this product.

4.2 Most important symptoms/effects, acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of immediate medical attention and special treatment needed, if necessary:

Not applicable (N/A)

SECTION 5: FIRE-FIGHTING MEASURES

5.1 Suitable (and unsuitable) extinguishing media:

Suitable extinguishing media:

Product is non-flammable under normal conditions of storage, handling and use. In the case of combustion as a result of improper handling, storage or use preferably use polyvalent powder extinguishers (ABC powder), in accordance with the Regulation on fire protection systems.

Unsuitable extinguishing media:

Non-applicable

5.2 Specific hazards arising from the chemical:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Special protective equipment and precautions for fire-fighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and individual respiratory equipment. Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...)

Additional provisions:

As in any fire, prevent human exposure to fire, smoke, fumes or products of combustion. Only properly trained personnel should be involved in firefighting. Evacuate nonessential personnel from the fire area. Destroy any source of ignition. In case of fire, refrigerate the storage containers and tanks for products susceptible to inflammation. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:

For non-emergency personnel:

Isolate leaks provided that there is no additional risk for the people performing this task. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Evacuate the area and keep out those who do not have protection.

For emergency responders:

Wear protective equipment. Keep unprotected persons away. See section 8.

6.2 Environmental precautions:

This product is not classified as hazardous to the environment. Keep product away from drains, surface and underground water.

6.3 Methods and materials for containment and cleaning up:

For accidental releases in excess of reportables quantities (RQ) (Table 302.4), refer to 40 CFR 302 for detailed instructions concerning reporting requirements and notify the National Response Center (800) 424-8802.

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

- CONTINUED ON NEXT PAGE -

6.4 Reference to other sections:

Safety data sheet according to 29 CFR 1910.1200

MA-3910 - MAXIMA PREMIUM WHITE/PASTEL FLAT INT/EXT



SECTION 6: ACCIDENTAL RELEASE MEASURES (continued)

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:

A.- General precautions for safe use

Comply with the current legislation concerning the prevention of industrial risks with regards manually handling weights. Maintain order, cleanliness and dispose of using safe methods (section 6).

B.- Technical recommendations for the prevention of fires and explosions

Product is non-flammable under normal conditions of storage, manipulation and use. It is recommended to transfer at slow speeds to avoid the generation of electrostatic charges that can affect flammable products. Consult section 10 for information on conditions and materials that should be avoided.

C.- Technical recommendations on general occupational hygiene

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

It is recommended to have absorbent material available at close proximity to the product (See subsection 6.3)

7.2 Conditions for safe storage, including any incompatibilities:

A.- Specific storage requirements

Minimum Temp.: 45 °F

Maximum Temp.: 100 °F

Maximum time: 24 Months

NFPA 30: IIIB

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters:

Substances whose occupational exposure limits have to be assessed in the workplace:

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000):

Identification	Occupa	ntional exposure lin	nits
Titanium dioxide (aerodynamic diameter ≤ 10 μm)	8-hour TWA PEL		15 mg/m ³
	Ceiling Values - TWA PEL		

US. ACGIH Threshold Limit Values (2022):

Identification	Occupa	tional exposure lin	nits
Titanium dioxide (aerodynamic diameter ≤ 10 μm)	TLV-TWA		0.2 mg/m ³
CAS: 13463-67-7	TLV-STEL		

8.2 Appropriate engineering controls:

A.- Individual protection measures, such as personal protective equipment

Always provide effective general and, when necessary, local exhaust ventilation to maintain the ambient workplace atmosphere below the exposure limits.. For more information on Personal Protection Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For additional information see subsection 7.1. All information contained herein is a recommendation, the information on clothing performance must be combined with professional judgment, and a clear understanding of the clothing application, to provide the best protection to the worker. All chemical protective clothing use must be based on a hazard assessment to determine the risks for exposure to chemicals and other hazards. Conduct hazard assessments in accordance with 29 CFR 1910.132.

B.- Respiratory protection

Date of compilation: 1/22/2019 Revised: 11/14/2023 Version: 10 (Replaced 9) Page 4/12

Safety data sheet according to 29 CFR 1910.1200

MA-3910 - MAXIMA PREMIUM WHITE/PASTEL FLAT INT/EXT



SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Pictogram	PPE	Remarks
Mandatory respiratory tract protection	Filter mask for gases and vapours	Replace when there is a taste or smell of the contaminant inside the face mask. If the contaminant comes with warnings it is recommended to use isolation equipment. Use respirator in accordance with manufacturer's use limitations and OSHA standard 1910.134 (29CFR)

C.- Specific protection for the hands

Pictogram	PPE	Remarks
Mandatory hand protection	NON-disposable chemical protective gloves	The Breakthrough Time indicated by the manufacturer must exceed the period during which the product is being used. Do not use protective creams after the product has come into contact with skin. Use gloves in accordance with manufacturer's use limitations and OSHA standard 1910.138 (29CFR)

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.

D.- Eye and face protection

Pictogram	PPE	Remarks
Mandatory face protection	Face shield	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing. Use this PPE in accordance with manufacturer's use limitations and OSHA standard 1910.133 (29CFR)

E.- Bodily protection

Pictogram	PPE	Remarks
Mandatory complete body protection	Disposable clothing for protection against chemical risks	For professional use only. Clean periodically according to the manufacturer's instructions.
Mandatory foot protection	Safety footwear for protection against chemical risk	Replace boots at any sign of deterioration. Use foot protection in accordance with manufacturer's use limitations and OSHA standard 1910.136 (29CFR)

F.- Additional emergency measures

Emergency measure	Standards	Emergency measure	Standards
•	ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011	- ∰	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011
Emergency shower		Eyewash stations	

Environmental exposure controls:

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

40 CFR Part 59 (VOC):

V.O.C.(weight-percent): 0.8 % weight
V.O.C. at 68 °F: 79 kg/m³ (79 g/L)

California Air Resources Board (CARB) - VOC Regulatory:

V.O.C.(weight-percent): 0.8 % weight

V.O.C. at 68 °F: 21.58 kg/m³ (21.58 g/L)

South Coast Air Quality Management District (AQMD) - VOC Regulatory:

V.O.C.(weight-percent): 0.8 % weight

V.O.C. at 68 °F: 21.58 kg/m³ (21.58 g/L)

Ozone Transport Commission (OTC) Rules - VOC Regulatory:

- CONTINUED ON NEXT PAGE -

Date of compilation: 1/22/2019 Revised: 11/14/2023 Version: 10 (Replaced 9) **Page 5/12**



MA-3910 - MAXIMA PREMIUM WHITE/PASTEL FLAT INT/EXT



SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

V.O.C.(weight-percent): 0.8 % weight

V.O.C. at 68 °F: 21.58 kg/m³ (21.58 g/L)

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties:

For complete information see the product datasheet.

Appearance:

Physical state at 68 °F: Liquid
Appearance: Viscous

Color: According to the markings on the package

Odor: Not available

Odour threshold: Not applicable (N/A) *

Volatility:

Boiling point at atmospheric pressure: 242 °F Vapour pressure at 68 °F: 2283 Pa

Vapour pressure at 122 °F: 12027.95 Pa (12.03 kPa) Evaporation rate at 68 °F: Not applicable (N/A) *

Product description:

Density at 68 °F: 1361.5 kg/m³

Relative density at 68 °F: 1.361

Dynamic viscosity at 68 °F:

Kinematic viscosity at 68 °F:

Not applicable (N/A) *

Not applicable (N/A) *

Not applicable (N/A) *

Not applicable (N/A) *

Concentration: Not applicable (N/A) *

pH: 8 - 9

Vapour density at 68 °F:

Partition coefficient n-octanol/water 68 °F:

Not applicable (N/A) *

Solubility in water at 68 °F:

Not applicable (N/A) *

Solubility properties:

Not applicable (N/A) *

Not applicable (N/A) *

Meting point/freezing point:

Not applicable (N/A) *

Flammability:

Flash Point: Non Flammable (>199.4 $^{\circ}$ F) Flammability (solid, gas): Not applicable (N/A) *

Autoignition temperature: 739 °F

Lower flammability limit: Not applicable (N/A) $\,^*$ Upper flammability limit: Not applicable (N/A) $\,^*$

Particle characteristics:

Median equivalent diameter: Non-applicable

9.2 Other information:

Information with regard to physical hazard classes:

Explosive properties: Not applicable (N/A) *
Oxidising properties: Not applicable (N/A) *
Corrosive to metals: Not applicable (N/A) *

*Not applicable (N/A) due to the nature of the product, not providing information property of its hazards.

Date of compilation: 1/22/2019 Revised: 11/14/2023 Version: 10 (Replaced 9) **Page 6/12**



MA-3910 - MAXIMA PREMIUM WHITE/PASTEL FLAT INT/EXT



SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)

Heat of combustion: Not applicable (N/A) * Aerosols-total percentage (by mass) of flammable Not applicable (N/A) *

components:

Other safety characteristics:

Surface tension at 68 °F:

Not applicable (N/A) *

Refraction index:

Not applicable (N/A) *

*Not applicable (N/A) due to the nature of the product, not providing information property of its hazards.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7 from Safety Data Sheet.

10.2 Chemical stability:

Chemically stable under the indicated conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable

10.5 Incompatible materials:

Acids	Water	Oxidising materials	Combustible materials	Others
Avoid strong acids	Not applicable	Not applicable	Not applicable	Avoid alkalis or strong bases

10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO₂), carbon monoxide and other organic compounds.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects:

The experimental information related to the toxicological properties of the product itself is not available

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than recommended by the occupational exposure limits, it may result in adverse effects on health depending on the means of exposure:

- A- Ingestion (acute effect):
 - Acute toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for consumption. For more information see section 3
 - Corrosivity/Irritability: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- B- Inhalation (acute effect):
 - Acute toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for inhalation. For more information see section 3.
 - Corrosivity/Irritability: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- C- Contact with the skin and the eyes (acute effect):
 - Contact with the skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for skin contact. For more information see section 3.
 - Contact with the eyes: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):



MA-3910 - MAXIMA PREMIUM WHITE/PASTEL FLAT INT/EXT



SECTION 11: TOXICOLOGICAL INFORMATION (continued)

- Carcinogenicity: Exposure to this product can cause cancer. For more specific information on the possible health effects see section 2.

IARC: Titanium dioxide (aerodynamic diameter \leq 10 µm) (2B); Quartz (1 %< RCS < 10%) (1)

- Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

E- Sensitizing effects:

- Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous with sensitising effects. For more information see section 3.
- Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- F- Specific target organ toxicity (STOT) single exposure:

Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

- G- Specific target organ toxicity (STOT)-repeated exposure:
 - Specific target organ toxicity (STOT)-repeated exposure: Serious health effects in the case of prolonged consumption, including death, serious functional disorders or morphological changes of toxicological importance.
 - Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

H- Aspiration hazard:

Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

Other information:

CAS 13463-67-7 Titanium dioxide (aerodynamic diameter $\leq 10~\mu$ m): The classification as a carcinogen by inhalation applies only to mixtures in powder form containing 1 % or more of titanium dioxide which is in the form of or incorporated in particles with aerodynamic diameter $\leq 10~\mu$ m

Specific toxicology information on the substances:

Identification	Acute toxicity		Genus
Titanium dioxide (aer <mark>odynamic</mark> diameter ≤ 10 μm)	LD50 oral	10000 mg/kg	Rat
CAS: 13463-67-7	LD50 dermal	10000 mg/kg	Rabbit
	LC50 inhalation		
Isobutyric acid, mon <mark>oester with 2,2,4-tri</mark> methylpentane-1,3-diol	LD50 oral	6517 mg/kg	Rat
CAS: 25265-77-4	LD50 dermal	15200 mg/kg	Rabbit
	LC50 inhalation	3.55 mg/L (6 h)	Rat

Acute Toxicity Estimate (ATE mix):

ATE mix		Ingredient(s) of unknown toxicity
Oral	Oral >5000 mg/kg (Calculation method) N	
Dermal	>5000 mg/kg (Calculation method)	Non-applicable
Inhalation	>20 mg/L (4 h) (Calculation method)	Non-applicable

SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

12.1 Ecotoxicity (aquatic and terrestrial, where available):

Acute toxicity:

Identification	Concentration		Species	Genus
Isobutyric acid, monoester with 2,2,4-trimethylpentane-1,3-diol	LC50	30 mg/L (96 h)	Pimephales promelas	Fish
CAS: 25265-77-4	EC50	95 mg/L (96 h)	Daphnia magna	Crustacean
	EC50	18.4 mg/L (72 h)	Selenastrum capricornutum	Algae

12.2 Persistence and degradability:

Safety data sheet according to 29 CFR 1910.1200

MA-3910 - MAXIMA PREMIUM WHITE/PASTEL FLAT INT/EXT



SECTION 12: ECOLOGICAL INFORMATION (continued)

Substance-specific information:

Identification	Degradability		Biodegradability	
Isobutyric acid, monoester with 2,2,4-trimethylpentane-1,3 -diol	BOD5	2.2 g O2/g	Concentration	Not applicable (N/A)
CAS: 25265-77-4	COD	Not applicable (N/A)	Period	19 days
	BOD5/COD	Not applicable (N/A)	% Biodegradable	33 %

12.3 Bioaccumulative potential:

Substance-specific information:

Identification		Bioaccumulation potential	
Isobutyric acid, monoester with 2,2,4-trimethylpentane-1,3-diol	BCF		
CAS: 25265-77-4	Pow Log		3.47
	Potential		

12.4 Mobility in soil:

Not available

12.5 Results of PBT and vPvB assessment:

Non-applicable

12.6 Other adverse effects:

Not described

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Disposal methods:

Wastes generated by normal household activities (e.g., routine house and yard maintenance) are excluded from the definition of hazardous waste (Title 40 of the Code of Federal Regulations Part 261.4)

Waste management (disposal and evaluation):

Follow RCRA framework and EPA regulation for to ensure that hazardous waste is managed safely and properly. Waste should not be disposed of to drains. Remind, It is the responsibility of the waste generator to evaluate whether his wastes are hazardous by characteristics or listing. See section 6 for further information about Accidental release measures.

Regulations related to waste management:

Legislation related to waste management:

40 CFR Solid Wastes - Part 239 through 282.

State regulatory requirements for generators may be more stringent than those in the federal program. Be sure to check the state's policies.

SECTION 14: TRANSPORT INFORMATION

Transport of dangerous goods by land:

With regard to 49 CFR on the Transport of Dangerous Goods:

14.1 UN number: Not applicable (N/A)
 14.2 UN proper shipping name: Not applicable (N/A)
 14.3 Transport hazard class(es): Not applicable (N/A)
 Labels: Not applicable (N/A)
 14.4 Packing group, if applicable: Not applicable (N/A)

14.5 Marine pollutant: No

14.6 Special precautions which a user needs to be aware of, or needs to comply with, in connection with transport or conveyance either within or outside their premises

Physico-Chemical properties: see section 9

14.7 Transport in bulk (according Not applicable (N/A)

to Annex II of MARPOL 73/78 and the IBC Code):

Transport of dangerous goods by sea:

Safety data sheet according to 29 CFR 1910.1200

MA-3910 - MAXIMA PREMIUM WHITE/PASTEL FLAT INT/EXT



Page 10/12

SECTION 14: TRANSPORT INFORMATION (continued)

With regard to IMDG 41-22:

14.1 UN number: Not applicable (N/A)
 14.2 UN proper shipping name: Not applicable (N/A)
 14.3 Transport hazard class(es): Not applicable (N/A)
 Labels: Not applicable (N/A)
 14.4 Packing group, if applicable: Not applicable (N/A)

14.5 Marine pollutant: No

14.6 Special precautions which a user needs to be aware of, or needs to comply with, in connection with transport or conveyance either within or outside their premises

Special regulations: Not applicable (N/A)

EmS Codes:

Physico-Chemical properties: see section 9
Limited quantities: Not applicable (N/A)
Segregation group: Not applicable (N/A)

14.7 Transport in bulk (according Not applicable (N/A)

to Annex II of MARPOL 73/78 and the IBC Code): Transport of dangerous goods by air:

With regard to IATA/ICAO 2024:

14.1 UN number: Not applicable (N/A)
14.2 UN proper shipping name: Not applicable (N/A)
14.3 Transport hazard class(es): Not applicable (N/A)
Labels: Not applicable (N/A)

14.4 Packing group, if applicable: Not applicable (N/A)

14.5 Marine pollutant: No

14.6 Special precautions which a user needs to be aware of, or needs to comply with, in connection with transport or conveyance either within or outside their premises

Physico-Chemical properties: see section 9

14.7 Transport in bulk (according Not applicable (N/A)

to Annex II of MARPOL 73/78 and the IBC Code):

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations specific for the product in question:

Date of compilation: 1/22/2019 Revised: 11/14/2023 Version: 10 (Replaced 9)

Safety data sheet according to 29 CFR 1910.1200

MA-3910 - MAXIMA PREMIUM WHITE/PASTEL FLAT INT/EXT



SECTION 15: REGULATORY INFORMATION (continued)

- CALIFORNIA LABOR CODE The Hazardous Substances List: Not applicable (N/A)
- California Proposition 65 (the Safe Drinking Water and Toxic Enforcement Act of 1986) Birth defects or other reproductive harm: Not applicable (N/A)
- California Proposition 65 (the Safe Drinking Water and Toxic Enforcement Act of 1986) Cancer: *Titanium dioxide (aerodynamic diameter* ≤ 10 µm) (13463-67-7); *Nepheline syenite (37244-96-5)*; *Kieselguhr, soda ash flux-calcined (RCS* >= 10 %) (68855-54-9)
- CANADA-Domestic Substances List (DSL): Water (7732-18-5); Titanium dioxide (aerodynamic diameter ≤ 10 µm) (13463-67-7); Nepheline syenite (37244-96-5); Isobutyric acid, monoester with 2,2,4-trimethylpentane-1,3-diol (25265-77-4); Kieselguhr, soda ash flux-calcined (RCS >= 10 %) (68855-54-9)
- CANADA-Non-Domestic Substances List (NDSL): Not applicable (N/A)
- Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA) Reportable Quantities: Not applicable (N/A)
- Hazardous Air Pollutants (Clean Air Act): Not applicable (N/A)
- Massachusetts RTK Substance List: Titanium dioxide (aerodynamic diameter $\leq 10 \ \mu m$) (13463-67-7); Nepheline syenite (37244-96-5); Kieselguhr, soda ash flux-calcined (RCS >= $10 \ \%$) (68855-54-9)
- Minnesota Hazardous substances ERTK: Titanium dioxide (aerodynamic diameter ≤ 10 µm) (13463-67-7)
- New Jersey Worker and Community Right-to-Know Act: *Titanium dioxide (aerodynamic diameter ≤ 10 µm) (13463-67-7)*
- New York RTK Substance list: *Titanium dioxide (aerodynamic diameter ≤ 10 μm) (13463-67-7)*
- NTP (National Toxicology Program): Nepheline syenite (37244-96-5); Kieselguhr, soda ash flux-calcined (RCS >= 10 %) (68855-54-9)
- OSHA Specifically Regulated Substances (29 CFR 1910.1001-1096): Nepheline syenite (37244-96-5); Kieselguhr, soda ash flux-calcined (RCS >= 10 %) (68855-54-9)
- Pennsylvania Worker and Community Right-to-Know Law: *Titanium dioxide* (aerodynamic diameter ≤ 10 μm) (13463-67-7); Kieselguhr, soda ash flux-calcined (RCS >= 10 %) (68855-54-9)
- Protective Action Criteria (PAC) with AEGLs, ERPGs, & TEELs: *Titanium dioxide (aerodynamic diameter ≤ 10 μm) (13463-67-7)*; *Isobutyric acid, monoester with 2,2,4-trimethylpentane-1,3-diol (25265-77-4)*
- Rhode Island Hazardous substances RTK: Not applicable (N/A)
- The Toxic Substances Control Act (TSCA): Water (7732-18-5); Titanium dioxide (aerodynamic diameter ≤ 10 μm) (13463-67-7); Isobutyric acid, monoester with 2,2,4-trimethylpentane-1,3-diol (25265-77-4); Kieselguhr, soda ash flux-calcined (RCS >= 10 %) (68855-54-9)
- Toxic chemical release reporting under EPCRA section 313 (40 CFR Part 372): Not applicable (N/A)

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information provided in this safety data sheet as a foundation for conducting workplace-specific risk assessments. These assessments will help establish the appropriate risk prevention measures for handling, using, storing, and disposing of this product.

Other legislation:

Take into consideration other applicable federal, state, and local laws and local regulations.

SECTION 16: OTHER INFORMATION

Legislation related to safety data sheets:

This safety data sheet has been designed in accordance with Appendix d to §1910.1200 - Safety data sheets

Texts of the legislative phrases mentioned in section 2:

H350: May cause cancer.

H372: Causes damage to organs through prolonged or repeated exposure.

Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

29 CFR 1910.1200:

Carc. 1B: H350 - May cause cancer.

Carc. 2: H351 - Suspected of causing cancer (Inhalation).

STOT RE 1: H372 - Causes damage to organs through prolonged or repeated exposure.

Advice related to training:

According to 29 CFR 1910. 1200, training on chemical hazards is necessary for employees using this product. This training will facilitate their understanding and interpretation of the safety data sheet, as well as the product label.

Principal bibliographical sources:

Occupational Safety & Health Administration (OSHA).

Abbreviations and acronyms:

Safety data sheet according to 29 CFR 1910.1200

MA-3910 - MAXIMA PREMIUM WHITE/PASTEL FLAT INT/EXT



Page 12/12

SECTION 16: OTHER INFORMATION (continued)

IMDG: International maritime dangerous goods code IATA: International Air Transport Association ICAO: International Civil Aviation Organisation

COD: Chemical Oxygen Demand

BOD5: 5-day biochemical oxygen demand

BCF: Bioconcentration factor LD50: Lethal Dose 50 CL50: Lethal Concentration 50 EC50: Effective concentration 50

Log-POW: Octanol-water partition coefficient Koc: Partition coefficient of organic carbon IARC: International Agency for Research on Cancer

Date of compilation: 1/22/2019

Revised: 11/14/2023



Manufacturer Disclaimer: The information contained in this safety date sheet ("SDS") is based on sources, technical knowledge and current legislation. Furthermore, is based on data believed to be accurate; thus, the company does not assume any liability for its accuracy. The information provided herein cannot be considered a guarantee of the properties of this product and the same is simply a description of the security requirements. The use, occupational methodology and/or conditions for users of this product are not within our awareness or control. It is ultimately the responsibility of the user(s) to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information of this SDS only refers to this product, which should not be used for purposes other than those specified. Finally, the manner in which this product is used and whether there is any infringement of patents is the sole responsibility of the user(s).

Date of compilation: 1/22/2019 Revised: 11/14/2023 Version: 10 (Replaced 9)