



# Super Track™ ST-1383

## 100% Acrylic Asphalt Surface Protectant

**Description:**

**Super Track™** is a high performance, water-based, 100% acrylic latex coating designed to protect and prolongs the life of asphalt surfaces. Designed for heavy traffic.

**Meets Requirements for:**

MPI:	N/A
VOC Compliant (<50 g/L):	Yes
SCAQMD:	Pass
AIM & OTC:	Pass

**Product Advantages:**

- Protects against oil & water
- Holds asphalt together
- Excellent adhesion on traffic surfaces
- For use on concrete or asphaltic surfaces
- Heavy metal and lead free
- Excellent coverage
- Fast drying

**Uses:**

Super Track™ is ideal for interior or exterior surfaces such as asphalt, wood and concrete. Excellent for floor applications like driveways, decks, go-carts, running and bike tracks.

**Technical Data:**

Product Type:	100% Acrylic
Finish:	Egg Shell (9° - 15°) *Geometry 60°
Solids (%):	51 ± 2% by weight 34 ± 2% by volume
Weight/Gallon:	10.9 ± 0.05lbs. ( 4.7 ± 0.02kg.)
Colors:	Black
Drying Time:	To touch: 30-60 min. To recoat: 4-5 hrs. Foot traffic: 8-12 hrs. Final Cure: 24 hrs.
Coverage:	
Theoretical:	Up to 518 ft. <sup>2</sup> per gallon @ 1 mil
Recommended:	350-400 ft. <sup>2</sup> /gal. (32-37 m <sup>2</sup> /gal.) @ 1.6 dry mils, 4.6 wet mils
Can Sizes:	5 gallons can 1 gallon can
Thinning:	Is not recommended.
Flash Point:	Non-flammable
Viscosity:	93 - 100 KU's
VOC:	<50 g/L

Notice: The technical data contained herein are true and accurate to the best of our knowledge. Published technical data and instructions are subject to change without prior notice.

S.D.S.: Available upon request.

**Surface Preparation:**

All surfaces must be dry, clean, sound and free of contaminants such as dirt, grease, chalk, mildew, oil, rust, concrete curing agents, laitance, efflorescence, loose or badly cracked paint. Remove all contaminants by washing surfaces with an appropriate cleaner, sanding, scraping and/or using a pressure washing machine.

**Surface Application Recommendations:**

**Previously painted surfaces:** The surface must be clean and dry prior to painting. Remove dirt, grease and scrape off loose and scaling paint. Dull glossy surfaces by lightly sanding.

**Asphalt pavement surfaces:** The surface should be aged or must be weathered for at least 60 days for new surfaces, must be free of oils and other contaminants.

**Unpainted surfaces wood:** All pressure treated wood must be weathered at least 60 days prior to painting and moisture content should be under 16%.

**Concrete:** The surface must be clean and acid etched with muriatic acid and water following label directions and cautions prior to painting. Rinse thoroughly using clean water and let dry 24 hours or until completely dry.

**Method of Application:**

Stir gently. Apply liberally, roll out no more than a 10 ft. by 10 ft. area with a full 9 inch roller. Resists light foot traffic in 12 hours. Do not apply when surface or air temperature is below 50 °F (10 °C) or if rain is expected within 5 hours. Apply product with brush, roller or sprayer. Apply generously with a full brush or roller and avoid excessive brushing or spreading too thinly.

**Mixing and thinning:** Mix always thoroughly before application. Thinning is not recommended, if necessary use only 8oz. of water per gallon of this product.

**Brush:** Use a good quality nylon PA-1982 or polyester brush PA-1999.

**Roller:** Use a Lanco® All-Purpose 3/8" or thicker Nap Roller. Apply generously, but avoid excessive brushing or reworking of painted areas, do not apply or spread too thinly.

**Caution:** Harmful if swallowed. Contains acrylic resin. In case of eye contact, flush thoroughly with water. Do not rub eyes. In case of skin contact, flush area immediately with clean water. If swallowed, Do not induce vomiting. Consult a physician immediately. Use only with adequate ventilation. Adequate ventilation required when sanding or abrading the dried film. Always use (NIOSH/MSHA TC21C or equivalent.) Goggles are recommended while handling the product.

**Warning!** If you scrape, sand, or remove old paint, you may release lead dust. Lead is toxic. Exposure to lead dust can cause serious illness, such as brain damage, especially in children. Pregnant women should also avoid exposure. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead). Keep out reach of children. For chemical emergency call ChemTrec 1-800-424-9300.

