



Eco Gel Strip PR-114

Int/Ext Semi-Pasted Paint Remover without NMP

Description:

Eco Gel Strip is a powerful and safe semi-paste paint stripper. Ideal for vertical and horizontal surfaces due to its extremely fast drying, non-running type. Designed for interior and exterior. Ideal for interior use due to its none odor formula.

Product Advantages:

- For interior or exterior use
- Semi-pasted, non running formula
- Free of Methylene Chloride
- Free of NMP N Methyl Pyloridone
- Easy water clean-up
- Fast-acting
- Non-staining

Uses:

Designed for a fast-acting and quick removal of polyurethanes, enamels, lacquers, primers and clear coats over base coat systems from wood, metal, concrete and other surfaces. Do not use on plastic.

Surface Preparation:

All surfaces must be clean, dry and free of contaminants prior to apply this product.

Product Data:

Weight/Gallon:	8.55 ± 0.05lbs. (3.88 ± 0.02kg.)
Sizes:	1 gallon 1 quart
Viscosity:	Semi-Paste
Flash Point:	< 205°F (96°C) TCC

Notice: The technical data contained herein are true and accurate to the best of our knowledge. Published technical data and instructions are subject to change without prior notice.

S.D.S.: Available upon request.

Storage:

Protect from freezing; store in a cool, dry place at room temperature. Product must be used within one year of purchase.

Application Method:

For best results, follow these steps:

Shake well before using. Apply a thick coat (minimum 1/8") of Lanco® Eco Gel Strip to the entire surface. The thicker the coat of stripper applied, the more effective the stripping action. Brushing in one direction helps provide a thick, uniform coat.

For varnish, lacquer or shellac removal wait at least 20 minutes. To remove alkyd paints and polyurethanes wait 1-2 hours, depending on the number of coats to be stripped. If used indoors in a heavy coat, the stripper will remain active for up to 3 hours; although it may seem dry.

Remove finish with a putty knife or scraper. (This product will not raise the grain of the wood). On tough spots, reapply. Wait only 15 minutes and remove again. To achieve greater penetration of the product on the surface, you can use a polyethylene to wrap or cover the area to be removed. Wipe off with a paper towel or use water dipped rags. On wood, let dry thoroughly and sand before refinishing.

1. **Brushing:** Use a soft natural nylon brush, apply a heavy coat of Lanco® Super Safe Strip in one direction only. Let it stand for 15 to 30 minutes.

2. **Spraying:** Use a high-pressure spray gun.

3. **Dipping:** Dip the entire piece for a period of 15 to 30 minutes. Allow the remover to penetrate into the old finish and do the work for you.

Danger/Warning:

Do not store in heated areas or in strong sunlight.

Precautions: Use only in well ventilated areas. Ventilation should be enough for the limits of exposure to be less than those on the Material Safety Data Sheet. Eye irritation or dizziness are indications of over exposure. For more information refer to Lanco® Eco Gel Strip.

First aid: avoid prolonged or repeated breathing of vapor. High vapor concentrations may cause unconsciousness or even asphyxiation. Do not take internally. Swallowing may cause injury, illness or death. If swallowed do not induce vomiting; consult a physician immediately. Avoid prolonged or repeated contact with skin. Contact may cause skin irritation and dermatitis. Do not get in eyes. Keep out reach of children.

