



Toluene TO-100

Solvent for Oil-Based Lacquers and Enamels

Description:

Toluene TO-100 is a high-quality, slow evaporating solvent thinner for use with oil-based lacquers and enamels to promote flow and better application of the product.

Product Advantages:

- Medium evaporation
- High Quality
- Prevent moating
- Increase gloss finish

Uses:

Toluene TO-100 is used as a component of solvents in paint and lacquer industry and as an octane enhancing component of gasoline. It is used as a feedstock for a number of chemical syntheses, as raw material in the production of a polymers used to make nylon, plastic soda bottles and polyurethanes and in synthesis of organic chemicals, benzene and xylene.

Storage:

Protect from freezing; store in a cool, dry place at room temperature. Product must be used within one year of purchase.

Product Data:

Weight/Gallon:	7.52 ± 0.05lb. (3.41 ± 0.02kg.)
Sizes:	55 gallons 5 gallons
Viscosity:	Liquid
Flash Point:	154°F TCC

Notice: The technical data contained herein are true and accurate to the best of our knowledge. Published technical data and instructions are subject to change without prior notice.

S.D.S.: Available upon request.

Warning:

Prior to use refer to S.D.S. For safety data and summary of HMIS rating code. For S.D.S. Sheet, please visit www.lancopaints.com.

Use only in well ventilated area. Keep away from heat and open flame Avoid prolonged contact with skin and eyes- If swallowed, do not induce vomiting. Call physician immediately. Eyes - Flush with water for 15 minutes. Get prompt medical attention. KEEP away from heat, sparks, and open flame. Vapor is heavier than air. Prevent build up of vapors (open all windows and door) use only with cross ventilation. Extinguish all flames and pilot lights and turn off stoves, heaters, electric motors and eliminate all other sources of ignition (including static sparks) during use and until all vapors are gone. Keep container closed when not in use.

Hazard Statements:

Highly flammable liquid and vapor. Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment. May be fatal if swallowed and enters airways. Causes skin irritation. May cause drowsiness or dizziness. May cause damage to organs (central nervous system) through prolonged or repeated exposure. Suspected of damaging fertility or the unborn child.

Precautionary statements:

Keep away from heat, hot surfaces, sparks, open flames/hot surfaces. No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ ventilating/ lighting/ equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray. Wash skin thoroughly after handling. Avoid release to the environment. Wear protective gloves/ protective clothing/ eye protection/ face protection. If on skin (or hair): remove/ take off immediately all contaminated clothing. Rinse skin with water/ shower. If swallowed: immediately call a poison center or doctor-physician. Do not induce vomiting. If inhaled: remove victim to fresh air. In case of fire: use dry sand, dry chemical or alcohol-resistant foam to extinguish. Storage: store container tightly closed in well-ventilated place. Keep cool. Store locked up. Disposal: dispose of contents/ container in accordance with local/ regional/ national/ international regulations.

Keep out of the reach of children. For industrial use only.

