



## TECHNICAL DATA SHEET

# Acrylic Caulk (CC-756)

## 20 – year Acrylic Latex Sealant

### Description

A good quality latex caulk suitable for all interior and exterior applications where minimum joint movement is expected; adheres to most building materials and is easy to apply, tool and clean up.

### Product Advantages

- 100% paintable
- Moisture resistant
- Water cleanup
- Interior / exterior
- Twenty-year warranty
- All-purpose
- Mildew resistant
- Long-lasting

### Product Uses

Ideal to seal cracks around doors and window frames, baseboard trim and other areas where joint movement is minimal; excellent for sealing cracks in concrete, drywall and wood.

### Technical Data

**Solids:** 72.00 ± 1% by weight  
58.00 ± 1% by volume

**Weight / Gallon:** 2.73 ± 1 lb.

**Finish:** White

**Flash Point:** Non-Flammable

**Fire Rating:** Class A

**Viscosity:** 350,000 – 400,000 cps

**Drying Time:**  
Tack free: 15 minutes  
To coat with latex paint: 2 hours  
To coat with alkyd paint: 24 hours

**Theoretical Coverage:**  
Approximately 34 linear feet of 1/4" bead per 10.1- oz. cartridge.

### Application

- (1) Apply at temperatures above 40°F (5°C) and when no precipitation is expected within 72 hours.
- (2) Cut nozzle to desired bead size (1/4" is recommended).
- (3) Hold gun at 45° angle to the seam and push LANCO® Acrylic Caulk CC-756 ahead of nozzle, applying uniform pressure to the trigger in order to get a smooth bead.
- (4) Tool within 15 minutes with finger or damp smooth sponge.
- (5) Limit joint size to be filled to approximately 1/4" (0.6 cm) deep by 1/4" (0.6 cm) wide. If depth of joint exceeds 3/8", use polyethylene foam or oakum as backup filler.
- (6) Wipe away excess with a damp cloth before surface skins.

**CLEANUP:** Clean all equipment immediately after use with warm soapy water. Completely flush all spray equipment with this solution.

Member of  
Blanco Group



### CORPORATE OFFICE & MANUFACTURING PLANT

600 Mid Florida Drive Airport Industrial Park of Orlando, Florida 32824  
Toll Free. (866) 447-2400 Tel. (407) 240-4000 Fax (407) 240-4046  
Visit [lancoproducts.com](http://lancoproducts.com)

**Surface Preparation**

All surfaces must be dry, clean and free of contaminants such as dirt, grease, chalk, mildew, oil, rust, loose or badly cracked paint.

**MILDEWED SURFACES:** Any existing mildew on the surface must be killed and removed prior to the application of this product. Any mildew not removed may continue to grow through the new finish. Using a long-handled brush, scrub mildewed surfaces with a mixture of one quart of household bleach and three quarts of warm water. Allow the solution to remain on the surface for 10 minutes. Rinse thoroughly with water and allow the surface to dry before painting. Wear protective eyewear, waterproof gloves, and protective clothing. Quickly wash off any of the mixture that comes in contact with your skin. Do not add detergents or ammonia to the bleach / water solution.

**PREVIOUSLY CAULKED SURFACES:** It is critical to remove as much old sealant as possible before applying new caulk, especially if it is cracked, eroded or pulled away from the joint.

**STORAGE:** Protect from freezing; store in a cool, dry place at room temperature. Product must be used within one year of purchase.

**MILDEWED SURFACES:** Any existing mildew on the surface must be killed and removed prior to the application of this product. Any mildew not removed may continue to grow through the new finish. Using a long-handled brush, scrub mildewed surfaces with a mixture of one quart of household bleach and three quarts of warm water. Allow the solution to remain on the surface for 10 minutes. Rinse thoroughly with water and allow the surface to dry before painting. Wear protective eyewear, waterproof gloves, and protective clothing. Quickly wash off any of the mixture that comes in contact with your skin. Do not add detergents or ammonia to the bleach / water solution.

**General Information**

**Drying Time:** Wait two hours before painting with latex paint or 24 hours if using alkyd (oil based) paint.

**Cleanup:** Clean up excess with damp cloth before caulk cures.

**LIMITED WARRANTY:** Satisfaction guaranteed for 20 years. If product cracks, peels or separates while you own your home during period of guarantee, when used as directed, return sales receipt and used container to for product replacement. The seller will not accept liability for more than product replacement or purchase price.

**CAUTION:** Harmful if swallowed. Contains Acrylic Resin. In case of eye contact, flush thoroughly with water. Do not rub eyes. In case of skin contact, flush area immediately with clean water. If swallowed, do not induce vomiting. Consult a physician immediately. Use only with adequate ventilation. Adequate ventilation required when sanding or abrading the dried film. Always use NIOSH/MSHA TC21C or equivalent.) Goggles are recommended while handling the product. Keep out of reach of children.

**WARNING!** If you scrape, sand, or remove old paint, you may release lead dust. Lead is toxic. Exposure to lead dust can cause serious illness, such as brain damage, especially in children. Pregnant women should also avoid exposure. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead). For chemical emergency call ChemTrec 1-800-424-9300. PROTECT FROM FREEZING.

S.D.S.: Available upon request.

The information presented on this Technical Data Sheet is based on testing conducted by Lanco® Paints & Coatings. No guarantee of accuracy, comprehensiveness, or performance is given or implied. Information and recommendations are subject to change dependent on surface conditions (substrate), weather and method of application. Please consult with a Lanco Representative or visit [www.lancopaints.com](http://www.lancopaints.com) for complete, up-to-date technical information.

Member of  
Blanco Group

**CORPORATE OFFICE & MANUFACTURING PLANT**

600 Mid Florida Drive Airport Industrial Park of Orlando, Florida 32824  
Toll Free. (866) 447-2400 Tel. (407) 240-4000 Fax (407) 240-4046  
Visit [lancoproducts.com](http://lancoproducts.com)