



# Acrylic Retarder SR-110

## Slow Evaporating Retarder

### Description:

**Acrylic Retarder SR-110** Is a high-quality, slow-evaporating solvent for use with acrylic and nitrocellulose lacquers to promote flow and eliminate blushing in hot or humid weather.

### Product Advantages:

- Medium evaporation
- High quality
- Prevent moating
- Increase gloss finish

### Uses:

Acrylic Retarder SR-110 Designed for to promote flow and eliminate blushing in hot or humid weather when using acrylic and nitrocellulose lacquers.

### Storage Information:

Protect from freezing; store in a cool, dry place at room temperature. Product must be used within one year of purchase.

### Product Data:

Weight/Gallon:	7.52 ± 0.05 lb. (3.41 ± 0.02 kg.)
Sizes:	55 gallons 5 gallons 1 gallon 1 quart
Viscosity:	Liquid
Flash Point:	154°F TCC

Notice: The technical data contained herein are true and accurate to the best of our knowledge. Published technical data and instructions are subject to change without prior notice.

S.D.S.: Available upon request.

### Warning:

Prior to use refer to S.D.S. For safety data and summary of HMIS rating code. For S.D.S. Sheet, please visit [www.lancopaints.com](http://www.lancopaints.com).

Contains toluene, acetone and methyl alcohol. Cannot be made non-poisonous.

Use only in well ventilated area. Keep away from heat and open flame Avoid prolonged contact with skin and eyes- If swallowed, do not induce vomiting. Call physician immediately. Eyes - Flush with water for 15 minutes. Get prompt medical attention. Keep away from heat, sparks, and open flame. Vapor is heavier than air. Prevent build up of vapors (open all windows and door) use only with cross ventilation. Extinguish all flames and pilot lights and turn off stoves, heaters, electric motors and eliminate all other sources of ignition (including static sparks) during use and until all vapors are gone. Keep container closed when not in use.

Use only with adequate ventilation. Ventilation must be sufficient to limit exposure below M.S.D.S. limits. Eye irritation and dizziness are indications of over exposure, Refer to Lanco® material safety data sheet. Avoid prolonged or repeated breathing of vapor, it is important to use adequate ventilation as high vapor concentration may cause unconsciousness or even asphyxiation. Do not take internally. Swallowing may cause injury, illness or death.

Avoid prolonged or repeated contact with skin. Contact may cause skin irritation and dermatitis. Do not get in eyes. Will cause discomfort and irritation. Do no eat, drink or smoke in work areas.

**Notice:** Reports have associated repeated and prolonged occupational over exposure to solvents with permanent brain and nervous system damage, peripheral nervous tissue damage and liver abnormalities. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

**Warning!** May be harmful if inhaled or swallowed. Skin and eye irritant. Always wear respiratory protection (NIOSH MSHA TC 23c or equivalent). Vapors harmful.

Inhalation overexposure - Remove patient to fresh air. If breathing stops, give artificial respiration. Call a physician  
Swallowing - Seek medical attention immediately. Do not induce vomiting.  
Skin contact - Remove contaminated clothing and shoes. Wash skin with warm water and soap. Wash clothes and air out shoes.

Consult material safety data sheet for additional information. Keep out of the reach of children.

