

SAFETY DATA SHEET Complete Zero Interior Latex Semi-Gloss White Pastel

According to Appendix D, OSHA Hazard Communication Standard 29 CFR §1910.1200

1. Identification	
Product identifier	
Product name	Complete Zero Interior Latex Semi-Gloss White Pastel
Product number	JB-490
Recommended use of the chemical and restrictions on use	
Application	Paint.
Uses advised against	No specific uses advised against are identified.
Details of the supplier of the safety data sheet	
Supplier	See Manufacturer
Contact Person	Milton Arnold
Manufacturer	LANCO & HARRIS CORP. 600 MID FLORIDA DRIVE ORLANDO, FL. 32824 407-240-4000 www.lancopaints.com
Emergency telephone number	
Emergency telephone	Office 407-240-4000 9 – 5 eastern M_F Chemtrec 24 Hours: 800-424-9300
2. Hazard(s) identification	
Classification of the substanc	e or mixture
Physical hazards	Not Classified
Health hazards	Carc. 2 - H351
Environmental hazards	Not Classified
Label elements	
Pictogram	
Signal word	Warning
Hazard statements	H351 Suspected of causing cancer.

Precautionary statements	 P201 Obtain special instructions before use. P202 Do not handle until all safety precautions have been read and understood. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. P308+P313 If exposed or concerned: Get medical advice/ attention. P405 Store locked up. P501 Dispose of contents/ container in accordance with national regulations.
Contains	Titanium dioxide

Other hazards

This product does not contain any substances classified as PBT or vPvB.

3. Composition/information on ingredients

Mixtures Titanium dioxide 10-30% CAS number: 13463-67-7 Classification Carc. 2 - H351 Silicon dioxide 1-5% CAS number: 7631-86-9 Classification Not Classified Aluminum hydroxide <1% CAS number: 21645-51-2 Classification Not Classified Zirconium(IV) oxide <1% CAS number: 1314-23-4 Classification Not Classified

The full text for all hazard statements is displayed in Section 16.

Composition comments

* The exact percentage withheld as a trade secret in accordance with 29 CFR 1910.1200. The highly refined mineral oil contains <3% (w/w) DMSO-extract, according to IP346.

4. First-aid measures

Description of first aid measures	
General information	Get medical attention if any discomfort continues. Show this Safety Data Sheet to the medical personnel.
Inhalation	Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Loosen tight clothing such as collar, tie or belt. Get medical attention if symptoms are severe or persist.
Ingestion	Rinse mouth thoroughly with water. Get medical advice/attention if you feel unwell. Do not induce vomiting unless under the direction of medical personnel.
Skin Contact	Rinse with water.
Eye contact	Rinse with water. Get medical attention if any discomfort continues.
Protection of first aiders	First aid personnel should wear appropriate protective equipment during any rescue.
Most important symptoms and	l effects, both acute and delayed
General information	The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
Inhalation	Prolonged or repeated exposure may cause the following adverse effects: Suspected of causing cancer.
Ingestion	Prolonged or repeated exposure may cause the following adverse effects: Suspected of causing cancer.
Skin contact	Prolonged or repeated exposure may cause the following adverse effects: Suspected of causing cancer.
Eye contact	No specific symptoms known. May be slightly irritating to eyes.
Indication of immediate medic	al attention and special treatment needed
Notes for the doctor	Treat symptomatically.
5. Fire-fighting measures	
Extinguishing media	
Suitable extinguishing media	The product is not flammable. Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog. Use fire-extinguishing media suitable for the surrounding fire.
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Special hazards arising from t	he substance or mixture
Specific hazards	Containers can burst violently or explode when heated, due to excessive pressure build-up.
Hazardous combustion products	Thermal decomposition or combustion products may include the following substances: Harmful gases or vapors.
Advice for firefighters	
Protective actions during firefighting	Avoid breathing fire gases or vapors. Evacuate area. Keep upwind to avoid inhalation of gases, vapors, fumes and smoke. Ventilate closed spaces before entering them. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. If a leak or spill has not ignited, use water spray to disperse vapors and protect men stopping the leak. Control run-off water by containing and keeping it out of sewers and watercourses. If risk of water pollution occurs, notify appropriate authorities.

Description of first aid measures

Special protective equipment for firefighters	Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Standard Firefighter's clothing including helmets, protective boots and gloves will provide a basic level of protection for chemical incidents.
6. Accidental release measure	S
Personal precautions, protectiv	ve equipment and emergency procedures
Personal precautions	Wear protective clothing as described in Section 8 of this safety data sheet. No action shall be taken without appropriate training or involving any personal risk.
Environmental precautions	
Environmental precautions	Avoid discharge into drains or watercourses or onto the ground. Avoid discharge to the aquatic environment.
Methods and material for conta	ainment and cleaning up
Methods for cleaning up	Wear protective clothing as described in Section 8 of this safety data sheet. Clear up spills immediately and dispose of waste safely. Small Spillages: Collect spillage. Large Spillages: Absorb spillage with non-combustible, absorbent material. The contaminated absorbent may pose the same hazard as the spilled material. Collect and place in suitable waste disposal containers and seal securely. Label the containers containing waste and contaminated materials and remove from the area as soon as possible. Flush contaminated area with plenty of water. Wash thoroughly after dealing with a spillage. For waste disposal, see Section 13.
Reference to other sections	For personal protection, see Section 8. See Section 11 for additional information on health hazards. See Section 12 for additional information on ecological hazards. For waste disposal, see Section 13.
7. Handling and storage	
Precautions for safe handling	
Usage precautions	Read and follow manufacturer's recommendations. Wear protective clothing as described in Section 8 of this safety data sheet. Keep away from food, drink and animal feeding stuffs. Handle all packages and containers carefully to minimize spills. Keep container tightly sealed when not in use. Avoid the formation of mists. May cause cancer. Do not handle until all safety precautions have been read and understood. Do not handle broken packages without protective equipment. Do not reuse empty containers.
Advice on general occupational hygiene	Wash promptly if skin becomes contaminated. Take off contaminated clothing and wash before reuse. Wash contaminated clothing before reuse.
Conditions for safe storage, in	cluding any incompatibilities
Storage precautions	Store locked up. Keep only in the original container. Keep container tightly closed, in a cool, well ventilated place. Keep containers upright. Protect containers from damage.
Storage class	Chemical storage.
Specific end uses(s)	
Specific end use(s)	The identified uses for this product are detailed in Section 1.2.
8. Exposure Controls/personal	protection
Control parameters Occupational exposure limits	

Titanium dioxide

Long-term exposure limit (8-hour TWA): ACGIH 10 mg/m³

Long-term exposure limit (8-hour TWA): OSHA 15 mg/m³ total dust

Silicon dioxide

A4

Long-term exposure limit (8-hour TWA): OSHA 0.8 mg/m³

Aluminum hydroxide

Long-term exposure limit (8-hour TWA): ACGIH 1 mg/m³ respirable fraction

Zirconium(IV) oxide

Long-term exposure limit (8-hour TWA): OSHA 5 mg/m³ Long-term exposure limit (8-hour TWA): ACGIH Threshold Limit Values (TLV) 5 mg/m³ Short-term exposure limit (15-minute): ACGIH 10 mg/m³

Titanium dioxide (CAS: 13463-67-7)

Immediate danger to life and health	5000 mg/m³
	Silicon dioxide (CAS: 7631-86-9)
Immediate danger to life and health	3000 mg/m³

Immediate danger to life and health

Exposure controls

Protective equipment



Appropriate engineering controls

Provide adequate general and local exhaust ventilation. Ensure the ventilation system is regularly maintained and tested. Good general ventilation should be adequate to control worker exposure to airborne contaminants. Observe any occupational exposure limits for the product or ingredients.

Eye/face protection Unless the assessment indica

Unless the assessment indicates a higher degree of protection is required, the following protection should be worn: Tight-fitting safety glasses.

Hand protection	Wear protective gloves. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. To protect hands from chemicals, gloves should comply with OSHA 1910.138 and be demonstrated to be impervious to the chemical and resist degradation. Considering the data specified by the glove manufacturer, check during use that the gloves are retaining their protective properties and change them as soon as any deterioration is detected. Frequent changes are recommended.
Other skin and body protection	Wear appropriate clothing to prevent any possibility of skin contact.
Hygiene measures	Wash hands thoroughly after handling. Wash at the end of each work shift and before eating, smoking and using the toilet. Do not eat, drink or smoke when using this product.
Respiratory protection	Ensure all respiratory protective equipment is suitable for its intended use and is NIOSH approved. Check that the respirator fits tightly and the filter is changed regularly. Gas and combination filter cartridges should comply with OSHA 1910.134. Full face mask respirators with replaceable filter cartridges should comply with OSHA 1910.134. Half mask and quarter mask respirators with replaceable filter cartridges should comply with OSHA 1910.134.
Environmental exposure controls	Keep container tightly sealed when not in use. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

9. Physical and Chemical Properties

Information on basic physical and chemical properties

Information on basic physical	information on basic physical and chemical properties	
Appearance	Liquid.	
Color	Various colors.	
Odor	Mild.	
Odor threshold	Not available.	
рН	pH (concentrated solution): 8.2 - 9.5	
Melting point	Not available.	
Initial boiling point and range	Not available.	
Flash point	Not applicable.	
Evaporation rate	Not available.	
Upper/lower flammability or explosive limits	Not available.	
Vapor pressure	Not available.	
Vapor density	Not available.	
Relative density	Lighter than air.	
Solubility(ies)	Soluble in water.	
Partition coefficient	Not available.	
Auto-ignition temperature	Not available.	
Decomposition Temperature	Not available.	
Viscosity	Not available.	

Explosive properties	Not applicable.
Specific Gravity (H2O = 1)	1.267
Oxidizing properties	Not available.
Coating v.o.c.	0 g/l
Material v.o.c.	0 g/l
10. Stability and reactivity	
Reactivity	There are no known reactivity hazards associated with this product.
Stability	Stable at normal ambient temperatures and when used as recommended. Stable under the prescribed storage conditions.
Possibility of hazardous reactions	No potentially hazardous reactions known.
Conditions to avoid	There are no known conditions that are likely to result in a hazardous situation.
Materials to avoid	No specific material or group of materials is likely to react with the product to produce a hazardous situation.
Hazardous decomposition products	Does not decompose when used and stored as recommended. Thermal decomposition or combustion products may include the following substances: Harmful gases or vapors.
11. Toxicological information	
Information on toxicological ef	fects
<u>Acute toxicity - oral</u> Notes (oral LD₅₀)	Based on available data the classification criteria are not met.
Acute toxicity - dermal Notes (dermal LD₅₀)	Based on available data the classification criteria are not met.
Acute toxicity - inhalation Notes (inhalation LC ₅₀)	Based on available data the classification criteria are not met.
Skin corrosion/irritation Animal data	Based on available data the classification criteria are not met.
Serious eye damage/irritation Serious eye damage/irritation	Based on available data the classification criteria are not met.
Respiratory sensitization Respiratory sensitization	Based on available data the classification criteria are not met.
Skin sensitization Skin sensitization	Based on available data the classification criteria are not met.
Germ cell mutagenicity Genotoxicity - in vitro	Based on available data the classification criteria are not met.
Carcinogenicity Carcinogenicity	Suspected of causing cancer.

IARC carcinogenicity	Contains a substance/a group of substances which may cause cancer. IARC Group 2B Possible Carcinogen to humans.
Reproductive toxicity	
Reproductive toxicity - fertility	Based on available data the classification criteria are not met.
Reproductive toxicity - development	Based on available data the classification criteria are not met.
Specific target organ toxicity -	single exposure
STOT - single exposure	Not classified as a specific target organ toxicant after a single exposure.
Specific target organ toxicity -	repeated exposure
STOT - repeated exposure	Not classified as a specific target organ toxicant after repeated exposure.
Aspiration hazard Aspiration hazard	Based on available data the classification criteria are not met.
General information	May cause cancer after repeated exposure. Risk of cancer depends on duration and level of exposure. The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
Inhalation	No specific symptoms known.
Ingestion	No specific symptoms known.
Skin Contact	No specific symptoms known.
Eye contact	No specific symptoms known.
Route of entry	Ingestion Inhalation Skin and/or eye contact
Target Organs	No specific target organs known.
12. Ecological Information	
Ecotoxicity	Not regarded as dangerous for the environment. However, large or frequent spills may have hazardous effects on the environment.
Toxicity	
Toxicity	Based on available data the classification criteria are not met.
Persistence and degradability	
Persistence and degradability	The degradability of the product is not known.
Bioaccumulative potential	
Bio-Accumulative Potential	No data available on bioaccumulation.
Partition coefficient	Not available.
Mobility in soil	
Mobility	No data available.
Results of PBT and vPvB asse	essment
Other adverse effects	
Other adverse effects	None known.
13. Disposal considerations	

Waste treatment methods General information The generation of waste should be minimized or avoided wherever possible. Reuse or recycle products wherever possible. This material and its container must be disposed of in a safe way. When handling waste, the safety precautions applying to handling of the product should be considered. Care should be taken when handling emptied containers that have not been thoroughly cleaned or rinsed out. Empty containers or liners may retain some product residues and hence be potentially hazardous. **Disposal methods** Dispose of surplus products and those that cannot be recycled via a licensed waste disposal contractor. Waste, residues, empty containers, discarded work clothes and contaminated cleaning materials should be collected in designated containers, labeled with their contents. Incineration or landfill should only be considered when recycling is not feasible. 14. Transport information General The product is not covered by international regulations on the transport of dangerous goods (IMDG, IATA, DOT). **UN Number** Not applicable. UN proper shipping name Not applicable. Transport hazard class(es) Not regulated. Packing group **Environmental hazards Environmentally Hazardous Substance** No. Special precautions for user Not applicable. 15. Regulatory information International Regulations **US State Regulations** California Proposition 65 Carcinogens and Reproductive Toxins Contains components known to the State of California to cause cancer. Silicon dioxide Known to the State of California to cause cancer. Titanium dioxide Known to the State of California to cause cancer. Massachusetts "Right To Know" List The following ingredients are listed or exempt: Distillates (petroleum), solvent-dewaxed light paraffinic Present. Zirconium(IV) oxide

Present.

Silicon dioxide Present.

Titanium dioxide Present.

Rhode Island "Right To Know" List

The following ingredients are listed or exempt:

Titanium dioxide Present.

Minnesota "Right To Know" List The following ingredients are listed or exempt:

Silicon dioxide Present.

Titanium dioxide Present.

New Jersey "Right To Know" List The following ingredients are listed or exempt:

2,2-dibromo-2-cyanoacetamide Present.

2-Bromo-2-(bromomethyl)pentanedinitrile Present.

Titanium dioxide Present.

Pennsylvania "Right To Know" List

The following ingredients are listed or exempt:

Silicon dioxide Present.

Titanium dioxide Present.

Inventories

Canada - DSL/NDSL Present.

US - TSCA Present.

16. Other information	
Training advice Revision	Only trained personnel should use this material.
comments Issued by	This is first issue.
Revision date	Milton Arnold
Revision	03/01/2017
SDS status	1
Hazard statements in full	Approved.
End of SDS	H350 May cause cancer. H351 Suspected of causing cancer. H372 Causes damage to organs (Lungs) through prolonged or repeated exposure. XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.